

Guidelines For: PR-1 Average Interval Offered

C2C Guideline:

Definition:	POTS and Specials: "Average Interval Offered" is also known as the "average appointed interval". The average number of business days between order application date and committed due date (appointment date). The application date is the date that a valid service request is received. All orders received after the "cut-off" time shown in the BA Product Interval Guide are considered received the next business day at 8:00 AM. The "cut-off" time for a CLEC order for a service will be the same as the "cut-off" time for a BA Retail order for the analogous BA Retail service. Complex Orders include: Two wire digital services (Basic Rate ISDN) and Two Wire xDSL services. Specials Orders include: All Designed circuits, 4 wire circuits (including Primary Rate ISDN and 4 wire xDSL services), all DS0, DS1 and DS3 circuits. EEL and IOF will be reported separately. Trunks: The average number of business days between date of receipt of a valid Access Service Request ("ASR") (received date restarted for each supplement) (application date) and due date committed to on firm order confirmation.
Performance Standard:	Resale: Parity with BA Retail, UNE: Parity with BA Retail, Trunks: Parity with BA Retail.
Exclusions:	BA Test Orders. Orders where customers request a due date that is greater than or less than the standard available Bell Atlantic Administrative Orders(footnote 22) with invalid intervals (Negative Intervals or intervals over 200 business days - indicative of typographical error). Additional Segments (pages or sections on individual orders) on orders (parts of a whole order are included in the whole). Suspend for non-payment and associated restore orders.(footnote 23)
Report Dimensions:	BA Retail CLEC Aggregate CLEC Specific BA Affiliate Aggregate BA Affiliate Specific
Geography:	POTS, Complex, 2 Wire Digital Services, and 2 Wire xDSL Services: Southern, Eastern Shore, Raritan, Suburban, Hudson-Bergen Specials, IOF and EEL: State trunks: State

22 BA Administrative Orders - See Glossary

23 See Glossary.

RESALE (PROVISIONING)

Report Labels: PR-1-01-2110 POTS - Business

Parity with VZ Retail

Guidelines: PR-1 - Average Interval Offered

Average Interval Offered – Total No Dispatch

Result: (Numerator / Denominator)**Denominator:**

Count of orders without an outside dispatch in Product Groups

Numerator:

Sum of committed due date less application date for Orders without an outside dispatch in Product Groups

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RSPB&
      AND &Exclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and
((INWARD_QTY>=0 or CHNG_QTY>=0) and OUT_QTY=0) or
((INWARD_QTY>0 or CHNG_QTY>0)and OUT_QTY>0)) or
(TYPE = 'R' and RESELLER_ACT='I' and APPINTV <= 2))
      AND STATUS in &STATUSC&
      AND &PROJECT&
      AND
      decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND (ATC IN ('W')or(TYPE = 'R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
SUM(APPINTV)
WHERE STATE = '&ST&'
      AND &RSPB&
      AND &Exclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and
((INWARD_QTY>=0 or CHNG_QTY>=0) and OUT_QTY=0) or
((INWARD_QTY>0 or CHNG_QTY>0)and OUT_QTY>0)) or
(TYPE = 'R' and RESELLER_ACT='I' and APPINTV <= 2))
      AND STATUS in &STATUSC&
      AND &PROJECT&
      AND
      decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND (ATC IN ('W')or(TYPE = 'R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPB&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
      decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND ATC IN ('W')
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
SUM(APPINTV)
WHERE STATE = '&ST&'
      AND &RTPB&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
      decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND ATC IN ('W')
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

RESALE (PROVISIONING)

Report Labels: PR-1-01-2120 POTS - Residence

Parity with VZ Retail

Guidelines: PR-1 - Average Interval Offered

Average Interval Offered – Total No Dispatch

Result: (Numerator / Denominator)**Denominator:**

Count of orders without an outside dispatch in Product Groups

Numerator:

Sum of committed due date less application date for Orders without an outside dispatch in Product Groups

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RSPR&
      AND &Exclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and
((INWARD_QTY>=0 or CHNG_QTY>=0) and OUT_QTY=0) or
((INWARD_QTY>0 or CHNG_QTY>0)and OUT_QTY>0)) or
(TYPE = 'R' and RESELLER_ACT='I' and APPINTV <= 2))
      AND STATUS in &STATUSC&
      AND &PROJECT&
      AND
      decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND (ATC IN ('W')or(TYPE = 'R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Numerator

```

SELECT
SUM(APPINTV)
WHERE STATE = '&ST&'
      AND &RSPR&
      AND &Exclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and
((INWARD_QTY>=0 or CHNG_QTY>=0) and OUT_QTY=0) or
((INWARD_QTY>0 or CHNG_QTY>0)and OUT_QTY>0)) or
(TYPE = 'R' and RESELLER_ACT='I' and APPINTV <= 2))
      AND STATUS in &STATUSC&
      AND &PROJECT&
      AND
      decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND (ATC IN ('W')or(TYPE = 'R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPR&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
      decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND ATC IN ('W')
      AND &PROJECT&
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN ('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Numerator

```

SELECT
SUM(APPINTV)
WHERE STATE = '&ST&'
      AND &RTPR&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
      decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND ATC IN ('W')
      AND &PROJECT&
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN ('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

RESALE (PROVISIONING)

Report Labels: PR-1-01-2200 Special Services - Provisioning

Parity with VZ Retail

Guidelines: PR-1 - Average Interval Offered

Average Interval Offered – Total No Dispatch

Result: (Numerator / Denominator)**Denominator:**

Count of orders without an outside dispatch in Product Groups

Numerator:

Sum of committed due date less application date for Orders without an outside dispatch in Product Groups

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RSSS&
      AND &Exclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND STATUS in &STATUSC&
AND &PROJECT&
      AND
      decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
SUM(APPINTV)
WHERE STATE = '&ST&'
      AND &RSSS&
      AND &Exclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0
or INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0
or INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND STATUS in &STATUSC&
AND &PROJECT&
      AND
      decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTSS&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
      decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND ATC IN ('W')
AND &PROJECT&
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
SUM(APPINTV)
WHERE STATE = '&ST&'
      AND &RTSS&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
      decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND ATC IN ('W')
AND &PROJECT&
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```


RESALE (PROVISIONING)

Report Labels: PR-1-01-2341

Complex Services - 2 Wire Digital

Parity with VZ Retail

Guidelines: PR-1 - Average Interval Offered

Average Interval Offered – Total No Dispatch

Result: (Numerator / Denominator)**Denominator:**

Count of orders without an outside dispatch in Product Groups

Numerator:

Sum of committed due date less application date for Orders without an outside dispatch in Product Groups

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RSPI&
      AND &Exclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and
((INWARD_QTY>=0 or CHNG_QTY>=0) and OUT_QTY=0) or
((INWARD_QTY>0 or CHNG_QTY>0)and OUT_QTY>0)) or
(TYPE = 'R' and RESELLER_ACT='I' and APPINTV <= 2))
      AND STATUS in &STATUSC&
and &PROJECT&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND (ATC IN ('W')or(TYPE = 'R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
SUM(APPINTV)
WHERE STATE = '&ST&'
      AND &RSPI&
      AND &Exclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and
((INWARD_QTY>=0 or CHNG_QTY>=0) and OUT_QTY=0) or
((INWARD_QTY>0 or CHNG_QTY>0)and OUT_QTY>0)) or
(TYPE = 'R' and RESELLER_ACT='I' and APPINTV <= 2))
      AND STATUS in &STATUSC&
and &PROJECT&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND (ATC IN ('W')or(TYPE = 'R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPI&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND ATC IN ('W')
AND &PROJECT&
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
SUM(APPINTV)
WHERE STATE = '&ST&'
      AND &RTPI&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0
or INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0
or INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND ATC IN ('W')
AND &PROJECT&
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```


RESALE (PROVISIONING)

Report Labels: PR-1-01-2342 Complex Services - 2 Wire xDSL

Parity with VZ Retail

Guidelines: PR-1 - Average Interval Offered

Average Interval Offered – Total No Dispatch

Result: (Numerator / Denominator)**Denominator:**

Count of orders without an outside dispatch in Product Groups

Numerator:

Sum of committed due date less application date for Orders without an outside dispatch in Product Groups

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RSPD&
      AND &Exclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and
((INWARD_QTY>=0 or CHNG_QTY>=0) and OUT_QTY=0) or
((INWARD_QTY>0 or CHNG_QTY>0)and OUT_QTY>0)) or
(TYPE ='R' and RESELLER_ACT='I' and APPINTV <= 2))
      AND STATUS in &STATUSC&
      AND &PROJECT&
      AND
      decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Numerator

```

SELECT
SUM(APPINTV)
WHERE STATE = '&ST&'
      AND &RSPD&
      AND &Exclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and
((INWARD_QTY>=0 or CHNG_QTY>=0) and OUT_QTY=0) or
((INWARD_QTY>0 or CHNG_QTY>0)and OUT_QTY>0)) or
(TYPE ='R' and RESELLER_ACT='I' and APPINTV <= 2))
      AND STATUS in &STATUSC&
      AND &PROJECT&
      AND
      decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPD&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
      decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND ATC IN ('W')
      AND &PROJECT&
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Numerator

```

SELECT
SUM(APPINTV)
WHERE STATE = '&ST&'
      AND &RTPD&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
      decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND ATC IN ('W')
      AND &PROJECT&
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```


UNE (Provisioning)

Report Labels: PR-1-01-3111 POTS - Provisioning

Parity with VZ Retail

Guidelines: PR-1 - Average Interval Offered

Average Interval Offered – Total No Dispatch - Hot Cut Loop

Result: (Numerator / Denominator)**Denominator:**

Count of orders without an outside dispatch in Product Groups

Numerator:

Sum of committed due date less application date for Orders without an outside dispatch in Product Groups

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &SOUNPSLH&
      AND &Exclusions&
      AND (TYPE IN ('N','T') or (TYPE IN 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      and ATC in ('W')
      AND &PROJECT&
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Numerator

```

SELECT
SUM(APPINTV)
WHERE STATE = '&ST&'
      AND &SOUNPSLH&
      AND &Exclusions&
      AND (TYPE IN ('N','T') or (TYPE IN 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      and ATC in ('W')
      AND &PROJECT&
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPB&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE IN 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND ATC IN ('W')
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Numerator

```

SELECT
SUM(APPINTV)
WHERE STATE = '&ST&'
      AND &RTPB&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE IN 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND ATC IN ('W')
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

UNE (Provisioning)

Report Labels: PR-1-01-3122 POTS - Provisioning

Parity with VZ Retail

Guidelines: PR-1 - Average Interval Offered

Average Interval Offered – Total No Dispatch - Other (Switch & INP)

Result: (Numerator / Denominator)**Denominator:**

Count of orders without an outside dispatch in Product Groups

Numerator:

Sum of committed due date less application date for Orders without an outside dispatch in Product Groups

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &SOUNPSO&
      AND &Exclusions&
      AND (TYPE IN ('N','T') or (TYPE IN 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND ATC IN ('W')
      AND &PROJECT&
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
SUM(APPINTV)
WHERE STATE = '&ST&'
      AND &SOUNPSO&
      AND &Exclusions&
      AND (TYPE IN ('N','T') or (TYPE IN 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND ATC IN ('W')
      AND &PROJECT&
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPB&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE IN 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND ATC IN ('W')
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
SUM(APPINTV)
WHERE STATE = '&ST&'
      AND &RTPB&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE IN 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND ATC IN ('W')
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

UNE (Provisioning)

Report Labels: PR-1-01-3140

POTS - Provisioning

Parity with VZ Retail

Guidelines: PR-1 - Average Interval Offered

Average Interval Offered – Total No Dispatch - Platform

Result: (Numerator / Denominator)**Denominator:**

Count of orders without an outside dispatch in Product Groups

Numerator:

Sum of committed due date less application date for Orders without an outside dispatch in Product Groups

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &SOUNPSP&
      AND &Exclusions&
      AND STATUS in &STATUSC&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_NUM_DO)=0
      AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND CMPINTV BETWEEN 0 AND 200
      AND (
(ATC IN ('W') AND APPINTV between 0 and 200 AND (TYPE IN
('N','T') or (TYPE in 'C' and (OUT_QTY=0 or INWARD_QTY>0 or
CHNG_QTY>0) and (OUTWARD_CKL=0 or INWARD_CKL>0 or
CHNG_CKL>0))))
or (type in ('R') and PON is not null and APPINTV between 0 and
2) )

```

```

SELECT
SUM(APPINTV)
WHERE STATE = '&ST&'
      AND &SOUNPSP&
      AND &Exclusions&
      AND STATUS in &STATUSC&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_NUM_DO)=0
      AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND CMPINTV BETWEEN 0 AND 200
      AND (
(ATC IN ('W') AND APPINTV between 0 and 200 AND (TYPE IN
('N','T') or (TYPE in 'C' and (OUT_QTY=0 or INWARD_QTY>0 or
CHNG_QTY>0) and (OUTWARD_CKL=0 or INWARD_CKL>0 or
CHNG_CKL>0))))
or (type in ('R') and PON is not null and APPINTV between 0 and
2) )

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPB&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_NUM_DO)=0
      AND ATC IN ('W')
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
SUM(APPINTV)
WHERE STATE = '&ST&'
      AND &RTPB&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_NUM_DO)=0
      AND ATC IN ('W')
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

UNE (Provisioning)

Report Labels: PR-1-01-3200

Special Services Provisioning

Parity with VZ Retail

Guidelines: PR-1 - Average Interval Offered

Average Interval Offered – Total No Dispatch

Result: (Numerator / Denominator)**Denominator:**

Count of orders without an outside dispatch in Product Groups

Numerator:

Sum of committed due date less application date for Orders without an outside dispatch in Product Groups

Filtered output file: ASR-UNE-SPECIAL

For the details on the above out put filtered file layout refer to File Appendix: 7 File Type: Excel

Denominator

```
SELECT
COUNT(*)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND ACT IN ('N', 'C')
AND PRODUCT_TYPE IN ('DS1', 'DS3')
AND DISPATCH_YN = N
AND W_CODED_YN = Y
AND ASR_STATUS = C
AND OFFERED_INTERVAL <= 200
```

Numerator

```
SELECT
SUM(OFFERED_INTERVAL)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND ACT IN ('N', 'C')
AND PRODUCT_TYPE IN ('DS1', 'DS3')
AND DISPATCH_YN = N
AND W_CODED_YN = Y
AND ASR_STATUS = C
AND OFFERED_INTERVAL <= 200
```

UNE (Provisioning)

Report Labels: PR-1-01-3341

Complex Services - 2 Wire Digital

Parity with VZ Retail

Guidelines: PR-1 - Average Interval Offered

Average Interval Offered – Total No Dispatch

Result: (Numerator / Denominator)**Denominator:**

Count of orders without an outside dispatch in Product Groups

Numerator:

Sum of committed due date less application date for Orders without an outside dispatch in Product Groups

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &SOUNPI&
      AND &PROJECT&
      AND &Exclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND ATC IN ('W')
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Numerator

```

SELECT
SUM(APPINTV)
WHERE STATE = '&ST&'
      AND &SOUNPI&
      AND &PROJECT&
      AND &Exclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND ATC IN ('W')
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPI&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND ATC IN ('W')
      AND &PROJECT&
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Numerator

```

SELECT
SUM(APPINTV)
WHERE STATE = '&ST&'
      AND &RTPI&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0
or INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0
or INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND ATC IN ('W')
      AND &PROJECT&
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

UNE (Provisioning)

Report Labels: PR-1-01-3342

Complex Services - 2 Wire xDSL

Parity with VZ Retail

Guidelines: PR-1 - Average Interval Offered

Average Interval Offered – Total No Dispatch

Result: (Numerator / Denominator)**Denominator:**

Count of orders without an outside dispatch in Product Groups

Numerator:

Sum of committed due date less application date for Orders without an outside dispatch in Product Groups

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &SOUNPD&
      AND &Exclusions&
      AND ((TYPE in 'N' and STATUS = '55B') or (TYPE in 'T' and
STATUS in &STATUSC&) or (TYPE in 'C' and STATUS in
&STATUSC& and (OUT_QTY=0 or INWARD_QTY>0 or
CHNG_QTY>0)) and (OUTWARD_CKL=0 or INWARD_CKL>0 or
CHNG_CKL>0))
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND ATC IN ('W')
      AND &PROJECT&
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
SUM(APPINTV)
WHERE STATE = '&ST&'
      AND &SOUNPD&
      AND &Exclusions&
      AND ((TYPE in 'N' and STATUS = '55B') or (TYPE in 'T' and
STATUS in &STATUSC&) or (TYPE in 'C' and STATUS in
&STATUSC& and (OUT_QTY=0 or INWARD_QTY>0 or
CHNG_QTY>0)) and (OUTWARD_CKL=0 or INWARD_CKL>0
or CHNG_CKL>0))
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND ATC IN ('W')
      AND &PROJECT&
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPD&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND ATC IN ('W')
AND &PROJECT&
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
SUM(APPINTV)
WHERE STATE = '&ST&'
      AND &RTPD&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND ATC IN ('W')
AND &PROJECT&
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

RESALE (PROVISIONING)

Report Labels: PR-1-02-2200 Special Services - Provisioning

Parity with VZ Retail

Guidelines: PR-1 - Average Interval Offered

Average Interval Offered – Total Dispatch

Result: (Numerator / Denominator)**Denominator:**

Count of Orders with an outside dispatch in Product Groups.

Numerator:

Sum of committed due date less application date for Orders with an outside dispatch in Product Groups.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RSSS&
      AND &Exclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND STATUS in &STATUSC&
AND &PROJECT&
      AND
      decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
SUM(APPINTV)
WHERE STATE = '&ST&'
      AND &RSSS&
      AND &Exclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND STATUS in &STATUSC&
AND &PROJECT&
      AND
      decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTSS&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
      decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND ATC IN ('W')
AND &PROJECT&
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
SUM(APPINTV)
WHERE STATE = '&ST&'
      AND &RTSS&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
      decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND ATC IN ('W')
AND &PROJECT&
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```


RESALE (PROVISIONING)

Report Labels: PR-1-02-2341

Complex Services - 2 Wire Digital

Parity with VZ Retail

Guidelines: PR-1 - Average Interval Offered

Average Interval Offered – Total Dispatch

Result: (Numerator / Denominator)**Denominator:**

Count of Orders with an outside dispatch in Product Groups.

Numerator:

Sum of committed due date less application date for Orders with an outside dispatch in Product Groups.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RSPI&
      AND &Exclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and
((INWARD_QTY>=0 or CHNG_QTY>=0) and OUT_QTY=0) or
((INWARD_QTY>0 or CHNG_QTY>0)and OUT_QTY>0)) or
(TYPE ='R' and RESELLER_ACT='I' and APPINTV <= 2))
      AND STATUS in &STATUSC&
      AND &PROJECT&
      AND
      decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
SUM(APPINTV)
WHERE STATE = '&ST&'
      AND &RSPI&
      AND &Exclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and
((INWARD_QTY>=0 or CHNG_QTY>=0) and OUT_QTY=0) or
((INWARD_QTY>0 or CHNG_QTY>0)and OUT_QTY>0)) or
(TYPE ='R' and RESELLER_ACT='I' and APPINTV <= 2))
      AND STATUS in &STATUSC&
      AND &PROJECT&
      AND
      decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPI&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
      decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND ATC IN ('W')
      AND &PROJECT&
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
SUM(APPINTV)
WHERE STATE = '&ST&'
      AND &RTPI&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
      decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND ATC IN ('W')
      AND &PROJECT&
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```


RESALE (PROVISIONING)

Report Labels: PR-1-02-2342 Complex Services - 2 Wire xDSL

Parity with VZ Retail

Guidelines: PR-1 - Average Interval Offered

Average Interval Offered – Total Dispatch

Result: (Numerator / Denominator)**Denominator:**

Count of Orders with an outside dispatch in Product Groups.

Numerator:

Sum of committed due date less application date for Orders with an outside dispatch in Product Groups.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RSPD&
      AND &Exclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and
((INWARD_QTY>=0 or CHNG_QTY>=0) and OUT_QTY=0) or
((INWARD_QTY>0 or CHNG_QTY>0)and OUT_QTY>0)) or
(TYPE ='R' and RESELLER_ACT='I' and APPINTV <= 2))
      AND STATUS in &STATUSC&
      AND &PROJECT&
      AND
      decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
SUM(APPINTV)
WHERE STATE = '&ST&'
      AND &RSPD&
      AND &Exclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and
((INWARD_QTY>=0 or CHNG_QTY>=0) and OUT_QTY=0) or
((INWARD_QTY>0 or CHNG_QTY>0)and OUT_QTY>0)) or
(TYPE ='R' and RESELLER_ACT='I' and APPINTV <= 2))
      AND STATUS in &STATUSC&
      AND &PROJECT&
      AND
      decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPD&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
      decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND ATC IN ('W')
      AND &PROJECT&
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
SUM(APPINTV)
WHERE STATE = '&ST&'
      AND &RTPD&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
      decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND ATC IN ('W')
      AND &PROJECT&
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```


UNE (Provisioning)

Report Labels: PR-1-02-3200 Special Services Provisioning Parity with VZ Retail

Guidelines: PR-1 - Average Interval Offered

Average Interval Offered – Total Dispatch

Result: (Numerator / Denominator)	
Denominator:	Numerator:
Count of Orders with an outside dispatch in Product Groups.	Sum of committed due date less application date for Orders with an outside dispatch in Product Groups.

Filtered output file: ASR-UNE-SPECIAL
For the details on the above out put filtered file layout refer to File Appendix: 7 File Type: Excel

Denominator	Numerator
<div>SELECT COUNT(*) WHERE STATE = NJ AND ACTIVITY_DATE >= STARTDATE AND ACTIVITY_DATE <= ENDDATE AND ACT IN ('N', 'C') AND PRODUCT_TYPE IN ('DS1', 'DS3') AND DISPATCH_YN = Y AND W_CODED_YN = Y AND ASR_STATUS = C AND OFFERED_INTERVAL <= 200</div>	<div>SELECT SUM(OFFERED_INTERVAL) WHERE STATE = NJ AND ACTIVITY_DATE >= STARTDATE AND ACTIVITY_DATE <= ENDDATE AND ACT IN ('N', 'C') AND PRODUCT_TYPE IN ('DS1', 'DS3') AND DISPATCH_YN = Y AND W_CODED_YN = Y AND ASR_STATUS = C AND OFFERED_INTERVAL <= 200</div>

UNE (Provisioning)

Report Labels: PR-1-02-3341

Complex Services - 2 Wire Digital

Parity with VZ Retail

Guidelines: PR-1 - Average Interval Offered

Average Interval Offered – Total Dispatch

Result: (Numerator / Denominator)**Denominator:**

Count of Orders with an outside dispatch in Product Groups.

Numerator:

Sum of committed due date less application date for Orders with an outside dispatch in Product Groups.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &SOUNPI&
      AND &Exclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND ATC IN ('W')
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
SUM(APPINTV)
WHERE STATE = '&ST&'
      AND &SOUNPI&
      AND &Exclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND ATC IN ('W')
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPI&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND ATC IN ('W')
AND &PROJECT&
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
SUM(APPINTV)
WHERE STATE = '&ST&'
      AND &RTPI&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND ATC IN ('W')
AND &PROJECT&
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

UNE (Provisioning)

Report Labels: PR-1-02-3342 Complex Services - 2 Wire xDSL

Parity with VZ Retail

Guidelines: PR-1 - Average Interval Offered

Average Interval Offered – Total Dispatch

Result: (Numerator / Denominator)**Denominator:**

Count of Orders with an outside dispatch in Product Groups.

Numerator:

Sum of committed due date less application date for Orders with an outside dispatch in Product Groups.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```
SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &SOUNPD&
      AND &Exclusions&
      AND ATC IN ('W')
      AND &PROJECT&
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
((decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_NUM_DO)=0
      AND (TYPE in 'N' and STATUS <> '55B')) or
(decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_NUM_DO)>0
      AND ((TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0))))
      AND STATUS in ('55B','CAN'))))
```

```
SELECT
SUM(APPINTV)
WHERE STATE = '&ST&'
      AND &SOUNPD&
      AND &Exclusions&
      AND ATC IN ('W')
      AND &PROJECT&
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
((decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_NUM_DO)=0
      AND (TYPE in 'N' and STATUS <> '55B')) or
(decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_NUM_DO)>0
      AND ((TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0))))
      AND STATUS in ('55B','CAN'))))
```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**


```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPD&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND ATC IN ('W')
AND &PROJECT&
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
SUM(APPINTV)
WHERE STATE = '&ST&'
      AND &RTPD&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND ATC IN ('W')
AND &PROJECT&
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

RESALE (PROVISIONING)

Report Labels: PR-1-03-2110

POTS - Business

Parity with VZ Retail

Guidelines: PR-1 - Average Interval Offered

Average Interval Offered – Dispatch (1-5 Lines)

Result: (Numerator / Denominator)**Denominator:**

Count of POTS Orders with an outside dispatch in Product Groups for orders with 1 to 5 lines.

Numerator:

Sum of committed due date less application date for POTS Orders with an outside dispatch in Product Groups for orders with 1 to 5 lines.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```
SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RSPB&
      AND &Exclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND STATUS in &STATUSC&
AND &PROJECT&
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (INWARD_QTY+CHNG_QTY) BETWEEN 1 AND 5
```

Numerator

```
SELECT
SUM(APPINTV)
WHERE STATE = '&ST&'
      AND &RSPB&
      AND &Exclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND STATUS in &STATUSC&
AND &PROJECT&
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (INWARD_QTY+CHNG_QTY) BETWEEN 1 AND 5
```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPB&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (INWARD_QTY+CHNG_QTY) BETWEEN 1 AND 5

```

```

SELECT
SUM(APPINTV)
WHERE STATE = '&ST&'
      AND &RTPB&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (INWARD_QTY+CHNG_QTY) BETWEEN 1 AND 5

```

RESALE (PROVISIONING)

Report Labels: PR-1-03-2120 POTS - Residence

Parity with VZ Retail

Guidelines: PR-1 - Average Interval Offered

Average Interval Offered – Dispatch (1-5 Lines)

Result: (Numerator / Denominator)**Denominator:**

Count of POTS Orders with an outside dispatch in Product Groups for orders with 1 to 5 lines.

Numerator:

Sum of committed due date less application date for POTS Orders with an outside dispatch in Product Groups for orders with 1 to 5 lines.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```
SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RSPR&
      AND &Exclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND STATUS in &STATUSC&
AND &PROJECT&
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (INWARD_QTY+CHNG_QTY) BETWEEN 1 AND 5
```

Numerator

```
SELECT
SUM(APPINTV)
WHERE STATE = '&ST&'
      AND &RSPR&
      AND &Exclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND STATUS in &STATUSC&
AND &PROJECT&
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (INWARD_QTY+CHNG_QTY) BETWEEN 1 AND 5
```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPR&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (INWARD_QTY+CHNG_QTY) BETWEEN 1 AND 5

```

```

SELECT
SUM(APPINTV)
WHERE STATE = '&ST&'
      AND &RTPR&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0
or INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0
or INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (INWARD_QTY+CHNG_QTY) BETWEEN 1 AND 5

```

UNE (Provisioning)

Report Labels: PR-1-03-3112 POTS - Provisioning

Parity with VZ Retail

Guidelines: PR-1 - Average Interval Offered

Average Interval Offered – Dispatch (1-5 Lines) - Loop

Result: (Numerator / Denominator)**Denominator:**

Count of POTS Orders with an outside dispatch in Product Groups for orders with 1 to 5 lines.

Numerator:

Sum of committed due date less application date for POTS Orders with an outside dispatch in Product Groups for orders with 1 to 5 lines.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &SOUNPSL&
      AND &Exclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (INWARD_QTY+CHNG_QTY) BETWEEN 1 AND 5

```

```

SELECT
SUM(APPINTV)
WHERE STATE = '&ST&'
      AND &SOUNPSL&
      AND &Exclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (INWARD_QTY+CHNG_QTY) BETWEEN 1 AND 5

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPB&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (INWARD_QTY+CHNG_QTY) BETWEEN 1 AND 5

```

```

SELECT
SUM(APPINTV)
WHERE STATE = '&ST&'
      AND &RTPB&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (INWARD_QTY+CHNG_QTY) BETWEEN 1 AND 5

```


UNE (Provisioning)

Report Labels: PR-1-03-3140 POTS - Provisioning

Parity with VZ Retail

Guidelines: PR-1 - Average Interval Offered

Average Interval Offered – Dispatch (1-5 Lines) - Platform

Result: (Numerator / Denominator)**Denominator:**

Count of POTS Orders with an outside dispatch in Product Groups for orders with 1 to 5 lines.

Numerator:

Sum of committed due date less application date for POTS Orders with an outside dispatch in Product Groups for orders with 1 to 5 lines.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &SOUNPSP&
      AND &PROJECT&
      AND &Exclusions&
      AND STATUS in &STATUSC&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_NUM_DO)>0
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (INWARD_QTY+CHNG_QTY) BETWEEN 1 AND 5
AND CMPINTV BETWEEN 0 AND 200
      AND (
(ATC IN ('W') AND APPINTV between 0 and 200 AND (TYPE IN
('N','T') or (TYPE in 'C' and (OUT_QTY=0 or INWARD_QTY>0 or
CHNG_QTY>0) and (OUTWARD_CKL=0 or INWARD_CKL>0 or
CHNG_CKL>0))))
or (type in ('R') and PON is not null and APPINTV between 0 and
2) )

```

```

SELECT
SUM(APPINTV)
WHERE STATE = '&ST&'
      AND &SOUNPSP&
      AND &PROJECT&
      AND &Exclusions&
      AND STATUS in &STATUSC&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_NUM_DO)>0
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (INWARD_QTY+CHNG_QTY) BETWEEN 1 AND 5
AND CMPINTV BETWEEN 0 AND 200
      AND (
(ATC IN ('W') AND APPINTV between 0 and 200 AND (TYPE IN
('N','T') or (TYPE in 'C' and (OUT_QTY=0 or INWARD_QTY>0 or
CHNG_QTY>0) and (OUTWARD_CKL=0 or INWARD_CKL>0 or
CHNG_CKL>0))))
or (type in ('R') and PON is not null and APPINTV between 0 and
2) )

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**


```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPB&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (INWARD_QTY+CHNG_QTY) BETWEEN 1 AND 5

```

```

SELECT
SUM(APPINTV)
WHERE STATE = '&ST&'
      AND &RTPB&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (INWARD_QTY+CHNG_QTY) BETWEEN 1 AND 5

```

RESALE (PROVISIONING)

Report Labels: PR-1-04-2100 POTS - Provisioning - Total

Parity with VZ Retail

Guidelines: PR-1 - Average Interval Offered

Average Interval Offered – Dispatch (6-9 Lines)

Result: (Numerator / Denominator)**Denominator:**

Count of POTS Orders with an outside dispatch in Product Groups for orders with 6 to 9 lines.

Numerator:

Sum of committed due date less application date for POTS Orders with an outside dispatch in Product Groups for orders with 6 to 9 lines.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RSPS&
      AND &Exclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND STATUS in &STATUSC&
AND &PROJECT&
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (INWARD_QTY+CHNG_QTY) BETWEEN 6 AND 9

```

Numerator

```

SELECT
SUM(APPINTV)
WHERE STATE = '&ST&'
      AND &RSPS&
      AND &Exclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND STATUS in &STATUSC&
AND &PROJECT&
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (INWARD_QTY+CHNG_QTY) BETWEEN 6 AND 9

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RTPS&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (INWARD_QTY+CHNG_QTY) BETWEEN 6 AND 9

```

```

SELECT
SUM(appintv)
WHERE STATE = '&ST&'
      AND &RTPS&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0
or INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0
or INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (INWARD_QTY+CHNG_QTY) BETWEEN 6 AND 9

```

UNE (Provisioning)

Report Labels: PR-1-04-3112 POTS - Provisioning

Parity with VZ Retail

Guidelines: PR-1 - Average Interval Offered

Average Interval Offered – Dispatch (6-9 Lines) - Loop

Result: (Numerator / Denominator)**Denominator:**

Count of POTS Orders with an outside dispatch in Product Groups for orders with 6 to 9 lines.

Numerator:

Sum of committed due date less application date for POTS Orders with an outside dispatch in Product Groups for orders with 6 to 9 lines.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &SOUNPSL&
      AND &Exclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND &PROJECT&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (INWARD_QTY+CHNG_QTY) BETWEEN 6 AND 9

```

```

SELECT
SUM(APPINTV)
WHERE STATE = '&ST&'
      AND &SOUNPSL&
      AND &Exclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND &PROJECT&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (INWARD_QTY+CHNG_QTY) BETWEEN 6 AND 9

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPS&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (INWARD_QTY+CHNG_QTY) BETWEEN 6 AND 9

```

```

SELECT
SUM(appintv)
WHERE STATE = '&ST&'
      AND &RTPS&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
or INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0
or INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (INWARD_QTY+CHNG_QTY) BETWEEN 6 AND 9

```


UNE (Provisioning)

Report Labels: PR-1-04-3140 POTS - Provisioning

Parity with VZ Retail

Guidelines: PR-1 - Average Interval Offered

Average Interval Offered – Dispatch (6-9 Lines) - Platform

Result: (Numerator / Denominator)**Denominator:**

Count of POTS Orders with an outside dispatch in Product Groups for orders with 6 to 9 lines.

Numerator:

Sum of committed due date less application date for POTS Orders with an outside dispatch in Product Groups for orders with 6 to 9 lines.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```
SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &SOUNPSP&
      AND &PROJECT&
      AND &Exclusions&
      AND STATUS in &STATUSC&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_NUM_DO)>0
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (INWARD_QTY+CHNG_QTY) BETWEEN 6 AND 9
      AND CMPINTV between 0 and 200
      AND (
(ATC IN ('W') AND APPINTV between 0 and 200 AND ((TYPE IN
('N','T')) or (TYPE in 'C' and (OUT_QTY=0 or INWARD_QTY>0 or
CHNG_QTY>0) and (OUTWARD_CKL=0 or INWARD_CKL>0 or
CHNG_CKL>0))))
or (type in ('R') and PON is not null and APPINTV between 0 and
2) )
```

Numerator

```
SELECT
SUM(APPINTV)
WHERE STATE = '&ST&'
      AND &SOUNPSP&
      AND &PROJECT&
      AND &Exclusions&
      AND STATUS in &STATUSC&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_NUM_DO)>0
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (INWARD_QTY+CHNG_QTY) BETWEEN 6 AND 9
      AND CMPINTV between 0 and 200
      AND (
(ATC IN ('W') AND APPINTV between 0 and 200 AND ((TYPE IN
('N','T')) or (TYPE in 'C' and (OUT_QTY=0 or INWARD_QTY>0 or
CHNG_QTY>0) and (OUTWARD_CKL=0 or INWARD_CKL>0 or
CHNG_CKL>0))))
or (type in ('R') and PON is not null and APPINTV between 0 and
2) )
```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPS&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (INWARD_QTY+CHNG_QTY) BETWEEN 6 AND 9

```

```

SELECT
SUM(appintv)
WHERE STATE = '&ST&'
      AND &RTPS&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0
or INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0
or INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (INWARD_QTY+CHNG_QTY) BETWEEN 6 AND 9

```

RESALE (PROVISIONING)

Report Labels: PR-1-05-2100 POTS - Provisioning - Total

Parity with VZ Retail

Guidelines: PR-1 - Average Interval Offered

Average Interval Offered - Dispatch (>= 10lines)

Result: (Numerator / Denominator)**Denominator:**

Count of POTS Orders with an outside dispatch in Product Groups for orders with 10 or more lines.

Numerator:

Sum of committed due date less application date for POTS Orders with an outside dispatch in Product Groups for orders with 10 or more lines.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RSPS&
      AND &Exclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND STATUS in &STATUSC&
AND &PROJECT&
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (INWARD_QTY+CHNG_QTY) > 9

```

Numerator

```

SELECT
SUM(APPINTV)
WHERE STATE = '&ST&'
      AND &RSPS&
      AND &Exclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND STATUS in &STATUSC&
AND &PROJECT&
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (INWARD_QTY+CHNG_QTY) > 9

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPS&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (INWARD_QTY+CHNG_QTY) > 9

```

Numerator

```

SELECT
SUM(appintv)
WHERE STATE = '&ST&'
      AND &RTPS&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0
or INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0
or INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (INWARD_QTY+CHNG_QTY) > 9

```


UNE (Provisioning)

Report Labels: PR-1-05-3112 POTS - Provisioning

Parity with VZ Retail

Guidelines: PR-1 - Average Interval Offered

Average Interval Offered – Dispatch (>= 10 Lines) - Loop

Result: (Numerator / Denominator)**Denominator:**

Count of POTS Orders with an outside dispatch in Product Groups for orders with 10 or more lines.

Numerator:

Sum of committed due date less application date for POTS Orders with an outside dispatch in Product Groups for orders with 10 or more lines.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &SOUNPSL&
      AND &Exclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (INWARD_QTY+CHNG_QTY) > 9

```

```

SELECT
SUM(APPINTV)
WHERE STATE = '&ST&'
      AND &SOUNPSL&
      AND &Exclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0
or INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0
or INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (INWARD_QTY+CHNG_QTY) > 9

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPS&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (INWARD_QTY+CHNG_QTY) > 9

```

```

SELECT
SUM(appintv)
WHERE STATE = '&ST&'
      AND &RTPS&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0
or INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0
or INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (INWARD_QTY+CHNG_QTY) > 9

```

UNE (Provisioning)

Report Labels: PR-1-05-3140 POTS - Provisioning

Parity with VZ Retail

Guidelines: PR-1 - Average Interval Offered

Average Interval Offered – Dispatch (>= 10 Lines) - Platform

Result: (Numerator / Denominator)**Denominator:**

Count of POTS Orders with an outside dispatch in Product Groups for orders with 10 or more lines.

Numerator:

Sum of committed due date less application date for POTS Orders with an outside dispatch in Product Groups for orders with 10 or more lines.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```
SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &SOUNPSP&
      AND &PROJECT&
      AND &Exclusions&
      AND STATUS in &STATUSC&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_NUM_DO)>0
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (INWARD_QTY+CHNG_QTY) > 9
      AND CMPINTV between 0 and 200
      AND (
( (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC = 'W'
      AND APPINTV between 0 and 200 )
OR
(TYPE = 'R'
      AND PON IS NOT NULL
      AND NVL(APPINTV,0) IN (0,1,2))
)
```

```
SELECT
SUM(APPINTV)
WHERE STATE = '&ST&'
      AND &SOUNPSP&
      AND &PROJECT&
      AND &Exclusions&
      AND STATUS in &STATUSC&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_NUM_DO)>0
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (INWARD_QTY+CHNG_QTY) > 9
      AND CMPINTV between 0 and 200
      AND (
( (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC = 'W'
      AND APPINTV between 0 and 200 )
OR
(TYPE = 'R'
      AND PON IS NOT NULL
      AND NVL(APPINTV,0) IN (0,1,2))
)
```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPS&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (INWARD_QTY+CHNG_QTY) > 9

```

```

SELECT
SUM(appintv)
WHERE STATE = '&ST&'
      AND &RTPS&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0
or INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0
or INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (INWARD_QTY+CHNG_QTY) > 9

```

RESALE (PROVISIONING)

Report Labels: PR-1-06-2210 Special Services - Provisioning

Parity with VZ Retail

Guidelines: PR-1 - Average Interval Offered

Average Interval Offered – DS0

Result: (Numerator / Denominator)**Denominator:**

Count of Special Services orders for DS0 services.

Numerator:

Sum of committed due date less application date for Special Services orders for DS0 services.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RSSS&
      AND &Exclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND STATUS in &STATUSC&
AND &PROJECT&
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND &DS0&

```

```

SELECT
SUM(APPINTV)
WHERE STATE = '&ST&'
      AND &RSSS&
      AND &Exclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND STATUS in &STATUSC&
AND &PROJECT&
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND &DS0&

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTSS&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND &DS0&

```

```

SELECT
SUM(APPINTV)
WHERE STATE = '&ST&'
      AND &RTSS&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND &DS0&

```

UNE (Provisioning)

Report Labels: PR-1-06-3210 Special Services Provisioning

Parity with VZ Retail

Guidelines: PR-1 - Average Interval Offered

Average Interval Offered – DS0

Result: (Numerator / Denominator)**Denominator:**

Count of Special Services orders for DS0 services.

Numerator:

Sum of committed due date less application date for Special Services orders for DS0 services.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &SOUNSS&
      AND &Exclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND &DS0&

```

```

SELECT
SUM(APPINTV)
WHERE STATE = '&ST&'
      AND &SOUNSS&
      AND &Exclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND &DS0&

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTSS&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND &DS0&

```

```

SELECT
SUM(APPINTV)
WHERE STATE = '&ST&'
      AND &RTSS&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND &DS0&

```

RESALE (PROVISIONING)

Report Labels: PR-1-07-2211 Special Services - Provisioning

Parity with VZ Retail

Guidelines: PR-1 - Average Interval Offered

Average Interval Offered – DS1

Result: (Numerator / Denominator)**Denominator:**

Count of Special Services orders for DS1 services.

Numerator:

Sum of committed due date less application date for Special Services orders for DS1 services.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE ='&ST&'
      AND &RSSS&
      AND &Exclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND STATUS in &STATUSC&
AND &PROJECT&
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND &DS1&

```

```

SELECT
SUM(APPINTV)
WHERE STATE ='&ST&'
      AND &RSSS&
      AND &Exclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND STATUS in &STATUSC&
AND &PROJECT&
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND &DS1&

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTSS&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND &DS0&

```

```

SELECT
SUM(APPINTV)
WHERE STATE = '&ST&'
      AND &RTSS&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUSC&
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND &DS0&

```

UNE (Provisioning)

Report Labels: PR-1-07-3211 Special Services Provisioning Parity with VZ Retail

Guidelines: PR-1 - Average Interval Offered

Average Interval Offered – DS1

Result: (Numerator / Denominator)	
Denominator:	Numerator:
Count of Special Services orders for DS1 services.	Sum of committed due date less application date for Special Services orders for DS1 services.

Filtered output file: ASR-UNE-SPECIAL
For the details on the above out put filtered file layout refer to File Appendix: 7 File Type: Excel

Denominator	Numerator
<pre>SELECT COUNT(*) WHERE STATE = NJ AND ACTIVITY_DATE >= STARTDATE AND ACTIVITY_DATE <= ENDDATE AND ACT IN ('C', 'N') AND PRODUCT_TYPE = DS1 AND W_CODED_YN = Y AND ASR_STATUS = C AND OFFERED_INTERVAL <= 200</pre>	<pre>SELECT SUM(OFFERED_INTERVAL) WHERE STATE = NJ AND ACTIVITY_DATE >= STARTDATE AND ACTIVITY_DATE <= ENDDATE AND ACT IN ('C', 'N') AND PRODUCT_TYPE = DS1 AND W_CODED_YN = Y AND ASR_STATUS = C AND OFFERED_INTERVAL <= 200</pre>

RESALE (PROVISIONING)

Report Labels: PR-1-08-2213

Special Services - Provisioning

Parity with VZ Retail

Guidelines: PR-1 - Average Interval Offered

Average Interval Offered – DS3

Result: (Numerator / Denominator)**Denominator:**

Count of Special Services orders for DS3 services.

Numerator:

Sum of committed due date less application date for Special Services orders for DS3 services.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE &RSSS&
  AND &Exclusions&
    AND STATE = '&ST&'
    AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
    AND STATUS in &STATUSC&
AND &PROJECT&
  AND APPINTV between 0 and 200
  AND CMPINTV between 0 and 200
  AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
  AND &DS3&

```

```

SELECT
SUM(APPINTV)
WHERE &RSSS&
  AND &Exclusions&
    AND STATE = '&ST&'
    AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
    AND STATUS in &STATUSC&
AND &PROJECT&
  AND APPINTV between 0 and 200
  AND CMPINTV between 0 and 200
  AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
  AND &DS3&

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE &RTSS&
  AND &RetailExclusions&
    AND STATE = '&ST&'
    AND STATUS in &STATUSC&
    AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
    AND APPINTV between 0 and 200
    AND CMPINTV between 0 and 200
    AND ATC IN ('W')
AND &PROJECT&
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
  AND &DS3&

```

```

SELECT
SUM(APPINTV)
WHERE &RTSS&
  AND &RetailExclusions&
    AND STATE = '&ST&'
    AND STATUS in &STATUSC&
    AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
    AND APPINTV between 0 and 200
    AND CMPINTV between 0 and 200
    AND ATC IN ('W')
AND &PROJECT&
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
  AND &DS3&

```

UNE (Provisioning)

Report Labels: PR-1-08-3213

Special Services Provisioning

Parity with VZ Retail

Guidelines: PR-1 - Average Interval Offered

Average Interval Offered – DS3

Result: (Numerator / Denominator)**Denominator:**

Count of Special Services orders for DS3 services.

Numerator:

Sum of committed due date less application date for Special Services orders for DS3 services.

Filtered output file: ASR-UNE-SPECIAL

For the details on the above out put filtered file layout refer to File Appendix: 7 File Type: Excel

Denominator

```
SELECT
COUNT(*)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND ACT IN ('C', 'N')
AND PRODUCT_TYPE = DS3
AND W_CODED_YN = Y
AND ASR_STATUS = C
AND OFFERED_INTERVAL <= 200
```

Numerator

```
SELECT
SUM(OFFERED_INTERVAL)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND ACT IN ('C', 'N')
AND PRODUCT_TYPE = DS3
AND W_CODED_YN = Y
AND ASR_STATUS = C
AND OFFERED_INTERVAL <= 200
```

UNE (Provisioning)

Report Labels: PR-1-09-3510 Special Services Provisioning

Parity with VZ Retail

Guidelines: PR-1 - Average Interval Offered

Average Interval Offered – Total - EEL

Result: (Numerator / Denominator)**Denominator:**

Count of orders for product group.

Numerator:

Sum of committed due date less application date for product group orders.

Filtered output file: ASR-UNE-SPECIAL

For the details on the above out put filtered file layout refer to File Appendix: 7 File Type: Excel

Denominator

```
SELECT
COUNT(*)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND ACT IN ('C', 'N')
AND PRODUCT_TYPE = EEL
AND W_CODED_YN = Y
AND ASR_STATUS = C
AND OFFERED_INTERVAL <= 200
```

Numerator

```
SELECT
SUM(OFFERED_INTERVAL)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND ACT IN ('C', 'N')
AND PRODUCT_TYPE = EEL
AND W_CODED_YN = Y
AND ASR_STATUS = C
AND OFFERED_INTERVAL <= 200
```

UNE (Provisioning)

Report Labels: PR-1-09-3530 Special Services Provisioning

Parity with VZ Retail

Guidelines: PR-1 - Average Interval Offered

Average Interval Offered – Total - IOF

Result: (Numerator / Denominator)**Denominator:**

Count of orders for product group.

Numerator:

Sum of committed due date less application date for product group orders.

Filtered output file: ASR-UNE-SPECIAL

For the details on the above out put filtered file layout refer to File Appendix: 7 File Type: Excel

Denominator

```
SELECT
COUNT(*)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND ACT IN ('C', 'N')
AND PRODUCT_TYPE = IOF
AND W_CODED_YN = Y
AND ASR_STATUS = C
AND OFFERED_INTERVAL <= 200
```

Numerator

```
SELECT
SUM(OFFERED_INTERVAL)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND ACT IN ('C', 'N')
AND PRODUCT_TYPE = IOF
AND W_CODED_YN = Y
AND ASR_STATUS = C
AND OFFERED_INTERVAL <= 200
```

TRUNKS (Aggregate)

Report Labels: PR-1-09-5020 PROVISIONING

Parity with IXC / FGD

Guidelines: PR-1 - Average Interval Offered

Average Interval Offered – Total <= 192 Forecasted Trunks

Result: (Numerator / Denominator)**Denominator:**

Count of orders for product group.

Numerator:

Sum of committed due date less application date for product group orders.

Filtered output file: Trunking Filter Data

For the details on the above out put filtered file layout refer to File Appendix: 4 File Type: Excel

Formula For: CLEC**Denominator**

```
SELECT
COUNT(SERVICE_ORDER_NO)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND SERVICE_TYPE = T
AND PROJECT_YN = N
AND NEW_OR_AUGMENT = A
AND ASR_TRUNK_SIZE <= 192
AND FORECAST_YN = Y
AND ( ORDER_STATUS = C
AND CREATE_CDDD_INTERVAL <= 18
OR ( ORDER_STATUS = L
AND SAFE_OFFERED_INTERVAL <> NULL ))
```

Numerator

```
SELECT
SUM(SAFE_OFFERED_INTERVAL)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND SERVICE_TYPE = T
AND PROJECT_YN = N
AND NEW_OR_AUGMENT = A
AND ASR_TRUNK_SIZE <= 192
AND FORECAST_YN = Y
AND ( ORDER_STATUS = C
AND CREATE_CDDD_INTERVAL <= 18
OR ( ORDER_STATUS = L
AND SAFE_OFFERED_INTERVAL <> NULL ))
```

Filtered output file: Trunking Filter Data

For the details on the above out put filtered file layout refer to File Appendix: 4 File Type: Excel

Formula For: VERIZON**Denominator**

```
SELECT
COUNT(SERVICE_ORDER_NO)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND SERVICE_TYPE IN ('I', 'W')
AND PROJECT_YN = N
AND NEW_OR_AUGMENT = A
AND ASR_TRUNK_SIZE <= 192
AND FORECAST_YN = Y
AND ( ORDER_STATUS = C
AND CREATE_CDDD_INTERVAL <= 18
OR ( ORDER_STATUS = L
AND SAFE_OFFERED_INTERVAL <> NULL ))
```

Numerator

```
SELECT
SUM(SAFE_OFFERED_INTERVAL)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND SERVICE_TYPE IN ('I', 'W')
AND PROJECT_YN = N
AND NEW_OR_AUGMENT = A
AND ASR_TRUNK_SIZE <= 192
AND FORECAST_YN = Y
AND ( ORDER_STATUS = C
AND CREATE_CDDD_INTERVAL <= 18
OR ( ORDER_STATUS = L
AND SAFE_OFFERED_INTERVAL <> NULL ))
```

TRUNKS (Aggregate)

Report Labels: PR-1-09-5030 PROVISIONING

Parity with IXC / FGD

Guidelines: PR-1 - Average Interval Offered

Average Interval Offered – Total > 192 Forecasted & Unforecasted

Result: (Numerator / Denominator)**Denominator:**

Count of orders for product group.

Numerator:

Sum of committed due date less application date for product group orders.

Filtered output file: Trunking Filter Data

For the details on the above out put filtered file layout refer to File Appendix: 4 File Type: Excel

Formula For: CLEC**Denominator**

```
SELECT
COUNT(SERVICE_ORDER_NO)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND SERVICE_TYPE = T
AND NOT ( PROJECT_YN = N
AND NEW_OR_AUGMENT = A
AND ASR_TRUNK_SIZE <= 192
AND FORECAST_YN = Y )
AND ( ORDER_STATUS = C
AND CREATE_CDDD_INTERVAL <= 18
OR ( ORDER_STATUS = L
AND SAFE_OFFERED_INTERVAL <> NULL ))
```

Numerator

```
SELECT
SUM(SAFE_OFFERED_INTERVAL)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND SERVICE_TYPE = T
AND NOT ( PROJECT_YN = N
AND NEW_OR_AUGMENT = A
AND ASR_TRUNK_SIZE <= 192
AND FORECAST_YN = Y )
AND ( ORDER_STATUS = C
AND CREATE_CDDD_INTERVAL <= 18
OR ( ORDER_STATUS = L
AND SAFE_OFFERED_INTERVAL <> NULL ))
```

Filtered output file: Trunking Filter Data

For the details on the above out put filtered file layout refer to File Appendix: 4 File Type: Excel

Formula For: VERIZON**Denominator****Numerator**

RESALE (PROVISIONING)

Report Labels: PR-1-10-2103 POTS & Complex Aggregate

Parity with VZ Retail

Guidelines: PR-1 - Average Interval Offered

Average Interval Offered – Disconnects – No Dispatch

Result: (Numerator / Denominator)**Denominator:**

Count of orders for product group.

Numerator:

Sum of committed due date less application date for product group no dispatch disconnect (D & F) orders.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&' and nvl(out_seller,0) not in
('BAND','BNK')
    AND &RTSSDisc&
    AND STATUS in &STATUSC&
    AND TYPE IN ('D','F')
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(out_seller,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
UNION
SELECT COUNT(ORDER_NUM),
SUM(APPINTV),SUM(APPINTV)/COUNT(ORDER_NUM),SUM(PO
WER(APPINTV,2)) C
FROM &DATAPATH&
WHERE STATE = '&ST&'
    AND &RTSS&
    AND &RetailExclusions&
    AND STATUS in &STATUSC&
    AND (TYPE in 'C' AND SELLER_TYPE = '1' and
(OUT_QTY>0 or OUTWARD_CKL>0 ) and INWARD_QTY=0 and
CHNG_QTY=0 and INWARD_CKL=0 and CHNG_CKL=0)
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
    AND NVL(ATC,0) not in ('S','X')

```

```

SELECT
SUM(APPINTV)
WHERE STATE = '&ST&' and nvl(out_seller,0) not in
('BAND','BNK')
    AND &RTSSDisc&
    AND STATUS in &STATUSC&
    AND TYPE IN ('D','F')
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(out_seller,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
UNION
SELECT COUNT(ORDER_NUM),
SUM(APPINTV),SUM(APPINTV)/COUNT(ORDER_NUM),SUM(P
OWER(APPINTV,2)) C
FROM &DATAPATH&
WHERE STATE = '&ST&'
    AND &RTSS&
    AND &RetailExclusions&
    AND STATUS in &STATUSC&
    AND (TYPE in 'C' AND SELLER_TYPE = '1' and
(OUT_QTY>0 or OUTWARD_CKL>0 ) and INWARD_QTY=0 and
CHNG_QTY=0 and INWARD_CKL=0 and CHNG_CKL=0)
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
    AND NVL(ATC,0) not in ('S','X')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&' and nvl(out_seller,0) not in
('BAND','BNK')
    AND &RTSSDisc&
    AND STATUS in &STATUSC&
    AND TYPE IN ('D','F')
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_NUM_DO)=0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(out_seller,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
UNION
SELECT COUNT(ORDER_NUM),
SUM(APPINTV),SUM(APPINTV)/COUNT(ORDER_NUM),SUM(POWER(APPINTV,2)) C
FROM &DATAPATH&
WHERE STATE = '&ST&'
    AND &RTSS&
    AND &RetailExclusions&
    AND STATUS in &STATUSC&
    AND (TYPE in 'C' AND SELLER_TYPE = '1' and
(OUT_QTY>0 or OUTWARD_CKL>0 ) and INWARD_QTY=0 and
CHNG_QTY=0 and INWARD_CKL=0 and CHNG_CKL=0)
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_NUM_DO)=0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
    AND NVL(ATC,0) not in ('S','X')

```

```

SELECT
SUM(APPINTV)
WHERE STATE = '&ST&' and nvl(out_seller,0) not in
('BAND','BNK')
    AND &RTSSDisc&
    AND STATUS in &STATUSC&
    AND TYPE IN ('D','F')
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_NUM_DO)=0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(out_seller,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
UNION
SELECT COUNT(ORDER_NUM),
SUM(APPINTV),SUM(APPINTV)/COUNT(ORDER_NUM),SUM(POWER(APPINTV,2)) C
FROM &DATAPATH&
WHERE STATE = '&ST&'
    AND &RTSS&
    AND &RetailExclusions&
    AND STATUS in &STATUSC&
    AND (TYPE in 'C' AND SELLER_TYPE = '1' and
(OUT_QTY>0 or OUTWARD_CKL>0 ) and INWARD_QTY=0 and
CHNG_QTY=0 and INWARD_CKL=0 and CHNG_CKL=0)
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_NUM_DO)=0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
    AND NVL(ATC,0) not in ('S','X')

```


RESALE (PROVISIONING)

Report Labels: PR-1-10-2200

Special Services - Provisioning

Parity with VZ Retail

Guidelines: PR-1 - Average Interval Offered

Average Interval Offered – Disconnects – No Dispatch

Result: (Numerator / Denominator)**Denominator:**

Count of orders for product group.

Numerator:

Sum of committed due date less application date for product group no dispatch disconnect (D & F) orders.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&' and nvl(out_seller,0) not in
('BAND','BNK')
    AND &RSSSDisc&
    AND &Exclusions&
    AND STATUS in &STATUSC&
    AND &PROJECTdisc&
    AND TYPE IN ('D','F')
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(OUT_SELLER,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
UNION
SELECT COUNT(ORDER_NUM),
SUM(APPINTV),SUM(APPINTV)/COUNT(ORDER_NUM),SUM(PO
WER(APPINTV,2)) C
FROM &DATAPATH&
WHERE STATE = '&ST&'
    AND &RSSS&
    AND &Exclusions&
    AND STATUS in &STATUSC&
    AND &PROJECT&
    AND (TYPE in 'C' and (OUT_QTY>0 or
OUTWARD_CKL>0 ) and INWARD_QTY=0 and CHNG_QTY=0
and INWARD_CKL=0 and CHNG_CKL=0)
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
    AND NVL(ATC,0) not in ('S','X')

```

```

SELECT
SUM(APPINTV)
WHERE STATE = '&ST&' and nvl(out_seller,0) not in
('BAND','BNK')
    AND &RSSSDisc&
    AND &Exclusions&
    AND STATUS in &STATUSC&
    AND &PROJECTdisc&
    AND TYPE IN ('D','F')
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(OUT_SELLER,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
UNION
SELECT COUNT(ORDER_NUM),
SUM(APPINTV),SUM(APPINTV)/COUNT(ORDER_NUM),SUM(P
OWER(APPINTV,2)) C
FROM &DATAPATH&
WHERE STATE = '&ST&'
    AND &RSSS&
    AND &Exclusions&
    AND STATUS in &STATUSC&
    AND &PROJECT&
    AND (TYPE in 'C' and (OUT_QTY>0 or
OUTWARD_CKL>0 ) and INWARD_QTY=0 and CHNG_QTY=0
and INWARD_CKL=0 and CHNG_CKL=0)
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
    AND NVL(ATC,0) not in ('S','X')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
SUM(APPINTV)
WHERE STATE = '&ST&' and nvl(out_seller,0) not in
('BAND','BNK')
    AND &RTSSDisc&
    AND STATUS in &STATUSC&
    AND TYPE IN ('D','F')
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(out_seller,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
UNION
SELECT COUNT(ORDER_NUM),
SUM(APPINTV),SUM(APPINTV)/COUNT(ORDER_NUM),SUM(P
OWER(APPINTV,2)) C
FROM &DATAPATH&
WHERE STATE = '&ST&'
    AND &RTSS&
    AND &RetailExclusions&
    AND STATUS in &STATUSC&
    AND (TYPE in 'C' AND SELLER_TYPE = '1' and
(OUT_QTY>0 or OUTWARD_CKL>0 ) and INWARD_QTY=0 and
CHNG_QTY=0 and INWARD_CKL=0 and CHNG_CKL=0)
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
    AND NVL(ATC,0) not in ('S','X')

```

UNE (Provisioning)

Report Labels: PR-1-10-3133

POTS & Complex Aggregate

Parity with VZ Retail

Guidelines: PR-1 - Average Interval Offered

Average Interval Offered – Disconnects – No Dispatch

Result: (Numerator / Denominator)**Denominator:**

Count of orders for product group.

Numerator:

Sum of committed due date less application date for product group no dispatch disconnect (D & F) orders.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&' and nvl(out_seller,0) not in
('BAND','BNK')
    AND &SOUNPDisc&
    AND &Exclusions&
    AND STATUS in &STATUSC&
    AND &PROJECT&
    AND TYPE IN ('D','F')
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(OUT_SELLER,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
UNION
SELECT COUNT(ORDER_NUM),
SUM(APPINTV),SUM(APPINTV)/COUNT(ORDER_NUM),SUM(PO
WER(APPINTV,2)) C
FROM &DATAPATH&
WHERE STATE = '&ST&'
    AND &SOUNP&
    AND &Exclusions&
    AND STATUS in &STATUSC&
    AND &PROJECT&
    AND (TYPE in 'C' and (OUT_QTY>0 or OUTWARD_CKL>0
) and INWARD_QTY=0 and CHNG_QTY=0 and INWARD_CKL=0
and CHNG_CKL=0)
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
    AND NVL(ATC,0) not in ('S','X')

```

```

SELECT
SUM(APPINTV)
WHERE STATE = '&ST&' and nvl(out_seller,0) not in
('BAND','BNK')
    AND &SOUNPDisc&
    AND &Exclusions&
    AND STATUS in &STATUSC&
    AND &PROJECT&
    AND TYPE IN ('D','F')
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(OUT_SELLER,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
UNION
SELECT COUNT(ORDER_NUM),
SUM(APPINTV),SUM(APPINTV)/COUNT(ORDER_NUM),SUM(P
OWER(APPINTV,2)) C
FROM &DATAPATH&
WHERE STATE = '&ST&'
    AND &SOUNP&
    AND &Exclusions&
    AND STATUS in &STATUSC&
    AND &PROJECT&
    AND (TYPE in 'C' and (OUT_QTY>0 or
OUTWARD_CKL>0 ) and INWARD_QTY=0 and CHNG_QTY=0
and INWARD_CKL=0 and CHNG_CKL=0)
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
    AND NVL(ATC,0) not in ('S','X')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
SUM(APPINTV)
WHERE STATE = '&ST&' and nvl(out_seller,0) not in
('BAND','BNK')
    AND &RTPDisc&
    AND STATUS in &STATUSC&
    AND TYPE IN ('D','F')
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(out_SELLER,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
UNION
SELECT COUNT(ORDER_NUM),
SUM(APPINTV),SUM(APPINTV)/COUNT(ORDER_NUM),SUM(P
OWER(APPINTV,2)) C
FROM &DATAPATH&
WHERE STATE = '&ST&'
    AND &RTP&
    AND &RetailExclusions&
    AND STATUS in &STATUSC&
    AND (TYPE in 'C' AND SELLER_TYPE = '1' and
(OUT_QTY>0 or OUTWARD_CKL>0 ) and INWARD_QTY=0 and
CHNG_QTY=0 and INWARD_CKL=0 and CHNG_CKL=0)
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
    AND NVL(ATC,0) not in ('S','X')

```

UNE (Provisioning)

Report Labels: PR-1-10-3200

Special Services Provisioning

Parity with VZ Retail

Guidelines: PR-1 - Average Interval Offered

Average Interval Offered – Disconnects – No Dispatch

Result: (Numerator / Denominator)**Denominator:**

Count of orders for product group.

Numerator:

Sum of committed due date less application date for product group no dispatch disconnect (D & F) orders.

Filtered output file: ASR-UNE-SPECIAL

For the details on the above out put filtered file layout refer to File Appendix: 7 File Type: Excel

Denominator

```
SELECT
COUNT(*)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND ACT = D
AND PRODUCT_TYPE IN ('DS1', 'DS3', 'EXP')
AND DISPATCH_YN = N
AND W_CODED_YN = Y
AND ASR_STATUS = C
AND OFFERED_INTERVAL <= 2
```

Numerator

```
SELECT
SUM(OFFERED_INTERVAL)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND ACT = D
AND PRODUCT_TYPE IN ('DS1', 'DS3', 'EXP')
AND DISPATCH_YN = N
AND W_CODED_YN = Y
AND ASR_STATUS = C
AND OFFERED_INTERVAL <= 2
```

RESALE (PROVISIONING)

Report Labels: PR-1-11-2103 POTS & Complex Aggregate

Parity with VZ Retail

Guidelines: PR-1 - Average Interval Offered

Average Interval Offered – Disconnects – Dispatch

Result: (Numerator / Denominator)**Denominator:**

Count of orders for product group.

Numerator:Sum of committed due date less application date for product group
dispatch disconnect (D&F) orders.**Filtered output file:** Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&' and nvl(out_seller,0) not in
('BAND','BNK')
  AND &SOUNPDisc&
  AND &Exclusions&
  AND STATUS in &STATUSC&
  AND &PROJECT&
  AND TYPE IN ('D','F')
  AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
  AND APPINTV between 0 and 1
  AND CMPINTV between 0 and 200
  AND nvl(OUT_SELLER,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
UNION
SELECT COUNT(ORDER_NUM),
SUM(APPINTV),SUM(APPINTV)/COUNT(ORDER_NUM),SUM(PO
WER(APPINTV,2)) C
  FROM &DATAPATH&
  WHERE STATE = '&ST&'
  AND &SOUNP&
  AND &Exclusions&
  AND STATUS in &STATUSC&
  AND &PROJECT&
  AND (TYPE in 'C' and (OUT_QTY>0 or OUTWARD_CKL>0
) and INWARD_QTY=0 and CHNG_QTY=0 and INWARD_CKL=0
and CHNG_CKL=0)
  AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
  AND APPINTV between 0 and 1
  AND CMPINTV between 0 and 200
  AND nvl(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
  AND NVL(ATC,0) not in ('S','X')

```

```

SELECT
SUM(CMPINTV)
WHERE STATE = '&ST&' and nvl(out_seller,0) not in
('BAND','BNK')
  AND &SOUNPDisc&
  AND &Exclusions&
  AND STATUS in &STATUSC&
  AND &PROJECT&
  AND TYPE IN ('D','F')
  AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
  AND APPINTV between 0 and 1
  AND CMPINTV between 0 and 200
  AND nvl(OUT_SELLER,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
UNION
SELECT COUNT(ORDER_NUM),
SUM(APPINTV),SUM(APPINTV)/COUNT(ORDER_NUM),SUM(P
OWER(APPINTV,2)) C
  FROM &DATAPATH&
  WHERE STATE = '&ST&'
  AND &SOUNP&
  AND &Exclusions&
  AND STATUS in &STATUSC&
  AND &PROJECT&
  AND (TYPE in 'C' and (OUT_QTY>0 or
OUTWARD_CKL>0 ) and INWARD_QTY=0 and CHNG_QTY=0
and INWARD_CKL=0 and CHNG_CKL=0)
  AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
  AND APPINTV between 0 and 1
  AND CMPINTV between 0 and 200
  AND nvl(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
  AND NVL(ATC,0) not in ('S','X')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&' and nvl(out_seller,0) not in
('BAND','BNK')
    AND &RTPDisc&
    AND STATUS in &STATUSC&
    AND TYPE IN ('D','F')
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(out_SELLER,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
UNION
SELECT COUNT(ORDER_NUM),
SUM(APPINTV),SUM(APPINTV)/COUNT(ORDER_NUM),SUM(PO
WER(APPINTV,2)) C
FROM &DATAPATH&
WHERE STATE = '&ST&'
    AND &RTP&
    AND &RetailExclusions&
    AND STATUS in &STATUSC&
    AND (TYPE in 'C' AND SELLER_TYPE = '1' and
(OUT_QTY>0 or OUTWARD_CKL>0 ) and INWARD_QTY=0 and
CHNG_QTY=0 and INWARD_CKL=0 and CHNG_CKL=0)
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
    AND NVL(ATC,0) not in ('S','X')

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&' and nvl(out_seller,0) not in
('BAND','BNK')
    AND &RTPDisc&
    AND STATUS in &STATUSC&
    AND TYPE IN ('D','F')
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(out_SELLER,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
UNION
SELECT COUNT(ORDER_NUM),
SUM(APPINTV),SUM(APPINTV)/COUNT(ORDER_NUM),SUM(P
OWER(APPINTV,2)) C
FROM &DATAPATH&
WHERE STATE = '&ST&'
    AND &RTP&
    AND &RetailExclusions&
    AND STATUS in &STATUSC&
    AND (TYPE in 'C' AND SELLER_TYPE = '1' and
(OUT_QTY>0 or OUTWARD_CKL>0 ) and INWARD_QTY=0 and
CHNG_QTY=0 and INWARD_CKL=0 and CHNG_CKL=0)
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
    AND NVL(ATC,0) not in ('S','X')

```

RESALE (PROVISIONING)

Report Labels: PR-1-11-2200 Special Services - Provisioning

Parity with VZ Retail

Guidelines: PR-1 - Average Interval Offered

Average Interval Offered – Disconnects – Dispatch

Result: (Numerator / Denominator)**Denominator:**

Count of orders for product group.

Numerator:

Sum of committed due date less application date for product group dispatch disconnect (D&F) orders.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&' and nvl(out_seller,0) not in
('BAND','BNK')
    AND &RSSSDisc&
    AND &Exclusions&
    AND STATUS in &STATUSC&
    AND TYPE IN ('D','F')
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_NUM_DO)>0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(OUT_SELLER,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
UNION
SELECT COUNT(ORDER_NUM),
SUM(APPINTV),SUM(APPINTV)/COUNT(ORDER_NUM),SUM(POWER(APPINTV,2)) C
FROM &DATAPATH&
WHERE STATE = '&ST&'
    AND &RSSS&
    AND &Exclusions&
    AND STATUS in &STATUSC&
    AND (TYPE in 'C' and (OUT_QTY>0 or
OUTWARD_CKL>0 ) and INWARD_QTY=0 and CHNG_QTY=0
and INWARD_CKL=0 and CHNG_CKL=0)
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_NUM_DO)>0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
    AND NVL(ATC,0) not in ('S','X')

```

```

SELECT
SUM(APPINTV)
WHERE STATE = '&ST&' and nvl(out_seller,0) not in
('BAND','BNK')
    AND &RSSSDisc&
    AND &Exclusions&
    AND STATUS in &STATUSC&
    AND TYPE IN ('D','F')
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_NUM_DO)>0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(OUT_SELLER,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
UNION
SELECT COUNT(ORDER_NUM),
SUM(APPINTV),SUM(APPINTV)/COUNT(ORDER_NUM),SUM(POWER(APPINTV,2)) C
FROM &DATAPATH&
WHERE STATE = '&ST&'
    AND &RSSS&
    AND &Exclusions&
    AND STATUS in &STATUSC&
    AND (TYPE in 'C' and (OUT_QTY>0 or
OUTWARD_CKL>0 ) and INWARD_QTY=0 and CHNG_QTY=0
and INWARD_CKL=0 and CHNG_CKL=0)
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_NUM_DO)>0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
    AND NVL(ATC,0) not in ('S','X')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**


```

SELECT
count(order_num)
WHERE STATE = '&ST&' and nvl(out_seller,0) not in
('BAND','BNK')
    AND &RTSSDisc&
    AND STATUS in &STATUSC&
    AND TYPE IN ('D','F')
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_NUM_DO)>0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(out_seller,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
UNION
SELECT COUNT(ORDER_NUM),
SUM(APPINTV),SUM(APPINTV)/COUNT(ORDER_NUM),SUM(POWER(APPINTV,2)) C
FROM &DATAPATH&
WHERE STATE = '&ST&'
    AND &RTSS&
    AND &RetailExclusions&
    AND STATUS in &STATUSC&
    AND (TYPE in 'C' AND SELLER_TYPE = '1' and
(OUT_QTY>0 or OUTWARD_CKL>0 ) and INWARD_QTY=0 and
CHNG_QTY=0 and INWARD_CKL=0 and CHNG_CKL=0)
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_NUM_DO)>0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
    AND NVL(ATC,0) not in ('S','X')

```

```

SELECT
SUM(APPINTV)
WHERE STATE = '&ST&' and nvl(out_seller,0) not in
('BAND','BNK')
    AND &RTSSDisc&
    AND STATUS in &STATUSC&
    AND TYPE IN ('D','F')
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_NUM_DO)>0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(out_seller,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
UNION
SELECT COUNT(ORDER_NUM),
SUM(APPINTV),SUM(APPINTV)/COUNT(ORDER_NUM),SUM(POWER(APPINTV,2)) C
FROM &DATAPATH&
WHERE STATE = '&ST&'
    AND &RTSS&
    AND &RetailExclusions&
    AND STATUS in &STATUSC&
    AND (TYPE in 'C' AND SELLER_TYPE = '1' and
(OUT_QTY>0 or OUTWARD_CKL>0 ) and INWARD_QTY=0 and
CHNG_QTY=0 and INWARD_CKL=0 and CHNG_CKL=0)
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_NUM_DO)>0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
    AND NVL(ATC,0) not in ('S','X')

```

UNE (Provisioning)

Report Labels: PR-1-11-3133

POTS & Complex Aggregate

Parity with VZ Retail

Guidelines: PR-1 - Average Interval Offered

Average Interval Offered – Disconnects – Dispatch

Result: (Numerator / Denominator)**Denominator:**

Count of orders for product group.

Numerator:

Sum of committed due date less application date for product group dispatch disconnect (D&F) orders.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
SUM(APPINTV)
WHERE STATE = '&ST&' and nvl(out_seller,0) not in
('BAND','BNK')
  AND &SOUNPDisc&
  AND &Exclusions&
  AND STATUS in &STATUSC&
  AND &PROJECT&
  AND TYPE IN ('D','F')
  AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
  AND APPINTV between 0 and 1
  AND CMPINTV between 0 and 200
  AND nvl(OUT_SELLER,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
UNION
SELECT COUNT(ORDER_NUM),
SUM(APPINTV),SUM(APPINTV)/COUNT(ORDER_NUM),SUM(PO
WER(APPINTV,2)) C
FROM &DATAPATH&
WHERE STATE = '&ST&'
  AND &SOUNP&
  AND &Exclusions&
  AND STATUS in &STATUSC&
  AND &PROJECT&
  AND (TYPE in 'C' and (OUT_QTY>0 or OUTWARD_CKL>0
) and INWARD_QTY=0 and CHNG_QTY=0 and INWARD_CKL=0
and CHNG_CKL=0)
  AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
  AND APPINTV between 0 and 1
  AND CMPINTV between 0 and 200
  AND nvl(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
  AND NVL(ATC,0) not in ('S','X')

```

```

SELECT
SUM(APPINTV)
WHERE STATE = '&ST&' and nvl(out_seller,0) not in
('BAND','BNK')
  AND &SOUNPDisc&
  AND &Exclusions&
  AND STATUS in &STATUSC&
  AND &PROJECT&
  AND TYPE IN ('D','F')
  AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
  AND APPINTV between 0 and 1
  AND CMPINTV between 0 and 200
  AND nvl(OUT_SELLER,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
UNION
SELECT COUNT(ORDER_NUM),
SUM(APPINTV),SUM(APPINTV)/COUNT(ORDER_NUM),SUM(P
OWER(APPINTV,2)) C
FROM &DATAPATH&
WHERE STATE = '&ST&'
  AND &SOUNP&
  AND &Exclusions&
  AND STATUS in &STATUSC&
  AND &PROJECT&
  AND (TYPE in 'C' and (OUT_QTY>0 or
OUTWARD_CKL>0 ) and INWARD_QTY=0 and CHNG_QTY=0
and INWARD_CKL=0 and CHNG_CKL=0)
  AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
  AND APPINTV between 0 and 1
  AND CMPINTV between 0 and 200
  AND nvl(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
  AND NVL(ATC,0) not in ('S','X')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
SUM(APPINTV)
WHERE STATE = '&ST&' and nvl(out_seller,0) not in
('BAND','BNK')
    AND &RTPDisc&
    AND STATUS in &STATUSC&
    AND TYPE IN ('D','F')
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(out_SELLER,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
UNION
SELECT COUNT(ORDER_NUM),
SUM(APPINTV),SUM(APPINTV)/COUNT(ORDER_NUM),SUM(P
OWER(APPINTV,2)) C
FROM &DATAPATH&
WHERE STATE = '&ST&'
    AND &RTP&
    AND &RetailExclusions&
    AND STATUS in &STATUSC&
    AND (TYPE in 'C' AND SELLER_TYPE = '1' and
(OUT_QTY>0 or OUTWARD_CKL>0 ) and INWARD_QTY=0 and
CHNG_QTY=0 and INWARD_CKL=0 and CHNG_CKL=0)
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
    AND NVL(ATC,0) not in ('S','X')

```

UNE (Provisioning)

Report Labels: PR-1-11-3200

Special Services Provisioning

Parity with VZ Retail

Guidelines: PR-1 - Average Interval Offered

Average Interval Offered – Disconnects – Dispatch

Result: (Numerator / Denominator)**Denominator:**

Count of orders for product group.

Numerator:Sum of committed due date less application date for product group
dispatch disconnect (D&F) orders.**Filtered output file:** ASR-UNE-SPECIAL

For the details on the above out put filtered file layout refer to File Appendix: 7 File Type: Excel

Denominator

```
SELECT
COUNT(*)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND ACT = D
AND PRODUCT_TYPE IN ('DS1', 'DS3', 'EXP')
AND DISPATCH_YN = Y
AND W_CODED_YN = Y
AND ASR_STATUS = C
AND OFFERED_INTERVAL <= 2
```

Numerator

```
SELECT
SUM(OFFERED_INTERVAL)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND ACT = D
AND PRODUCT_TYPE IN ('DS1', 'DS3', 'EXP')
AND DISPATCH_YN = Y
AND W_CODED_YN = Y
AND ASR_STATUS = C
AND OFFERED_INTERVAL <= 2
```

Guidelines For: PR-2 Average Interval Completed**C2C Guideline:**

Definition:	POTS and Specials: The average number of business days between order application date and completion date. The application date is the date that a valid service request is received. All orders received after the "cut-off" time shown in the BA Product Interval Guide are considered received the next business day at 8:00 AM. The "cut-off" time for a CLEC order for a service will be the same as the "cut-off" time for a BA Retail order for the analogous BA Retail service. Orders sent by fax are considered received 24 hours later. Coordinated Cut-over (Hot Cut) Loop orders are considered complete upon acceptance by CLEC. However, if a CLEC is not ready on the due date to test and accept, BA will complete the order. (Any problems with the loop subsequent to this completion should be entered into RETAS as a trouble. If the trouble cannot be entered, due to order processing, the CLEC should call into the BA center (RCCC) where the trouble will be tracked. CLECs should provide serial number to BA at turn-up for documentation.) Trunks: The average amount of time in business days between date of receipt of a valid Access Service Request ("ASR") (received date restarted for each supplement) (application date) and date order is completed and customer is notified. Measures service orders completed between the measured dates.
Performance Standard:	Metrics PR-2-01 through 11 (except PR-2-09, UNE IOF and EEL): Parity with BA Retail. Metric PR-2-09, UNE IOF and EEL: Not greater than applicable interval stated in BA Product Interval Guide.(footnote 24) Metrics PR-2-13 through 17: No standard.
Exclusions:	BA Test Orders Orders where customers request a due date that is greater than or less than the standard available appointment interval (X or S Appointment Code). Bell Atlantic Administrative orders. Orders with invalid intervals (Negative Intervals or intervals over 200 business days - indicative of typographical error). Additional Segments on orders (parts of a whole order are included in the whole). Orders that are not complete. (Orders are included in the month that they are complete). Suspend for non-payment and associated restore orders. Orders completed late due to any end user or CLEC caused delay. Trunks: Excludes projects, reciprocal trunks from BA to the CLEC, and new connect orders for CLECs initially establishing service in a BA central office.
Report Dimensions:	BA Retail CLEC Aggregate CLEC Specific BA Affiliate Aggregate BA Affiliate Specific
Geography:	POTS, Complex, 2 Wire Digital Services, and 2 Wire xDSL Services: Southern, Eastern Shore, Raritan, Suburban, Hudson-Bergen Specials, IOF and EEL: State Trunks: State

24 The BA Product Interval Guide is set out on BA's Web Page at http://www.BellAtlantic.com/wholesale/html/cd_supp_document.htm.

RESALE (PROVISIONING)

Report Labels: PR-2-01-2110

POTS - Business

Parity with VZ Retail

Guidelines: PR-2 - Average Completed Interval

Average Interval Completed – Total No Dispatch

Result: (Numerator / Denominator)**Denominator:**

Count of orders for Orders without an outside dispatch in Product Groups

Numerator:

Sum of completion date less application date for Orders without an outside dispatch in Product Groups

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RSPB&
      AND &Exclusions&
AND &PROJECT&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Numerator

```

SELECT
SUM(CMPINTV)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RSPB&
      AND &Exclusions&
AND &PROJECT&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTPB&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
SUM(CMPINTV)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTPB&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

RESALE (PROVISIONING)

Report Labels: PR-2-01-2120 POTS - Residence

Parity with VZ Retail

Guidelines: PR-2 - Average Completed Interval

Average Interval Completed – Total No Dispatch

Result: (Numerator / Denominator)**Denominator:**

Count of orders for Orders without an outside dispatch in Product Groups

Numerator:

Sum of completion date less application date for Orders without an outside dispatch in Product Groups

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RSPR&
      AND &Exclusions&
AND &PROJECT&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Numerator

```

SELECT
SUM(CMPINTV)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RSPR&
      AND &Exclusions&
AND &PROJECT&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**


```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTPR&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
SUM(CMPINTV)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTPR&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

RESALE (PROVISIONING)

Report Labels: PR-2-01-2200

Special Services - Provisioning

Parity with VZ Retail

Guidelines: PR-2 - Average Completed Interval

Average Interval Completed – Total No Dispatch

Result: (Numerator / Denominator)**Denominator:**

Count of orders for Orders without an outside dispatch in Product Groups

Numerator:

Sum of completion date less application date for Orders without an outside dispatch in Product Groups

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RSSS&
      AND &Exclusions&
AND &PROJECT&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Numerator

```

SELECT
SUM(CMPINTV)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RSSS&
      AND &Exclusions&
AND &PROJECT&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```
SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTSS&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
```

```
SELECT
SUM(CMPINTV)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTSS&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
```

RESALE (PROVISIONING)

Report Labels: PR-2-01-2341

Complex Services - 2 Wire Digital

Parity with VZ Retail

Guidelines: PR-2 - Average Completed Interval

Average Interval Completed – Total No Dispatch

Result: (Numerator / Denominator)**Denominator:**

Count of orders for Orders without an outside dispatch in Product Groups

Numerator:

Sum of completion date less application date for Orders without an outside dispatch in Product Groups

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RSPI&
      AND &Exclusions&
      AND &PROJECT&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
SUM(CMPINTV)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RSPI&
      AND &Exclusions&
      AND &PROJECT&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTPI&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
SUM(CMPINTV)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTPI&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

RESALE (PROVISIONING)

Report Labels: PR-2-01-2342

Complex Services - 2 Wire xDSL

Parity with VZ Retail

Guidelines: PR-2 - Average Completed Interval

Average Interval Completed – Total No Dispatch

Result: (Numerator / Denominator)**Denominator:**

Count of orders for Orders without an outside dispatch in Product Groups

Numerator:

Sum of completion date less application date for Orders without an outside dispatch in Product Groups

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RSPD&
      AND &Exclusions&
AND &PROJECT&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
SUM(CMPINTV)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RSPD&
      AND &Exclusions&
AND &PROJECT&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTPD&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
SUM(CMPINTV)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTPD&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0
or INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0
or INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

UNE (Provisioning)

Report Labels: PR-2-01-3111 POTS - Provisioning

Parity with VZ Retail

Guidelines: PR-2 - Average Completed Interval

Average Interval Completed – Total No Dispatch - Hot Cut Loop

Result: (Numerator / Denominator)**Denominator:**

Count of orders for Orders without an outside dispatch in Product Groups

Numerator:

Sum of completion date less application date for Orders without an outside dispatch in Product Groups

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &SOUNPSLH&
      AND &Exclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      and atc in ('W')
      AND &PROJECT&
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
SUM(CMPINTV)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &SOUNPSLH&
      AND &Exclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0
or INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0
or INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      and atc in ('W')
      AND &PROJECT&
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTPB&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
SUM(CMPINTV)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTPB&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```


UNE (Provisioning)

Report Labels: PR-2-01-3122 POTS - Provisioning

Parity with VZ Retail

Guidelines: PR-2 - Average Completed Interval

Average Interval Completed – Total No Dispatch - Other (Switch & INP)

Result: (Numerator / Denominator)**Denominator:**

Count of orders for Orders without an outside dispatch in Product Groups

Numerator:

Sum of completion date less application date for Orders without an outside dispatch in Product Groups

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &SOUNPSO&
      AND &Exclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
SUM(CMPINTV)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &SOUNPSO&
      AND &Exclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTPB&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
SUM(CMPINTV)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTPB&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```


UNE (Provisioning)

Report Labels: PR-2-01-3140 POTS - Provisioning

Parity with VZ Retail

Guidelines: PR-2 - Average Completed Interval

Average Interval Completed – Total No Dispatch - Platform

Result: (Numerator / Denominator)**Denominator:**

Count of orders for Orders without an outside dispatch in Product Groups

Numerator:

Sum of completion date less application date for Orders without an outside dispatch in Product Groups

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &SOUNPSP&
      AND &Exclusions&
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_NUM_DO)=0
      AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND CMPINTV BETWEEN 0 AND 200
      AND (
(ATC IN ('W') AND APPINTV between 0 and 200 AND (TYPE IN
('N','T') or (TYPE in 'C' and (OUT_QTY=0 or INWARD_QTY>0 or
CHNG_QTY>0) and (OUTWARD_CKL=0 or INWARD_CKL>0 or
CHNG_CKL>0))))
or (type in ('R') and PON is not null and APPINTV between 0 and
2) )

```

Numerator

```

SELECT
SUM(CMPINTV)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &SOUNPSP&
      AND &Exclusions&
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_NUM_DO)=0
      AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND CMPINTV BETWEEN 0 AND 200
      AND (
(ATC IN ('W') AND APPINTV between 0 and 200 AND (TYPE IN
('N','T') or (TYPE in 'C' and (OUT_QTY=0 or INWARD_QTY>0 or
CHNG_QTY>0) and (OUTWARD_CKL=0 or INWARD_CKL>0 or
CHNG_CKL>0))))
or (type in ('R') and PON is not null and APPINTV between 0 and
2) )

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTPB&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
SUM(CMPINTV)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTPB&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

UNE (Provisioning)

Report Labels: PR-2-01-3200 Special Services Provisioning Parity with VZ Retail

Guidelines: PR-2 - Average Completed Interval

Average Interval Completed – Total No Dispatch

Result: (Numerator / Denominator)	
Denominator:	Numerator:
Count of orders for Orders without an outside dispatch in Product Groups	Sum of completion date less application date for Orders without an outside dispatch in Product Groups

Filtered output file: ASR-UNE-SPECIAL

For the details on the above out put filtered file layout refer to File Appendix: 7 File Type: Excel

Denominator	Numerator
<div>SELECT COUNT(*) WHERE STATE = NJ AND ACTIVITY_DATE >= STARTDATE AND ACTIVITY_DATE <= ENDDATE AND ACT IN ('N', 'C') AND PRODUCT_TYPE IN ('DS1', 'DS3') AND DISPATCH_YN = N AND NVL(SUBSTR(WFA_MFC,1,1),'X') NOT IN ('C', 'D') AND W_CODED_YN = Y AND ASR_STATUS = C AND COMPLETED_INTERVAL <= 200</div>	<div>SELECT SUM(COMPLETED_INTERVAL) WHERE STATE = NJ AND ACTIVITY_DATE >= STARTDATE AND ACTIVITY_DATE <= ENDDATE AND ACT IN ('N', 'C') AND PRODUCT_TYPE IN ('DS1', 'DS3') AND DISPATCH_YN = N AND NVL(SUBSTR(WFA_MFC,1,1),'X') NOT IN ('C', 'D') AND W_CODED_YN = Y AND ASR_STATUS = C AND COMPLETED_INTERVAL <= 200</div>

UNE (Provisioning)

Report Labels: PR-2-01-3341

Complex Services - 2 Wire Digital

Parity with VZ Retail

Guidelines: PR-2 - Average Completed Interval

Average Interval Completed – Total No Dispatch

Result: (Numerator / Denominator)**Denominator:**

Count of orders for Orders without an outside dispatch in Product Groups

Numerator:

Sum of completion date less application date for Orders without an outside dispatch in Product Groups

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTPI&
      AND &RetailExclusions&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC in ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
SUM(CMPINTV)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTPI&
      AND &RetailExclusions&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC in ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTPI&
      AND &RetailExclusions&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC in ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
SUM(CMPINTV)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTPI&
      AND &RetailExclusions&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC in ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```


UNE (Provisioning)

Report Labels: PR-2-01-3342 Complex Services - 2 Wire xDSL

Parity with VZ Retail

Guidelines: PR-2 - Average Completed Interval

Average Interval Completed – Total No Dispatch

Result: (Numerator / Denominator)**Denominator:**

Count of orders for Orders without an outside dispatch in Product Groups

Numerator:

Sum of completion date less application date for Orders without an outside dispatch in Product Groups

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &SOUNPD&
      AND &Exclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
SUM(CMPINTV)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &SOUNPD&
      AND &Exclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0
or INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0
or INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTPD&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
SUM(CMPINTV)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTPD&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0
or INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0
or INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```


RESALE (PROVISIONING)

Report Labels: PR-2-02-2200 Special Services - Provisioning

Parity with VZ Retail

Guidelines: PR-2 - Average Completed Interval

Average Interval Completed – Total Dispatch

Result: (Numerator / Denominator)**Denominator:**

Count of orders for Orders with an outside dispatch in Product Groups.

Numerator:

Sum of completion date less application date for Orders with an outside dispatch in Product Groups.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RSSS&
      AND &Exclusions&
      AND &PROJECT&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE =R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND (ATC in ('W')or(TYPE =R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
SUM(CMPINTV)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RSSS&
      AND &Exclusions&
      AND &PROJECT&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE =R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND (ATC in ('W')or(TYPE =R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTSS&
      AND &RetailExclusions&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC in ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
SUM(CMPINTV)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTSS&
      AND &RetailExclusions&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC in ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```


RESALE (PROVISIONING)

Report Labels: PR-2-02-2341

Complex Services - 2 Wire Digital

Parity with VZ Retail

Guidelines: PR-2 - Average Completed Interval

Average Interval Completed – Total Dispatch

Result: (Numerator / Denominator)**Denominator:**

Count of orders for Orders with an outside dispatch in Product Groups.

Numerator:

Sum of completion date less application date for Orders with an outside dispatch in Product Groups.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RSPI&
      AND &Exclusions&
      AND &PROJECT&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE =R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND (ATC IN ('W')or(TYPE =R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
SUM(CMPINTV)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RSPI&
      AND &Exclusions&
      AND &PROJECT&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE =R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND (ATC IN ('W')or(TYPE =R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTPI&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
SUM(CMPINTV)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTPI&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```


RESALE (PROVISIONING)

Report Labels: PR-2-02-2342 Complex Services - 2 Wire xDSL

Parity with VZ Retail

Guidelines: PR-2 - Average Completed Interval

Average Interval Completed – Total Dispatch

Result: (Numerator / Denominator)**Denominator:**

Count of orders for Orders with an outside dispatch in Product Groups.

Numerator:

Sum of completion date less application date for Orders with an outside dispatch in Product Groups.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RSPD&
      AND &Exclusions&
      AND &PROJECT&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE =R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND (ATC IN ('W')or(TYPE =R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Numerator

```

SELECT
SUM(CMPINTV)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RSPD&
      AND &Exclusions&
      AND &PROJECT&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE =R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND (ATC IN ('W')or(TYPE =R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTPD&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Numerator

```

SELECT
SUM(CMPINTV)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTPD&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```


UNE (Provisioning)

Report Labels: PR-2-02-3200 Special Services Provisioning

Parity with VZ Retail

Guidelines: PR-2 - Average Completed Interval

Average Interval Completed – Total Dispatch

Result: (Numerator / Denominator)**Denominator:**

Count of orders for Orders with an outside dispatch in Product Groups.

Numerator:

Sum of completion date less application date for Orders with an outside dispatch in Product Groups.

Filtered output file: ASR-UNE-SPECIAL

For the details on the above out put filtered file layout refer to File Appendix: 7 File Type: Excel

Denominator

```
SELECT
COUNT(*)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND ACT IN ('N', 'C')
AND PRODUCT_TYPE IN ('DS1', 'DS3')
AND DISPATCH_YN = Y
AND NVL(SUBSTR(WFA_MFC,1,1),'X') NOT IN ('C', 'D')
AND W_CODED_YN = Y
AND ASR_STATUS = C
AND COMPLETED_INTERVAL <= 200
```

Numerator

```
SELECT
SUM(COMPLETED_INTERVAL)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND ACT IN ('N', 'C')
AND PRODUCT_TYPE IN ('DS1', 'DS3')
AND DISPATCH_YN = Y
AND NVL(SUBSTR(WFA_MFC,1,1),'X') NOT IN ('C', 'D')
AND W_CODED_YN = Y
AND ASR_STATUS = C
AND COMPLETED_INTERVAL <= 200
```

UNE (Provisioning)

Report Labels: PR-2-02-3341

Complex Services - 2 Wire Digital

Parity with VZ Retail

Guidelines: PR-2 - Average Completed Interval

Average Interval Completed – Total Dispatch

Result: (Numerator / Denominator)**Denominator:**

Count of orders for Orders with an outside dispatch in Product Groups.

Numerator:

Sum of completion date less application date for Orders with an outside dispatch in Product Groups.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &SOUNPI&
      AND &PROJECT&
      AND &Exclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Numerator

```

SELECT
SUM(CMPINTV)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &SOUNPI&
      AND &PROJECT&
      AND &Exclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTPI&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Numerator

```

SELECT
SUM(CMPINTV)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTPI&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

UNE (Provisioning)

Report Labels: PR-2-02-3342

Complex Services - 2 Wire xDSL

Parity with VZ Retail

Guidelines: PR-2 - Average Completed Interval

Average Interval Completed – Total Dispatch

Result: (Numerator / Denominator)**Denominator:**

Count of orders for Orders with an outside dispatch in Product Groups.

Numerator:

Sum of completion date less application date for Orders with an outside dispatch in Product Groups.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &SOUNPD&
      AND &Exclusions&
      AND &PROJECT&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
SUM(CMPINTV)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &SOUNPD&
      AND &Exclusions&
      AND &PROJECT&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0
or INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0
or INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTPD&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
SUM(CMPINTV)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTPD&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

RESALE (PROVISIONING)

Report Labels: PR-2-03-2110

POTS - Business

Parity with VZ Retail

Guidelines: PR-2 - Average Completed Interval

Average Interval Completed – Dispatch (1-5 Lines)

Result: (Numerator / Denominator)**Denominator:**

Count of orders for POTS Orders with 1 to 5 lines with an outside dispatch in Product Groups.

Numerator:

Sum of completion date less application date for POTS Orders with 1 to 5 lines with an outside dispatch in Product Groups.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```

SELECT
sum(count(order_num))
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RSPB&
      AND &Exclusions&
      AND &PROJECT&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
having sum(to_number(inward_qty+CHNG_QTY)) BETWEEN 1
AND 5
group by order_num,entity, type, cmpintv

```

Numerator

```

SELECT
sum(min(cmpintv))
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RSPB&
      AND &Exclusions&
      AND &PROJECT&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0
or INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0
or INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
having sum(to_number(inward_qty+CHNG_QTY)) BETWEEN 1
AND 5
group by order_num,entity, type, cmpintv

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
sum(count(order_num))
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTPB&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
having sum(to_number(inward_qty+CHNG_QTY)) BETWEEN 1
AND 5
group by order_num, entity, type, cmpintv

```

```

SELECT
sum(min(cmpintv))
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTPB&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0
or INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0
or INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
having sum(to_number(inward_qty+CHNG_QTY)) BETWEEN 1
AND 5
group by order_num, entity, type, cmpintv

```

RESALE (PROVISIONING)

Report Labels: PR-2-03-2120 POTS - Residence

Parity with VZ Retail

Guidelines: PR-2 - Average Completed Interval

Average Interval Completed – Dispatch (1-5 Lines)

Result: (Numerator / Denominator)**Denominator:**

Count of orders for POTS Orders with 1 to 5 lines with an outside dispatch in Product Groups.

Numerator:

Sum of completion date less application date for POTS Orders with 1 to 5 lines with an outside dispatch in Product Groups.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```

SELECT
sum(count(order_num))
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RSPR&
      AND &Exclusions&
AND &PROJECT&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND (ATC in ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
having sum(to_number(inward_qty+CHNG_QTY)) BETWEEN 1
AND 5
group by order_num, entity, type, cmpintv

```

Numerator

```

SELECT
sum(min(cmpintv))
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RSPR&
      AND &Exclusions&
AND &PROJECT&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND (ATC in ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
having sum(to_number(inward_qty+CHNG_QTY)) BETWEEN 1
AND 5
group by order_num, entity, type, cmpintv

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
sum(count(order_num))
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTPR&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
having sum(to_number(inward_qty+CHNG_QTY)) BETWEEN 1
AND 5
group by order_num, entity, type, cmpintv

```

```

SELECT
sum(min(cmpintv))
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTPR&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0
or INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0
or INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
having sum(to_number(inward_qty+CHNG_QTY)) BETWEEN 1
AND 5
group by order_num, entity, type, cmpintv

```

UNE (Provisioning)

Report Labels: PR-2-03-3112 POTS - Provisioning

Parity with VZ Retail

Guidelines: PR-2 - Average Completed Interval

Average Interval Completed – Dispatch (1-5 Lines) - Loop

Result: (Numerator / Denominator)**Denominator:**

Count of orders for POTS Orders with 1 to 5 lines with an outside dispatch in Product Groups.

Numerator:

Sum of completion date less application date for POTS Orders with 1 to 5 lines with an outside dispatch in Product Groups.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```
SELECT
sum(count(order_num))
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &SOUNPSL&
      AND &Exclusions
      AND &PROJECT&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0
or INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0
or INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC in ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
having sum(to_number(inward_qty+CHNG_QTY)) BETWEEN 1
AND 5
group by order_num, entity, type, cmpintv
```

```
SELECT
sum(min(cmpintv))
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &SOUNPSL&
      AND &Exclusions
      AND &PROJECT&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0
or INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0
or INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC in ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
having sum(to_number(inward_qty+CHNG_QTY)) BETWEEN 1
AND 5
group by order_num, entity, type, cmpintv
```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**


```

SELECT
sum(count(order_num))
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTPB&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
having sum(to_number(inward_qty+CHNG_QTY)) BETWEEN 1
AND 5
group by order_num, entity, type, cmpintv

```

```

SELECT
sum(min(cmpintv))
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTPB&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0
or INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0
or INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
having sum(to_number(inward_qty+CHNG_QTY)) BETWEEN 1
AND 5
group by order_num, entity, type, cmpintv

```

UNE (Provisioning)

Report Labels: PR-2-03-3140

POTS - Provisioning

Parity with VZ Retail

Guidelines: PR-2 - Average Completed Interval

Average Interval Completed – Dispatch (1-5 Lines) - Platform

Result: (Numerator / Denominator)**Denominator:**

Count of orders for POTS Orders with 1 to 5 lines with an outside dispatch in Product Groups.

Numerator:

Sum of completion date less application date for POTS Orders with 1 to 5 lines with an outside dispatch in Product Groups.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```

SELECT
sum(count(order_num))
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &SOUNPSP&
AND &PROJECT&
      AND &Exclusions&
      AND (
(ATC IN ('W') AND APPINTV between 0 and 200 AND ((TYPE IN
('N','T')) or (TYPE in 'C' and (OUT_QTY=0 or INWARD_QTY>0 or
CHNG_QTY>0) and (OUTWARD_CKL=0 or INWARD_CKL>0 or
CHNG_CKL>0))))
or (type in ('R') and PON is not null and APPINTV between 0 and
2) )
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN
(&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
having sum(to_number(inward_qty+CHNG_QTY)) BETWEEN 1
AND 5
group by order_num, entity, type, cmpintv

```

Numerator

```

SELECT
sum(min(cmpintv))
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &SOUNPSP&
AND &PROJECT&
      AND &Exclusions&
      AND (
(ATC IN ('W') AND APPINTV between 0 and 200 AND ((TYPE IN
('N','T')) or (TYPE in 'C' and (OUT_QTY=0 or INWARD_QTY>0 or
CHNG_QTY>0) and (OUTWARD_CKL=0 or INWARD_CKL>0 or
CHNG_CKL>0))))
or (type in ('R') and PON is not null and APPINTV between 0 and
2) )
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND CMPINTV between 0 and 200
      AND NVL(SELLER_NAME,0) NOT IN
(&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
having sum(to_number(inward_qty+CHNG_QTY)) BETWEEN 1
AND 5
group by order_num, entity, type, cmpintv

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
sum(count(order_num))
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTPB&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
having sum(to_number(inward_qty+CHNG_QTY)) BETWEEN 1
AND 5
group by order_num, entity, type, cmpintv

```

```

SELECT
sum(min(cmpintv))
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTPB&
      AND &RetailExclusions&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0
or INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0
or INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
having sum(to_number(inward_qty+CHNG_QTY)) BETWEEN 1
AND 5
group by order_num, entity, type, cmpintv

```

RESALE (PROVISIONING)

Report Labels: PR-2-04-2100 POTS - Provisioning - Total

Parity with VZ Retail

Guidelines: PR-2 - Average Completed Interval

Average Interval Completed - Dispatch (6-9 Lines)

Result: (Numerator / Denominator)**Denominator:**

Count of orders for POTS Orders with 6 to 9 lines with an outside dispatch in Product Groups

Numerator:

Sum of completion date less application date for POTS Orders with 6 to 9 lines with an outside dispatch in Product Groups.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
sum(count(order_num))
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RSPS&
      AND &Exclusions&
      AND &PROJECT&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
having sum(to_number(inward_qty+CHNG_QTY)) BETWEEN 6
AND 9
group by order_num, entity, type, cmpintv

```

```

SELECT
sum(min(cmpintv))
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RSPS&
      AND &Exclusions&
      AND &PROJECT&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
having sum(to_number(inward_qty+CHNG_QTY)) BETWEEN 6
AND 9
group by order_num, entity, type, cmpintv

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
sum(count(order_num))
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTPS&
      AND &RetailExclusions&
AND &PROJECT&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
having sum(to_number(inward_qty+CHNG_QTY)) BETWEEN 6
AND 9
group by order_num, entity, type, cmpintv

```

```

SELECT
sum(min(cmpintv))
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTPS&
      AND &RetailExclusions&
AND &PROJECT&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0
or INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0
or INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
having sum(to_number(inward_qty+CHNG_QTY)) BETWEEN 6
AND 9
group by order_num, entity, type, cmpintv

```

UNE (Provisioning)

Report Labels: PR-2-04-3112 POTS - Provisioning

Parity with VZ Retail

Guidelines: PR-2 - Average Completed Interval

Average Interval Completed - Dispatch (6-9 Lines) - Loop

Result: (Numerator / Denominator)**Denominator:**

Count of orders for POTS Orders with 6 to 9 lines with an outside dispatch in Product Groups

Numerator:

Sum of completion date less application date for POTS Orders with 6 to 9 lines with an outside dispatch in Product Groups.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```
SELECT
sum(count(order_num))
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &SOUNPSL&
      AND &Exclusions&
      AND &PROJECT&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC in ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
having sum(to_number(inward_qty+CHNG_QTY)) BETWEEN 6
AND 9
group by order_num, entity, type, cmpintv
```

Numerator

```
SELECT
sum(min(cmpintv))
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &SOUNPSL&
      AND &Exclusions&
      AND &PROJECT&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC in ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
having sum(to_number(inward_qty+CHNG_QTY)) BETWEEN 6
AND 9
group by order_num, entity, type, cmpintv
```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
sum(count(order_num))
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTPS&
      AND &RetailExclusions&
AND &PROJECT&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
having sum(to_number(inward_qty+CHNG_QTY)) BETWEEN 6
AND 9
group by order_num, entity, type, cmpintv

```

```

SELECT
sum(min(cmpintv))
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTPS&
      AND &RetailExclusions&
AND &PROJECT&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0
or INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0
or INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
having sum(to_number(inward_qty+CHNG_QTY)) BETWEEN 6
AND 9
group by order_num, entity, type, cmpintv

```

UNE (Provisioning)

Report Labels: PR-2-04-3140

POTS - Provisioning

Parity with VZ Retail

Guidelines: PR-2 - Average Completed Interval

Average Interval Completed - Dispatch (6-9 Lines) - Platform

Result: (Numerator / Denominator)**Denominator:**

Count of orders for POTS Orders with 6 to 9 lines with an outside dispatch in Product Groups

Numerator:

Sum of completion date less application date for POTS Orders with 6 to 9 lines with an outside dispatch in Product Groups.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```
SELECT
sum(count(order_num))
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &SOUNPSP&
      AND &Exclusions&
      AND &PROJECT&
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_NUM_DO)>0
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
(
(TYPE IN ('N','T') or (TYPE = 'C'
      AND (OUT_QTY=0 or INWARD_QTY>0 or CHNG_QTY>0)
      AND (OUTWARD_CKL=0 or INWARD_CKL>0 or
CHNG_CKL>0))
      AND ATC = 'W'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200)
OR
(TYPE = 'R'
      AND PON IS NOT NULL
      AND NVL(APPINTV,0) IN (0,1,2))
)
having sum(to_number(inward_qty+CHNG_QTY)) BETWEEN 6
AND 9
group by order_num, entity, type, cmpintv
```

Numerator

```
SELECT
sum(min(cmpintv))
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &SOUNPSP&
      AND &Exclusions&
      AND &PROJECT&
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_NUM_DO)>0
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
(
(TYPE IN ('N','T') or (TYPE = 'C'
      AND (OUT_QTY=0 or INWARD_QTY>0 or CHNG_QTY>0)
      AND (OUTWARD_CKL=0 or INWARD_CKL>0 or
CHNG_CKL>0))
      AND ATC = 'W'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200)
OR
(TYPE = 'R'
      AND PON IS NOT NULL
      AND NVL(APPINTV,0) IN (0,1,2))
)
having sum(to_number(inward_qty+CHNG_QTY)) BETWEEN 6
AND 9
group by order_num, entity, type, cmpintv
```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**


```

SELECT
sum(count(order_num))
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTPS&
      AND &RetailExclusions&
AND &PROJECT&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
having sum(to_number(inward_qty+CHNG_QTY)) BETWEEN 6
AND 9
group by order_num, entity, type, cmpintv

```

```

SELECT
sum(min(cmpintv))
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTPS&
      AND &RetailExclusions&
AND &PROJECT&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0
or INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0
or INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
having sum(to_number(inward_qty+CHNG_QTY)) BETWEEN 6
AND 9
group by order_num, entity, type, cmpintv

```

RESALE (PROVISIONING)

Report Labels: PR-2-05-2100 POTS - Provisioning - Total

Parity with VZ Retail

Guidelines: PR-2 - Average Completed Interval

Average Interval Completed - Dispatch (>= 10 Lines)

Result: (Numerator / Denominator)**Denominator:**

Count of orders for POTS Orders with 10 or more lines with an outside dispatch in Product Groups.

Numerator:

Sum of completion date less application date for POTS Orders with 10 or more lines with an outside dispatch in Product Groups.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```
SELECT
sum(count(order_num))
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RSPS&
      AND &Exclusions
AND &PROJECT&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
having sum(to_number(inward_qty+CHNG_QTY)) > 9
group by order_num, entity, type, cmpintv
```

Numerator

```
SELECT
sum(min(cmpintv))
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RSPS&
      AND &Exclusions
AND &PROJECT&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
having sum(to_number(inward_qty+CHNG_QTY)) > 9
group by order_num, entity, type, cmpintv
```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
sum(count(order_num))
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTPS&
      AND &RetailExclusions
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
having sum(to_number(inward_qty+CHNG_QTY)) > 9
group by order_num, entity, type, cmpintv

```

```

SELECT
sum(min(cmpintv))
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTPS&
      AND &RetailExclusions
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0
or INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0
or INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
having sum(to_number(inward_qty+CHNG_QTY)) > 9
group by order_num, entity, type, cmpintv

```

UNE (Provisioning)

Report Labels: PR-2-05-3112 POTS - Provisioning

Parity with VZ Retail

Guidelines: PR-2 - Average Completed Interval

Average Interval Completed - Dispatch (>= 10 Lines) - Loop

Result: (Numerator / Denominator)**Denominator:**

Count of orders for POTS Orders with 10 or more lines with an outside dispatch in Product Groups.

Numerator:

Sum of completion date less application date for POTS Orders with 10 or more lines with an outside dispatch in Product Groups.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```
SELECT
sum(count(order_num))
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &SOUNPSL&
      AND &Exclusions
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0
or INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0
or INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
having sum(to_number(inward_qty+CHNG_QTY)) > 9
group by order_num, entity, type, cmpintv
```

Numerator

```
SELECT
sum(min(cmpintv))
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &SOUNPSL&
      AND &Exclusions
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0
or INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0
or INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
having sum(to_number(inward_qty+CHNG_QTY)) > 9
group by order_num, entity, type, cmpintv
```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
sum(count(order_num))
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTPS&
      AND &RetailExclusions
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
having sum(to_number(inward_qty+CHNG_QTY)) > 9
group by order_num, entity, type, cmpintv

```

```

SELECT
sum(min(cmpintv))
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTPS&
      AND &RetailExclusions
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0
or INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0
or INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
having sum(to_number(inward_qty+CHNG_QTY)) > 9
group by order_num, entity, type, cmpintv

```

UNE (Provisioning)

Report Labels: PR-2-05-3140 POTS - Provisioning

Parity with VZ Retail

Guidelines: PR-2 - Average Completed Interval

Average Interval Completed - Dispatch (>= 10 Lines) - Platform

Result: (Numerator / Denominator)**Denominator:**

Count of orders for POTS Orders with 10 or more lines with an outside dispatch in Product Groups.

Numerator:

Sum of completion date less application date for POTS Orders with 10 or more lines with an outside dispatch in Product Groups.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```
SELECT
sum(count(order_num))
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &SOUNPSP&
      AND &Exclusions
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
      (
      (TYPE IN ('N','T') or (TYPE =
      AND (OUT_QTY=0 or INWARD_QTY>0
CHNG_QTY>0)
      AND (OUTWARD_CKL=0 or INWARD_CKL>0
CHNG_CKL>0))
      AND ATC = 'W'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200)
      OR
      (TYPE = 'R'
      AND PON IS NOT NULL
      AND NVL(APPINTV,0) IN (0,1,2))

having sum(to_number(inward_qty+CHNG_QTY)) > 9
group by order_num, entity, type, cmpintv
```

Numerator

```
SELECT
sum(min(cmpintv))
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &SOUNPSP&
      AND &Exclusions
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
      (
      (TYPE IN ('N','T') or (TYPE =
      AND (OUT_QTY=0 or INWARD_QTY>0
CHNG_QTY>0)
      AND (OUTWARD_CKL=0 or INWARD_CKL>0
CHNG_CKL>0))
      AND ATC = 'W'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200)
      OR
      (TYPE = 'R'
      AND PON IS NOT NULL
      AND NVL(APPINTV,0) IN (0,1,2))

having sum(to_number(inward_qty+CHNG_QTY)) > 9
group by order_num, entity, type, cmpintv
```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
sum(count(order_num))
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTPS&
      AND &RetailExclusions
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
having sum(to_number(inward_qty+CHNG_QTY)) > 9
group by order_num, entity, type, cmpintv

```

```

SELECT
sum(min(cmpintv))
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTPS&
      AND &RetailExclusions
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0
or INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0
or INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
having sum(to_number(inward_qty+CHNG_QTY)) > 9
group by order_num, entity, type, cmpintv

```

RESALE (PROVISIONING)

Report Labels: PR-2-06-2210 Special Services - Provisioning

Parity with VZ Retail

Guidelines: PR-2 - Average Completed Interval

Average Interval Completed - DSO

Result: (Numerator / Denominator)**Denominator:**

Count of orders for Special Services DSO Orders

Numerator:

Sum of completion date less application date for Special Services DSO Orders.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RSSS&
      AND &Exclusions
AND &PROJECT&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND &DSO&

```

```

SELECT
SUM(CMPINTV)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RSSS&
      AND &Exclusions
AND &PROJECT&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND &DSO&

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTSS&
      AND &RetailExclusions
AND &PROJECT&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND &DSO&

```

```

SELECT
SUM(CMPINTV)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTSS&
      AND &RetailExclusions
AND &PROJECT&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0
or INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0
or INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND &DSO&

```


UNE (Provisioning)

Report Labels:	PR-2-06-3210	Special Services Provisioning	Parity with VZ Retail
Guidelines:	PR-2 - Average Completed Interval		
	Average Interval Completed - DS0		

Result: (Numerator / Denominator)	
Denominator:	Numerator:
Count of orders for Special Services DS0 Orders	Sum of completion date less application date for Special Services DS0 Orders.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON

Denominator	Numerator
-------------	-----------

RESALE (PROVISIONING)

Report Labels: PR-2-07-2211

Special Services - Provisioning

Parity with VZ Retail

Guidelines: PR-2 - Average Completed Interval

Average Interval Completed – DS1

Result: (Numerator / Denominator)**Denominator:**

Count of orders for Special Services DS1 Orders.

Numerator:

Sum of completion date less application date for Special Services DS1 Orders.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RSSS&
      AND &Exclusions
AND &PROJECT&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND &DS1&

```

```

SELECT
SUM(CMPINTV)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RSSS&
      AND &Exclusions
AND &PROJECT&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND &DS1&

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTSS&
      AND &RetailExclusions
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&test_sellers&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND &DS1&

```

```

SELECT
SUM(CMPINTV)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTSS&
      AND &RetailExclusions
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&test_sellers&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND &DS1&

```

UNE (Provisioning)

Report Labels: PR-2-07-3211 Special Services Provisioning

Parity with VZ Retail

Guidelines: PR-2 - Average Completed Interval

Average Interval Completed – DS1

Result: (Numerator / Denominator)**Denominator:**

Count of orders for Special Services DS1 Orders.

Numerator:

Sum of completion date less application date for Special Services DS1 Orders.

Filtered output file: ASR-UNE-SPECIAL

For the details on the above out put filtered file layout refer to File Appendix: 7 File Type: Excel

Denominator

```
SELECT
COUNT(*)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND ACT IN ('N', 'C')
AND PRODUCT_TYPE = DS1
AND NVL(SUBSTR(WFA_MFC,1,1),'X') NOT IN ('C','D')
AND W_CODED_YN = Y
AND ASR_STATUS = C
AND COMPLETED_INTERVAL <= 200
```

Numerator

```
SELECT
SUM(COMPLETED_INTERVAL)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND ACT IN ('N', 'C')
AND PRODUCT_TYPE = DS1
AND NVL(SUBSTR(WFA_MFC,1,1),'X') NOT IN ('C','D')
AND W_CODED_YN = Y
AND ASR_STATUS = C
AND COMPLETED_INTERVAL <= 200
```

RESALE (PROVISIONING)

Report Labels: PR-2-08-2213 Special Services - Provisioning

Parity with VZ Retail

Guidelines: PR-2 - Average Completed Interval

Average Interval Completed – DS3

Result: (Numerator / Denominator)**Denominator:**

Count of orders for Special Services DS3 Orders.

Numerator:

Sum of completion date less application date for Special Services DS3 Orders.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RSSS&
      AND &Exclusions
AND &PROJECT&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND &DS3&

```

```

SELECT
SUM(CMPINTV)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RSSS&
      AND &Exclusions
AND &PROJECT&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND &DS3&

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTSS&
      AND &RetailExclusions
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND &DS3&

```

```

SELECT
SUM(CMPINTV)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTSS&
      AND &RetailExclusions
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0
or INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0
or INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND &DS3&

```

UNE (Provisioning)

Report Labels: PR-2-08-3213 Special Services Provisioning

Parity with VZ Retail

Guidelines: PR-2 - Average Completed Interval

Average Interval Completed – DS3

Result: (Numerator / Denominator)**Denominator:**

Count of orders for Special Services DS3 Orders.

Numerator:

Sum of completion date less application date for Special Services DS3 Orders.

Filtered output file: ASR-UNE-SPECIAL

For the details on the above out put filtered file layout refer to File Appendix: 7 File Type: Excel

Denominator

```
SELECT
COUNT(*)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND ACT IN ('N', 'C')
AND PRODUCT_TYPE = DS3
AND NVL(SUBSTR(WFA_MFC,1,1),'X') NOT IN ('C','D')
AND W_CODED_YN = Y
AND ASR_STATUS = C
AND COMPLETED_INTERVAL <= 200
```

Numerator

```
SELECT
SUM(COMPLETED_INTERVAL)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND ACT IN ('N', 'C')
AND PRODUCT_TYPE = DS3
AND NVL(SUBSTR(WFA_MFC,1,1),'X') NOT IN ('C','D')
AND W_CODED_YN = Y
AND ASR_STATUS = C
AND COMPLETED_INTERVAL <= 200
```

UNE (Provisioning)

Report Labels: PR-2-09-3510 Special Services Provisioning

Not greater than applicable interval stated in
VZ Product Interval Guide

Guidelines: PR-2 - Average Completed Interval

Average Interval Completed – EEL

Result: (Numerator / Denominator)**Denominator:**

Count of orders for orders within product groups.

Numerator:

Sum of completion date less application date for orders within product groups.

Filtered output file: ASR-UNE-SPECIAL

For the details on the above out put filtered file layout refer to File Appendix: 7 File Type: Excel

Denominator

```
SELECT
COUNT(*)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND ACT IN ('N', 'C')
AND PRODUCT_TYPE = EEL
AND NVL(SUBSTR(WFA_MFC,1,1),'X') NOT IN ('C','D')
AND W_CODED_YN = Y
AND ASR_STATUS = C
AND COMPLETED_INTERVAL <= 200
```

Numerator

```
SELECT
SUM(COMPLETED_INTERVAL)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND ACT IN ('N', 'C')
AND PRODUCT_TYPE = EEL
AND NVL(SUBSTR(WFA_MFC,1,1),'X') NOT IN ('C','D')
AND W_CODED_YN = Y
AND ASR_STATUS = C
AND COMPLETED_INTERVAL <= 200
```

UNE (Provisioning)

Report Labels: PR-2-09-3530 Special Services Provisioning

Not greater than applicable interval stated in
VZ Product Interval Guide

Guidelines: PR-2 - Average Completed Interval

Average Interval Completed – IOF

Result: (Numerator / Denominator)**Denominator:**

Count of orders for orders within product groups.

Numerator:

Sum of completion date less application date for orders within product groups.

Filtered output file: ASR-UNE-SPECIAL

For the details on the above out put filtered file layout refer to File Appendix: 7 File Type: Excel

Denominator

```
SELECT
COUNT(*)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND ACT IN ('N', 'C')
AND PRODUCT_TYPE = IOF
AND NVL(SUBSTR(WFA_MFC,1,1),'X') NOT IN ('C','D')
AND W_CODED_YN = Y
AND ASR_STATUS = C
AND COMPLETED_INTERVAL <= 200
```

Numerator

```
SELECT
SUM(COMPLETED_INTERVAL)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND ACT IN ('N', 'C')
AND PRODUCT_TYPE = IOF
AND NVL(SUBSTR(WFA_MFC,1,1),'X') NOT IN ('C','D')
AND W_CODED_YN = Y
AND ASR_STATUS = C
AND COMPLETED_INTERVAL <= 200
```

TRUNKS (Aggregate)

Report Labels: PR-2-09-5020 PROVISIONING

Parity with IXC / FGD

Guidelines: PR-2 - Average Interval Completed

Average Interval Completed – Total <= 192 Forecasted Trunks

Result: (Numerator / Denominator)**Denominator:**

Count of orders for orders within product groups.

Numerator:

Sum of completion date less application date for orders within product groups.

Filtered output file: Trunking Filter Data

For the details on the above out put filtered file layout refer to File Appendix: 4 File Type: Excel

Formula For: CLEC**Denominator****Numerator**

```
SELECT
COUNT(SERVICE_ORDER_NO)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND SERVICE_TYPE = T
AND CREATE_CDDD_INTERVAL <= 18
AND CNR_YN = N
AND PROJECT_YN = N
AND NEW_OR_AUGMENT = A
AND ASR_TRUNK_SIZE <= 192
AND FORECAST_YN = Y
AND ORDER_STATUS = C
```

```
SELECT
SUM(WFA_COMPLETED_INTERVAL)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND SERVICE_TYPE = T
AND CREATE_CDDD_INTERVAL <= 18
AND CNR_YN = N
AND PROJECT_YN = N
AND NEW_OR_AUGMENT = A
AND ASR_TRUNK_SIZE <= 192
AND FORECAST_YN = Y
AND ORDER_STATUS = C
```


TRUNKS (Aggregate)

Report Labels: PR-2-09-5030 PROVISIONING

Parity with IXC / FGD

Guidelines: PR-2 - Average Interval Completed

Average Interval Completed – Total > 192 Forecasted & Unforecasted

Result: (Numerator / Denominator)**Denominator:**

Count of orders for orders within product groups.

Numerator:

Sum of completion date less application date for orders within product groups.

Filtered output file: Trunking Filter Data

For the details on the above out put filtered file layout refer to File Appendix: 4 File Type: Excel

Formula For: VERIZON**Denominator**

```
SELECT
COUNT(SERVICE_ORDER_NO)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND SERVICE_TYPE IN ('I', 'W')
AND CREATE_CDDD_INTERVAL <= 18
AND CNR_YN = N
AND PROJECT_YN = N
AND NEW_OR_AUGMENT = A
AND (( ASR_TRUNK_SIZE <= 192
AND FORECAST_YN = N )
OR ASR_TRUNK_SIZE >= 193
AND ASR_TRUNK_SIZE <= 384 )
AND ORDER_STATUS = C
```

Numerator

```
SELECT
SUM(WFA_COMPLETED_INTERVAL)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND SERVICE_TYPE IN ('I', 'W')
AND CREATE_CDDD_INTERVAL <= 18
AND CNR_YN = N
AND PROJECT_YN = N
AND NEW_OR_AUGMENT = A
AND (( ASR_TRUNK_SIZE <= 192
AND FORECAST_YN = N )
OR ASR_TRUNK_SIZE >= 193
AND ASR_TRUNK_SIZE <= 384 )
AND ORDER_STATUS = C
```

RESALE (PROVISIONING)

Report Labels: PR-2-10-2103 POTS & Complex Aggregate

Parity with VZ Retail

Guidelines: PR-2 - Average Completed Interval

Average Interval Completed – Disconnects – No Dispatch

Result: (Numerator / Denominator)**Denominator:**

Count of no dispatch disconnect orders for product group.

Numerator:

Sum of completion date less application date for product group no dispatch disconnect (D&F) orders.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&' and nvl(out_seller,0) not in
('BAND','BNK')
    AND &RSPDisc&
    AND &Exclusions
    AND STATUS in &STATUS&
    AND TYPE IN ('D','F')
    AND NVL(CISR_MAC,1) NOT LIKE 'S%'
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_NUM_DO)=0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(OUT_SELLER,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
UNION
SELECT COUNT(ORDER_NUM),
SUM(CMPINTV),SUM(CMPINTV)/COUNT(ORDER_NUM),SUM(POWER(CMPINTV,2)) C
FROM &DATAPATH&
WHERE STATE = '&ST&'
    AND &RSP&
    AND &Exclusions
    AND STATUS in &STATUS&
    AND NVL(CISR_MAC,1) NOT LIKE 'S%'
    AND (TYPE in 'C' AND SELLER_TYPE = 'R' and
(OUT_QTY>0 or OUTWARD_CKL>0 ) and INWARD_QTY=0 and
CHNG_QTY=0 and INWARD_CKL=0 and CHNG_CKL=0)
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_NUM_DO)=0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
    AND NVL(ATC,0) not in ('S','X')

```

```

SELECT
SUM(CMPINTV)
WHERE STATE = '&ST&' and nvl(out_seller,0) not in
('BAND','BNK')
    AND &RSPDisc&
    AND &Exclusions
    AND STATUS in &STATUS&
    AND TYPE IN ('D','F')
    AND NVL(CISR_MAC,1) NOT LIKE 'S%'
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_NUM_DO)=0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(OUT_SELLER,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
UNION
SELECT COUNT(ORDER_NUM),
SUM(CMPINTV),SUM(CMPINTV)/COUNT(ORDER_NUM),SUM(POWER(CMPINTV,2)) C
FROM &DATAPATH&
WHERE STATE = '&ST&'
    AND &RSP&
    AND &Exclusions
    AND STATUS in &STATUS&
    AND NVL(CISR_MAC,1) NOT LIKE 'S%'
    AND (TYPE in 'C' AND SELLER_TYPE = 'R' and
(OUT_QTY>0 or OUTWARD_CKL>0 ) and INWARD_QTY=0 and
CHNG_QTY=0 and INWARD_CKL=0 and CHNG_CKL=0)
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_NUM_DO)=0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
    AND NVL(ATC,0) not in ('S','X')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&' and nvl(out_seller,0) not in
('BAND','BNK')
    AND &RTPDisc&

    AND STATUS in &STATUS&
    AND TYPE IN ('D','F')
    AND NVL(CISR_MAC,1) NOT LIKE 'S%'
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_NUM_DO)=0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(out_SELLER,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
UNION
SELECT COUNT(ORDER_NUM),
SUM(CMPINTV),SUM(CMPINTV)/COUNT(ORDER_NUM),SUM(POWER(CMPINTV,2)) C
FROM &DATAPATH&
WHERE STATE = '&ST&'
    AND &RTP&
    AND &RetailExclusions&
    AND STATUS in &STATUS&
    AND NVL(CISR_MAC,1) NOT LIKE 'S%'
    AND (TYPE in 'C' AND SELLER_TYPE = '1' and
(OUT_QTY>0 or OUTWARD_CKL>0 ) and INWARD_QTY=0 and
CHNG_QTY=0 and INWARD_CKL=0 and CHNG_CKL=0)
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_NUM_DO)=0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
    AND NVL(ATC,0) not in ('S','X')

```

```

SELECT
SUM(CMPINTV)
WHERE STATE = '&ST&' and nvl(out_seller,0) not in
('BAND','BNK')
    AND &RTPDisc&

    AND STATUS in &STATUS&
    AND TYPE IN ('D','F')
    AND NVL(CISR_MAC,1) NOT LIKE 'S%'
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_NUM_DO)=0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(out_SELLER,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
UNION
SELECT COUNT(ORDER_NUM),
SUM(CMPINTV),SUM(CMPINTV)/COUNT(ORDER_NUM),SUM(POWER(CMPINTV,2)) C
FROM &DATAPATH&
WHERE STATE = '&ST&'
    AND &RTP&
    AND &RetailExclusions&
    AND STATUS in &STATUS&
    AND NVL(CISR_MAC,1) NOT LIKE 'S%'
    AND (TYPE in 'C' AND SELLER_TYPE = '1' and
(OUT_QTY>0 or OUTWARD_CKL>0 ) and INWARD_QTY=0 and
CHNG_QTY=0 and INWARD_CKL=0 and CHNG_CKL=0)
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_NUM_DO)=0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
    AND NVL(ATC,0) not in ('S','X')

```

RESALE (PROVISIONING)

Report Labels: PR-2-10-2200 Special Services - Provisioning

Parity with VZ Retail

Guidelines: PR-2 - Average Completed Interval

Average Interval Completed – Disconnects – No Dispatch

Result: (Numerator / Denominator)**Denominator:**

Count of no dispatch disconnect orders for product group.

Numerator:

Sum of completion date less application date for product group no dispatch disconnect (D&F) orders.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&' and nvl(out_seller,0) not in
('BAND','BNK')
    AND &RSSSDisc&
    AND &Exclusions
    AND STATUS in &STATUS&
    AND TYPE IN ('D','F')
    AND NVL(CISR_MAC,1) NOT LIKE 'S%'
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(OUT_SELLER,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
UNION
SELECT COUNT(ORDER_NUM),
SUM(CMPINTV),SUM(CMPINTV)/COUNT(ORDER_NUM),SUM(P
OWER(CMPINTV,2)) C
FROM &DATAPATH&
WHERE STATE = '&ST&'
    AND &RSSS&
    AND &Exclusions
    AND STATUS in &STATUS&
    AND NVL(CISR_MAC,1) NOT LIKE 'S%'
    AND (TYPE in 'C' and (OUT_QTY>0 or OUTWARD_CKL>0
) and INWARD_QTY=0 and CHNG_QTY=0 and INWARD_CKL=0
and CHNG_CKL=0)
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
    AND NVL(ATC,0) not in ('S','X')

```

```

SELECT
SUM(CMPINTV)
WHERE STATE = '&ST&' and nvl(out_seller,0) not in
('BAND','BNK')
    AND &RSSSDisc&
    AND &Exclusions
    AND STATUS in &STATUS&
    AND TYPE IN ('D','F')
    AND NVL(CISR_MAC,1) NOT LIKE 'S%'
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(OUT_SELLER,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
UNION
SELECT COUNT(ORDER_NUM),
SUM(CMPINTV),SUM(CMPINTV)/COUNT(ORDER_NUM),SUM(P
OWER(CMPINTV,2)) C
FROM &DATAPATH&
WHERE STATE = '&ST&'
    AND &RSSS&
    AND &Exclusions
    AND STATUS in &STATUS&
    AND NVL(CISR_MAC,1) NOT LIKE 'S%'
    AND (TYPE in 'C' and (OUT_QTY>0 or
OUTWARD_CKL>0 ) and INWARD_QTY=0 and CHNG_QTY=0
and INWARD_CKL=0 and CHNG_CKL=0)
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
    AND NVL(ATC,0) not in ('S','X')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&' and nvl(out_seller,0) not in
('BAND','BNK')
    AND &RTSSDisc&
    AND STATUS in &STATUS&
    AND NVL(CISR_MAC,1) NOT LIKE 'S%'
    AND TYPE IN ('D','F')
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(out_seller,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
UNION
SELECT COUNT(ORDER_NUM),
SUM(CMPINTV),SUM(CMPINTV)/COUNT(ORDER_NUM),SUM(P
OWER(CMPINTV,2)) C
FROM &DATAPATH&
WHERE STATE = '&ST&'
    AND &RTSS&
    AND &RetailExclusions
    AND STATUS in &STATUS&
    AND NVL(CISR_MAC,1) NOT LIKE 'S%'
    AND (TYPE in 'C' AND SELLER_TYPE = '1' and
(OUT_QTY>0 or OUTWARD_CKL>0 ) and INWARD_QTY=0 and
CHNG_QTY=0 and INWARD_CKL=0 and CHNG_CKL=0)
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
    AND NVL(ATC,0) not in ('S','X')

```

```

SELECT
SUM(CMPINTV)
WHERE STATE = '&ST&' and nvl(out_seller,0) not in
('BAND','BNK')
    AND &RTSSDisc&
    AND STATUS in &STATUS&
    AND NVL(CISR_MAC,1) NOT LIKE 'S%'
    AND TYPE IN ('D','F')
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(out_seller,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
UNION
SELECT COUNT(ORDER_NUM),
SUM(CMPINTV),SUM(CMPINTV)/COUNT(ORDER_NUM),SUM(P
OWER(CMPINTV,2)) C
FROM &DATAPATH&
WHERE STATE = '&ST&'
    AND &RTSS&
    AND &RetailExclusions
    AND STATUS in &STATUS&
    AND NVL(CISR_MAC,1) NOT LIKE 'S%'
    AND (TYPE in 'C' AND SELLER_TYPE = '1' and
(OUT_QTY>0 or OUTWARD_CKL>0 ) and INWARD_QTY=0 and
CHNG_QTY=0 and INWARD_CKL=0 and CHNG_CKL=0)
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
    AND NVL(ATC,0) not in ('S','X')

```

UNE (Provisioning)

Report Labels: PR-2-10-3133

POTS & Complex Aggregate

Parity with VZ Retail

Guidelines: PR-2 - Average Completed Interval

Average Interval Completed – Disconnects – No Dispatch

Result: (Numerator / Denominator)**Denominator:**

Count of no dispatch disconnect orders for product group.

Numerator:

Sum of completion date less application date for product group no dispatch disconnect (D&F) orders.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&' and nvl(out_seller,0) not in
('BAND','BNK')
    AND &SOUNPDisc&
    AND &Exclusions
and &PROJECT&
    AND STATUS in &STATUS&
    AND NVL(CISR_MAC,1) NOT LIKE 'S%'
    AND TYPE IN ('D','F')
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(OUT_SELLER,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
UNION
SELECT COUNT(ORDER_NUM),
SUM(CMPINTV),SUM(CMPINTV)/COUNT(ORDER_NUM),SUM(P
OWER(CMPINTV,2)) C
FROM &DATAPATH&
    WHERE STATE = '&ST&'
    AND &SOUNP&
    AND &Exclusions
    AND STATUS in &STATUS&
    AND &PROJECT&
    AND NVL(CISR_MAC,1) NOT LIKE 'S%'
    AND (TYPE in 'C' and (OUT_QTY>0 or OUTWARD_CKL>0
) and INWARD_QTY=0 and CHNG_QTY=0 and INWARD_CKL=0
and CHNG_CKL=0)
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
    AND NVL(ATC,0) not in ('S','X')

```

Numerator

```

SELECT
SUM(CMPINTV)
WHERE STATE = '&ST&' and nvl(out_seller,0) not in
('BAND','BNK')
    AND &SOUNPDisc&
    AND &Exclusions
and &PROJECT&
    AND STATUS in &STATUS&
    AND NVL(CISR_MAC,1) NOT LIKE 'S%'
    AND TYPE IN ('D','F')
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(OUT_SELLER,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
UNION
SELECT COUNT(ORDER_NUM),
SUM(CMPINTV),SUM(CMPINTV)/COUNT(ORDER_NUM),SUM(P
OWER(CMPINTV,2)) C
FROM &DATAPATH&
    WHERE STATE = '&ST&'
    AND &SOUNP&
    AND &Exclusions
    AND STATUS in &STATUS&
    AND &PROJECT&
    AND NVL(CISR_MAC,1) NOT LIKE 'S%'
    AND (TYPE in 'C' and (OUT_QTY>0 or
OUTWARD_CKL>0 ) and INWARD_QTY=0 and CHNG_QTY=0
and INWARD_CKL=0 and CHNG_CKL=0)
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
    AND NVL(ATC,0) not in ('S','X')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&' and nvl(out_seller,0) not in
('BAND','BNK')
    AND &RTPDisc&

    AND STATUS in &STATUS&
    AND TYPE IN ('D','F')
    AND NVL(CISR_MAC,1) NOT LIKE 'S%'
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_NUM_DO)=0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(out_SELLER,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
UNION
SELECT COUNT(ORDER_NUM),
SUM(CMPINTV),SUM(CMPINTV)/COUNT(ORDER_NUM),SUM(POWER(CMPINTV,2)) C
FROM &DATAPATH&
WHERE STATE = '&ST&'
    AND &RTP&
    AND &RetailExclusions&
    AND STATUS in &STATUS&
    AND NVL(CISR_MAC,1) NOT LIKE 'S%'
    AND (TYPE in 'C' AND SELLER_TYPE = '1' and
(OUT_QTY>0 or OUTWARD_CKL>0 ) and INWARD_QTY=0 and
CHNG_QTY=0 and INWARD_CKL=0 and CHNG_CKL=0)
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_NUM_DO)=0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
    AND NVL(ATC,0) not in ('S','X')

```

```

SELECT
SUM(CMPINTV)
WHERE STATE = '&ST&' and nvl(out_seller,0) not in
('BAND','BNK')
    AND &RTPDisc&

    AND STATUS in &STATUS&
    AND TYPE IN ('D','F')
    AND NVL(CISR_MAC,1) NOT LIKE 'S%'
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_NUM_DO)=0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(out_SELLER,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
UNION
SELECT COUNT(ORDER_NUM),
SUM(CMPINTV),SUM(CMPINTV)/COUNT(ORDER_NUM),SUM(POWER(CMPINTV,2)) C
FROM &DATAPATH&
WHERE STATE = '&ST&'
    AND &RTP&
    AND &RetailExclusions&
    AND STATUS in &STATUS&
    AND NVL(CISR_MAC,1) NOT LIKE 'S%'
    AND (TYPE in 'C' AND SELLER_TYPE = '1' and
(OUT_QTY>0 or OUTWARD_CKL>0 ) and INWARD_QTY=0 and
CHNG_QTY=0 and INWARD_CKL=0 and CHNG_CKL=0)
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_NUM_DO)=0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
    AND NVL(ATC,0) not in ('S','X')

```

UNE (Provisioning)

Report Labels: PR-2-10-3200 Special Services Provisioning

Parity with VZ Retail

Guidelines: PR-2 - Average Completed Interval

Average Interval Completed – Disconnects – No Dispatch

Result: (Numerator / Denominator)**Denominator:**

Count of no dispatch disconnect orders for product group.

Numerator:

Sum of completion date less application date for product group no dispatch disconnect (D&F) orders.

Filtered output file: ASR-UNE-SPECIAL

For the details on the above out put filtered file layout refer to File Appendix: 7 File Type: Excel

Denominator

```
SELECT
COUNT(*)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND ACT = D
AND PRODUCT_TYPE IN ('DS1', 'DS3', 'EXP')
AND DISPATCH_YN = N
AND NVL(SUBSTR(WFA_MFC,1,1),'X') NOT IN ('C', 'D')
AND W_CODED_YN = Y
AND ASR_STATUS = C
AND COMPLETED_INTERVAL <= 200
AND OFFERED_INTERVAL <= 2
```

Numerator

```
SELECT
SUM(COMPLETED_INTERVAL)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND ACT = D
AND PRODUCT_TYPE IN ('DS1', 'DS3', 'EXP')
AND DISPATCH_YN = N
AND NVL(SUBSTR(WFA_MFC,1,1),'X') NOT IN ('C', 'D')
AND W_CODED_YN = Y
AND ASR_STATUS = C
AND COMPLETED_INTERVAL <= 200
AND OFFERED_INTERVAL <= 2
```


RESALE (PROVISIONING)

Report Labels: PR-2-11-2103 POTS & Complex Aggregate

Parity with VZ Retail

Guidelines: PR-2 - Average Completed Interval

Average Interval Completed – Disconnects – Dispatch

Result: (Numerator / Denominator)**Denominator:**

Count of dispatch disconnect orders for product group.

Numerator:

Sum of completion date less application date for product group dispatch disconnect (D&F) orders.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&' and nvl(out_seller,0) not in
('BAND','BNK')
    AND &RTPDisc&
    AND STATUS in &STATUS&
    AND TYPE IN ('D','F')
    AND NVL(CISR_MAC,1) NOT LIKE 'S%'
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(out_SELLER,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
UNION
SELECT COUNT(ORDER_NUM),
SUM(CMPINTV),SUM(CMPINTV)/COUNT(ORDER_NUM),SUM(P
OWER(CMPINTV,2)) C
FROM &DATAPATH&
WHERE STATE = '&ST&'
    AND &RTP&
    AND &RetailExclusions
    AND STATUS in &STATUS&
    AND NVL(CISR_MAC,1) NOT LIKE 'S%'
    AND (TYPE in 'C' AND SELLER_TYPE = '1' and
(OUT_QTY>0 or OUTWARD_CKL>0 ) and INWARD_QTY=0 and
CHNG_QTY=0 and INWARD_CKL=0 and CHNG_CKL=0)
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
    AND NVL(ATC,0) not in ('S','X')

```

```

SELECT
sum("211RTP DF ORDERS")
WHERE STATE = '&ST&' and nvl(out_seller,0) not in
('BAND','BNK')
    AND &RTPDisc&
    AND STATUS in &STATUS&
    AND TYPE IN ('D','F')
    AND NVL(CISR_MAC,1) NOT LIKE 'S%'
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(out_SELLER,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
UNION
SELECT COUNT(ORDER_NUM),
SUM(CMPINTV),SUM(CMPINTV)/COUNT(ORDER_NUM),SUM(P
OWER(CMPINTV,2)) C
FROM &DATAPATH&
WHERE STATE = '&ST&'
    AND &RTP&
    AND &RetailExclusions
    AND STATUS in &STATUS&
    AND NVL(CISR_MAC,1) NOT LIKE 'S%'
    AND (TYPE in 'C' AND SELLER_TYPE = '1' and
(OUT_QTY>0 or OUTWARD_CKL>0 ) and INWARD_QTY=0 and
CHNG_QTY=0 and INWARD_CKL=0 and CHNG_CKL=0)
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
    AND NVL(ATC,0) not in ('S','X')

```

RESALE (PROVISIONING)

Report Labels: PR-2-11-2200

Special Services - Provisioning

Parity with VZ Retail

Guidelines: PR-2 - Average Completed Interval

Average Interval Completed – Disconnects – Dispatch

Result: (Numerator / Denominator)**Denominator:**

Count of dispatch disconnect orders for product group.

Numerator:

Sum of completion date less application date for product group dispatch disconnect (D&F) orders.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&' and nvl(out_seller,0) not in
('BAND','BNK')
    AND &RTSSDisc&
    AND STATUS in &STATUS&
    AND NVL(CISR_MAC,1) NOT LIKE 'S%'
    AND TYPE IN ('D','F')
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(out_seller,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
UNION
SELECT COUNT(ORDER_NUM),
SUM(CMPINTV),SUM(CMPINTV)/COUNT(ORDER_NUM),SUM(P
OWER(CMPINTV,2)) C
FROM &DATAPATH&
WHERE STATE = '&ST&'
    AND &RTSS&
    AND &RetailExclusions
    AND STATUS in &STATUS&
    AND NVL(CISR_MAC,1) NOT LIKE 'S%'
    AND (TYPE in 'C' AND SELLER_TYPE = '1' and
(OUT_QTY>0 or OUTWARD_CKL>0 ) and INWARD_QTY=0 and
CHNG_QTY=0 and INWARD_CKL=0 and CHNG_CKL=0)
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
    AND NVL(ATC,0) not in ('S','X')

```

```

SELECT
sum("211RTSS DF ORDERS")
WHERE STATE = '&ST&' and nvl(out_seller,0) not in
('BAND','BNK')
    AND &RTSSDisc&
    AND STATUS in &STATUS&
    AND NVL(CISR_MAC,1) NOT LIKE 'S%'
    AND TYPE IN ('D','F')
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(out_seller,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
UNION
SELECT COUNT(ORDER_NUM),
SUM(CMPINTV),SUM(CMPINTV)/COUNT(ORDER_NUM),SUM(P
OWER(CMPINTV,2)) C
FROM &DATAPATH&
WHERE STATE = '&ST&'
    AND &RTSS&
    AND &RetailExclusions
    AND STATUS in &STATUS&
    AND NVL(CISR_MAC,1) NOT LIKE 'S%'
    AND (TYPE in 'C' AND SELLER_TYPE = '1' and
(OUT_QTY>0 or OUTWARD_CKL>0 ) and INWARD_QTY=0 and
CHNG_QTY=0 and INWARD_CKL=0 and CHNG_CKL=0)
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
    AND NVL(ATC,0) not in ('S','X')

```

UNE (Provisioning)

Report Labels: PR-2-11-3133 POTS & Complex Aggregate

Parity with VZ Retail

Guidelines: PR-2 - Average Completed Interval

Average Interval Completed – Disconnects – Dispatch

Result: (Numerator / Denominator)**Denominator:**

Count of dispatch disconnect orders for product group.

Numerator:

Sum of completion date less application date for product group dispatch disconnect (D&F) orders.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator****SELECT**

```

WHERE STATE = '&ST&' and nvl(out_seller,0) not in
('BAND','BNK')
    AND &RTPDisc&
    AND STATUS in &STATUS&
    AND TYPE IN ('D','F')
    AND NVL(CISR_MAC,1) NOT LIKE 'S%'
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_NUM_DO)>0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(out_SELLER,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
UNION
SELECT COUNT(ORDER_NUM),
SUM(CMPINTV),SUM(CMPINTV)/COUNT(ORDER_NUM),SUM(POWER(CMPINTV,2)) C
FROM &DATAPATH&
WHERE STATE = '&ST&'
    AND &RTP&
    AND &RetailExclusions&
    AND STATUS in &STATUS&
    AND NVL(CISR_MAC,1) NOT LIKE 'S%'
    AND (TYPE in 'C' AND SELLER_TYPE = '1' and
(OUT_QTY>0 or OUTWARD_CKL>0 ) and INWARD_QTY=0 and
CHNG_QTY=0 and INWARD_CKL=0 and CHNG_CKL=0)
    AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_NUM_DO)>0
    AND APPINTV between 0 and 1
    AND CMPINTV between 0 and 200
    AND nvl(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
    AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
    AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
    AND NVL(ATC,0) not in ('S','X')

```

UNE (Provisioning)

Report Labels: PR-2-11-3200

Special Services Provisioning

Parity with VZ Retail

Guidelines: PR-2 - Average Completed Interval

Average Interval Completed – Disconnects – Dispatch

Result: (Numerator / Denominator)**Denominator:**

Count of dispatch disconnect orders for product group.

Numerator:

Sum of completion date less application date for product group dispatch disconnect (D&F) orders.

Filtered output file: ASR-UNE-SPECIAL

For the details on the above out put filtered file layout refer to File Appendix: 7 File Type: Excel

Denominator

```
SELECT
COUNT(*)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND ACT = D
AND PRODUCT_TYPE IN ('DS1', 'DS3', 'EXP')
AND DISPATCH_YN = Y
AND NVL(SUBSTR(WFA_MFC,1,1),'X') NOT IN ('C', 'D')
AND W_CODED_YN = Y
AND ASR_STATUS = C
AND COMPLETED_INTERVAL <= 200
AND OFFERED_INTERVAL <= 2
```

Numerator

```
SELECT
SUM(COMPLETED_INTERVAL)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND ACT = D
AND PRODUCT_TYPE IN ('DS1', 'DS3', 'EXP')
AND DISPATCH_YN = Y
AND NVL(SUBSTR(WFA_MFC,1,1),'X') NOT IN ('C', 'D')
AND W_CODED_YN = Y
AND ASR_STATUS = C
AND COMPLETED_INTERVAL <= 200
AND OFFERED_INTERVAL <= 2
```

UNE (Provisioning)

Report Labels: PR-2-13-3342

Complex Services - 2 Wire xDSL

No Standard

Guidelines: PR-2 - Average Completed Interval

Avg. Interval Completed - With DD-2 Test Rslts, with 800 #& Serial#

Result: (Numerator / Denominator)**Denominator:**

UNE: Count of completed orders with DD-2 test results, with 800 number, and with CLEC serial number. Retail: Count of completed orders for specified product.

Numerator:

UNE: Sum of completion date less application date for orders completed with DD-2 Test results, with 800 Number, and with CLEC serial number. Retail: Sum of completion date less application date for specified product.

Filtered output file: PR-2-15 State Agg

For the details on the above out put filtered file layout refer to File Appendix: 52 File Type: Access DB (P

Formula For: CLEC**Denominator****Numerator**

```
SELECT
COUNT(*)
WHERE ORDSTATUS = "CLOSED OUT"
AND ORDDELETE = "FALSE"
AND ORDAPPPDATE LIKE "**ARDU"
AND CLCTESTING = "TRUE"
AND ORDCOOPTESTRESULT > 0
AND ORDCMPDATE < 5
AND ORDLATECUST = FALSE
```

```
SELECT
Sum([ordCmpDate]-[ordAppDate])
WHERE ORDSTATUS = "CLOSED OUT"
AND ORDDELETE = "FALSE"
AND ORDAPPPDATE LIKE "**ARDU"
AND CLCTESTING = "TRUE"
AND ORDCOOPTESTRESULT > 0
AND ORDCMPDATE < 5
AND ORDLATECUST = FALSE
```

UNE (Provisioning)

Report Labels: PR-2-14-3342 Complex Services - 2 Wire xDSL No Standard

Guidelines: PR-2 - Average Completed Interval

Avg. Interval Completed - With DD-2 Test Rslts, with 800 # & with/without Serial #

Result: (Numerator / Denominator)	
Denominator:	Numerator:
Count of completed orders with DD-2 test results, with 800 number, and with or without CLEC serial number.	Sum of completion date less application date for orders completed with DD-2 test results, with 800 number, and with or without CLEC serial number.

Filtered output file: PR-2-15 State Agg
For the details on the above out put filtered file layout refer to File Appendix: 52 File Type: Access DB (P)
Formula For: CLEC

Denominator	Numerator
SELECT COUNT(*) WHERE ORDSTATUS = "CLOSED OUT" AND ORDDELETE = "FALSE" AND ORDAPPPDATE LIKE "**ARDU" AND CLCTESTING = "TRUE" AND ORDCOOPTESTRESULT > 0 AND ORDCMPDATE < 5 AND ORDLATECUST = FALSE	SELECT Sum([ordCmpDate]-[ordAppDate]) WHERE ORDSTATUS = "CLOSED OUT" AND ORDDELETE = "FALSE" AND ORDAPPPDATE LIKE "**ARDU" AND CLCTESTING = "TRUE" AND ORDCOOPTESTRESULT > 0 AND ORDCMPDATE < 5 AND ORDLATECUST = FALSE

UNE (Provisioning)

Report Labels: PR-2-15-3342 Complex Services - 2 Wire xDSL No Standard

Guidelines: PR-2 - Average Completed Interval

Avg. Interval Completed - Without DD-2 Test,with 800 # & Serial #

Result: (Numerator / Denominator)	
Denominator:	Numerator:
Count of completed orders without DD-2 test results, with 800 number, and with CLEC serial number.	Sum of completion date less application date for orders completed without DD-2 test results, with 800 number, and with CLEC serial number.

Filtered output file: PR-2-15 State Agg
For the details on the above out put filtered file layout refer to File Appendix: 52 File Type: Access DB (P)
Formula For: CLEC

Denominator	Numerator
SELECT COUNT(*) WHERE ORDSTATUS = "CLOSED OUT" AND ORDDELETE = "FALSE" AND ORDAPPPDATE LIKE "**ARDU" AND CLCTESTING = "TRUE" AND ORDCOOPTESTRESULT > 0 AND ORDCMPDATE < 5 AND ORDLATECUST = FALSE	SELECT Sum([ordCmpDate]-[ordAppDate]) WHERE ORDSTATUS = "CLOSED OUT" AND ORDDELETE = "FALSE" AND ORDAPPPDATE LIKE "**ARDU" AND CLCTESTING = "TRUE" AND ORDCOOPTESTRESULT > 0 AND ORDCMPDATE < 5 AND ORDLATECUST = FALSE

UNE (Provisioning)

Report Labels: PR-2-16-3342

Complex Services - 2 Wire xDSL

No Standard

Guidelines: PR-2 - Average Completed Interval

Avg. Interval Completed - Without DD-2 Test Rslts, with 800 # & with/without Serial #

Result: (Numerator / Denominator)**Denominator:**

Count of completed orders without DD-2 test results, with 800 number, and with or without CLEC serial number.

Numerator:

Sum of completion date less application date for orders completed without DD-2 test results, with 800 number, and with or without CLEC serial number.

Filtered output file: PR-2-15 State Agg

For the details on the above out put filtered file layout refer to File Appendix: 52 File Type: Access DB (P

Formula For: CLEC**Denominator****Numerator**

```
SELECT
COUNT(*)
WHERE ORDSTATUS = "CLOSED OUT"
AND ORDDELETE = "FALSE"
AND ORDAPPPDATE LIKE "**ARDU"
AND CLCTESTING = "TRUE"
AND ORDCOOPTESTRESULT > 0
AND ORDCMPDATE < 5
AND ORDLATECUST = FALSE
```

```
SELECT
Sum([ordCmpDate]-[ordAppDate])
WHERE ORDSTATUS = "CLOSED OUT"
AND ORDDELETE = "FALSE"
AND ORDAPPPDATE LIKE "**ARDU"
AND CLCTESTING = "TRUE"
AND ORDCOOPTESTRESULT > 0
AND ORDCMPDATE < 5
AND ORDLATECUST = FALSE
```


UNE (Provisioning)

Report Labels: PR-2-17-3342 Complex Services - 2 Wire xDSL

No Standard

Guidelines: PR-2 - Average Completed Interval

Avg. Interval Completed - Without DD-2 Test Rslts, without 800 # & without Serial #

Result: (Numerator / Denominator)**Denominator:**

Count of completed orders without DD-2 test results, without 800 number, and without CLEC serial number.

Numerator:

Sum of completion date less application date for orders completed without DD-2 test results, without 800 number, and without CLEC serial number.

Filtered output file: PR-2-15 State Agg

For the details on the above out put filtered file layout refer to File Appendix: 52 File Type: Access DB (P

Formula For: CLEC**Denominator****Numerator**

```
SELECT
COUNT(*)
WHERE ORDSTATUS = "CLOSED OUT"
AND ORDDELETE = "FALSE"
AND ORDAPPPDATE LIKE "**ARDU"
AND CLCTESTING = "TRUE"
AND ORDCOOPTESTRESULT > 0
AND ORDCMPDATE < 5
AND ORDLATECUST = FALSE
```

```
SELECT
Sum([ordCmpDate]-[ordAppDate])
WHERE ORDSTATUS = "CLOSED OUT"
AND ORDDELETE = "FALSE"
AND ORDAPPPDATE LIKE "**ARDU"
AND CLCTESTING = "TRUE"
AND ORDCOOPTESTRESULT > 0
AND ORDCMPDATE < 5
AND ORDLATECUST = FALSE
```

Guidelines For: PR-3 Completed within Specified Number of Days (1-5 Lines)

C2C Guideline:	
Definition:	Completed within Specified Number of Days (1-5 Lines)
Performance Standard:	Resale: Parity with BA Retail, UNE: Parity with BA Retail.
Exclusions:	BA Test Orders, Disconnect Orders, Orders where customers request a due date that is greater than or less than the standard available appointment interval (X or S Appointment Code). Bell Atlantic Administrative orders. Orders with invalid intervals (Negative Intervals or intervals over 200 business days - indicative of typographical error). Additional Segments on orders (parts of a whole order are included in the whole). Orders that are not complete. (Orders are included in the month that they are complete). Suspend for non-payment and associated restore orders. Orders completed late due to any end user or CLEC caused delay. Coordinated cut-over Unbundled Network Elements such as loops or number portability orders.
Report Dimensions:	BA Retail, CLEC Aggregate, CLEC Specific, BA Affiliate Aggregate, BA Affiliate Specific
Geography:	POTS, 2 Wire Digital Services, and 2 Wire, xDSL Services: Southern, Eastern Shore, Raritan, Suburban, Hudson-Bergen

RESALE (PROVISIONING)

Report Labels: PR-3-01-2100 POTS - Provisioning - Total

Parity with VZ Retail

Guidelines: PR-3 - Completed within Specified Days

% Completed in 1 Day (1-5 Lines - No Dispatch)

Result: (Numerator / Denominator) * 100**Denominator:**

Count of No Dispatch POTS orders with 1 to 5 lines.

Numerator:

Count of No Dispatch POTS orders with 1 to 5 lines where completion date less application date is 1 or fewer days.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T','C')or(TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND &RSPS&
      AND &Exclusions
AND &PROJECT&
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5

```

Numerator

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T','C')or(TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND &RSPS&
      AND &Exclusions
AND &PROJECT&
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 1
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND TYPE IN ('N','T','C')
      AND &RTPS&
AND &PROJECT&
      AND &RetailExclusions
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5

```

Numerator

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND TYPE IN ('N','T','C')
      AND &RTPS&
      AND &RetailExclusions
AND &PROJECT&
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 1
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5

```


UNE (Provisioning)

Report Labels: PR-3-01-3142 POTS - Provisioning

Parity with VZ Retail

Guidelines: PR-3 - Completed within X Days - Platform & Other (Switch & INP)

% Completed in 1 Day (1-5 Lines - No Dispatch)

Result: (Numerator / Denominator) * 100**Denominator:**

Count of No Dispatch POTS orders with 1 to 5 lines.

Numerator:

Count of No Dispatch POTS orders with 1 to 5 lines where completion date less application date is 1 or fewer days.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &SOUNPSPO&
      AND &PROJECT&
      AND &Exclusions&
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND INWARD_QTY+CHNG_QTY BETWEEN 1 AND 5
      AND CMPINTV between 0 and 200
      AND (
(ATC IN ('W') AND APPINTV between 0 and 200 AND TYPE IN
('N','T','C'))
or (type in ('R') and CLS IN ('RRM','RBM') and PON is not null and
APPINTV between 0 and 2) )

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND TYPE IN ('N','T','C')
      AND &RTPS&
      AND &PROJECT&
      AND &RetailExclusions
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5

```

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND TYPE IN ('N','T','C')
      AND &RTPS&
      AND &RetailExclusions
      AND &PROJECT&
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 1
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5

```


RESALE (PROVISIONING)

Report Labels: PR-3-02-2100 POTS - Provisioning - Total

Parity with VZ Retail

Guidelines: PR-3 - Completed within Specified Days

% Completed in 2 Days (1-5 Lines - No Dispatch)

Result: (Numerator / Denominator) * 100**Denominator:**

Count of No Dispatch POTS orders with 1 to 5 lines.

Numerator:

Count of No Dispatch POTS orders with 1 to 5 lines where completion date less application date is 2 or fewer days.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T','C')or(TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND &RSPS&
      AND &Exclusions
AND &PROJECT&
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5

```

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T','C')or(TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND &RSPS&
      AND &Exclusions
AND &PROJECT&
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 2
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND TYPE IN ('N','T','C')
      AND &RTPS&
AND &PROJECT&
      AND &RetailExclusions
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5

```

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND TYPE IN ('N','T','C')
      AND &RTPS&
      AND &RetailExclusions&
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 2
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5

```


UNE (Provisioning)

Report Labels: PR-3-02-3142 POTS - Provisioning

Parity with VZ Retail

Guidelines: PR-3 - Completed within X Days - Platform & Other (Switch & INP)

% Completed in 2 Days (1-5 Lines - No Dispatch)

Result: (Numerator / Denominator) * 100**Denominator:**

Count of No Dispatch POTS orders with 1 to 5 lines.

Numerator:

Count of No Dispatch POTS orders with 1 to 5 lines where completion date less application date is 2 or fewer days.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator****Filtered output file:** Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```
SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND TYPE IN ('N','T','C')
      AND &RTPS&
AND &PROJECT&
      AND &RetailExclusions
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5
```

```
SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND TYPE IN ('N','T','C')
      AND &RTPS&
      AND &RetailExclusions&
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 2
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5
```

RESALE (PROVISIONING)

Report Labels: PR-3-03-2100 POTS - Provisioning - Total

Parity with VZ Retail

Guidelines: PR-3 - Completed within Specified Days

% Completed in 3 Days (1-5 Lines - No Dispatch)

Result: (Numerator / Denominator) * 100**Denominator:**

Count of No Dispatch POTS orders with 1 to 5 lines.

Numerator:

Count of No Dispatch POTS orders with 1 to 5 lines where completion date less application date is 3 or fewer days.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T','C')or(TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND &RSPS&
      AND &Exclusions
AND &PROJECT&
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5

```

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T','C')or(TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND &RSPS&
      AND &Exclusions
AND &PROJECT&
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 3
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND TYPE IN ('N','T','C')
      AND &RTPS&
AND &PROJECT&
      AND &RetailExclusions
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5

```

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND TYPE IN ('N','T','C')
      AND &RTPS&
      AND &RetailExclusions
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 3
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5

```


UNE (Provisioning)

Report Labels: PR-3-03-3142 POTS - Provisioning

Parity with VZ Retail

Guidelines: PR-3 - Completed within X Days - Platform & Other (Switch & INP)

% Completed in 3 Days (1-5 Lines - No Dispatch)

Result: (Numerator / Denominator) * 100**Denominator:**

Count of No Dispatch POTS orders with 1 to 5 lines.

Numerator:

Count of No Dispatch POTS orders with 1 to 5 lines where completion date less application date is 3 or fewer days.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator****Filtered output file:** Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```
SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND TYPE IN ('N','T','C')
      AND &RTPS&
AND &PROJECT&
      AND &RetailExclusions
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5
```

```
SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND TYPE IN ('N','T','C')
      AND &RTPS&
      AND &RetailExclusions
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 3
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5
```

RESALE (PROVISIONING)

Report Labels: PR-3-04-2100 POTS - Provisioning - Total

Parity with VZ Retail

Guidelines: PR-3 - Completed within Specified Days

% Completed in 1 Day (1-5 Lines - Dispatch)

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Dispatch POTS orders with 1 to 5 lines.

Numerator:

Count of Dispatch POTS orders with 1 to 5 lines where completion date less application date is 1 or fewer days.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T','C')or(TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND &RSPS&
      AND &Exclusions
AND &PROJECT&
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5

```

Numerator

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T','C')or(TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND &RSPS&
      AND &Exclusions
AND &PROJECT&
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 1
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND TYPE IN ('N','T','C')
      AND &RTPS&
      AND &RetailExclusions
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5

```

Numerator

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND TYPE IN ('N','T','C')
      AND &RTPS&
      AND &RetailExclusions
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 1
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5

```


UNE (Provisioning)

Report Labels: PR-3-04-3142

POTS - Provisioning

Parity with VZ Retail

Guidelines: PR-3 - Completed within X Days - Platform & Other (Switch & INP)

% Completed in 1 Day (1-5 Lines - Dispatch)

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Dispatch POTS orders with 1 to 5 lines.

Numerator:

Count of Dispatch POTS orders with 1 to 5 lines where completion date less application date is 1 or fewer days.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator****Filtered output file:** Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND TYPE IN ('N','T','C')
      AND &RTPS&
      AND &RetailExclusions
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
      decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5

```

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND TYPE IN ('N','T','C')
      AND &RTPS&
      AND &RetailExclusions
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 1
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
      decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5

```

RESALE (PROVISIONING)

Report Labels: PR-3-05-2100

POTS - Provisioning - Total

Parity with VZ Retail

Guidelines: PR-3 - Completed within Specified Days

% Completed in 2 Days (1-5 Lines - Dispatch)

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Dispatch POTS orders with 1 to 5 lines.

Numerator:

Count of Dispatch POTS orders with 1 to 5 lines where completion date less application date is 2 or fewer days.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T','C')or(TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND &RSPS&
      AND &Exclusions
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 2
AND &PROJECT&
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND TYPE IN ('N','T','C')
      AND &RTPS&
      AND &RetailExclusions
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5

```

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND TYPE IN ('N','T','C')
      AND &RTPS&
      AND &RetailExclusions
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 2
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5

```


UNE (Provisioning)

Report Labels: PR-3-05-3142

POTS - Provisioning

Parity with VZ Retail

Guidelines: PR-3 - Completed within X Days - Platform & Other (Switch & INP)

% Completed in 2 Days (1-5 Lines - Dispatch)

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Dispatch POTS orders with 1 to 5 lines.

Numerator:

Count of Dispatch POTS orders with 1 to 5 lines where completion date less application date is 2 or fewer days.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator****Filtered output file:** Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND TYPE IN ('N','T','C')
      AND &RTPS&
      AND &RetailExclusions
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5

```

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND TYPE IN ('N','T','C')
      AND &RTPS&
      AND &RetailExclusions
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 2
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5

```

RESALE (PROVISIONING)

Report Labels: PR-3-06-2100 POTS - Provisioning - Total

Parity with VZ Retail

Guidelines: PR-3 - Completed within Specified Days

% Completed in 3 Days (1-5 Lines - Dispatch)

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Dispatch POTS orders with 1 to 5 lines.

Numerator:

Count of Dispatch POTS orders with 1 to 5 lines where completion date less application date is 3 or fewer days.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T','C')or(TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND &RSPS&
      AND &Exclusions
AND &PROJECT&
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 3
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND TYPE IN ('N','T','C')
      AND &RTPS&
      AND &RetailExclusions
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5

```

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND TYPE IN ('N','T','C')
      AND &RTPS&
      AND &RetailExclusions
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 3
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5

```


UNE (Provisioning)

Report Labels: PR-3-06-3142

POTS - Provisioning

Parity with VZ Retail

Guidelines: PR-3 - Completed within X Days - Platform & Other (Switch & INP)

% Completed in 3 Days (1-5 Lines - Dispatch)

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Dispatch POTS orders with 1 to 5 lines.

Numerator:

Count of Dispatch POTS orders with 1 to 5 lines where completion date less application date is 3 or fewer days.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator****Filtered output file:** Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```
SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND TYPE IN ('N','T','C')
      AND &RTPS&
      AND &RetailExclusions
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5
```

```
SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND TYPE IN ('N','T','C')
      AND &RTPS&
      AND &RetailExclusions
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 3
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5
```

RESALE (PROVISIONING)

Report Labels: PR-3-07-2100 POTS - Provisioning - Total

Parity with VZ Retail

Guidelines: PR-3 - Completed within Specified Days

% Completed in 4 Days (1-5 Lines - Total)

Result: (Numerator / Denominator) * 100**Denominator:**

Count of POTS orders with 1 to 5 lines.

Numerator:

Count of POTS orders with 1 to 5 lines where completion date less application date is 4 or fewer days.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```
SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T','C')or(TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND &RSPS&
      AND &Exclusions
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5
```

Numerator

```
SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T','C')or(TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND &RSPS&
      AND &Exclusions
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 4
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5
```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator**

```
SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND TYPE IN ('N','T','C')
      AND &RTPS&
      AND &RetailExclusions
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5
```

Numerator

```
SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND TYPE IN ('N','T','C')
      AND &RTPS&
      AND &RetailExclusions
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 4
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5
```

UNE (Provisioning)

Report Labels: PR-3-07-3142 POTS - Provisioning

Parity with VZ Retail

Guidelines: PR-3 - Completed within X Days - Platform & Other (Switch & INP)

% Completed in 4 Days (1-5 Lines - Total)

Result: (Numerator / Denominator) * 100**Denominator:**

Count of POTS orders with 1 to 5 lines.

Numerator:

Count of POTS orders with 1 to 5 lines where completion date less application date is 4 or fewer days.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator****Filtered output file:** Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```
SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND TYPE IN ('N','T','C')
      AND &RTPS&
      AND &RetailExclusions
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5
```

```
SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND TYPE IN ('N','T','C')
      AND &RTPS&
      AND &RetailExclusions
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 4
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5
```

RESALE (PROVISIONING)

Report Labels: PR-3-08-2100 POTS - Provisioning - Total

Parity with VZ Retail

Guidelines: PR-3 - Completed within Specified Days

% Completed in 5 Days (1-5 Lines – No Dispatch)

Result: (Numerator / Denominator) * 100**Denominator:**

Count of No Dispatch POTS orders with 1 to 5 lines.

Numerator:

Count of No Dispatch POTS orders with 1 to 5 lines where completion date less application date is 5 or fewer days.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T','C')or(TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND &RSPS&
      AND &Exclusions
AND &PROJECT&
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5

```

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T','C')or(TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND &RSPS&
      AND &Exclusions
AND &PROJECT&
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 5
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND TYPE IN ('N','T','C')
      AND &RTPS&
AND &PROJECT&
      AND &RetailExclusions
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5

```

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND TYPE IN ('N','T','C')
      AND &RTPS&
      AND &RetailExclusions
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 5
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5

```


UNE (Provisioning)

Report Labels: PR-3-08-3142 POTS - Provisioning

Parity with VZ Retail

Guidelines: PR-3 - Completed within X Days - Platform & Other (Switch & INP)

% Completed in 5 Days (1-5 Lines – No Dispatch)

Result: (Numerator / Denominator) * 100**Denominator:**

Count of No Dispatch POTS orders with 1 to 5 lines.

Numerator:

Count of No Dispatch POTS orders with 1 to 5 lines where completion date less application date is 5 or fewer days.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &SOUNPSPO&
      AND &PROJECT&
      AND &Exclusions&
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND INWARD_QTY+CHNG_QTY BETWEEN 1 AND 5
      AND CMPINTV between 0 and 200
      AND (
(ATC IN ('W') AND APPINTV between 0 and 200 AND TYPE IN
('N','T','C'))
or (type in ('R') and CLS IN ('RRM','RBM') and PON is not null and
APPINTV between 0 and 2) )

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND TYPE IN ('N','T','C')
      AND &RTPS&
      AND &PROJECT&
      AND &RetailExclusions
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5

```

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND TYPE IN ('N','T','C')
      AND &RTPS&
      AND &RetailExclusions
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 5
      AND ATC IN ('W')
      AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5

```


RESALE (PROVISIONING)

Report Labels: PR-3-09-2100 POTS - Provisioning - Total

Parity with VZ Retail

Guidelines: PR-3 - Completed within Specified Days

% Completed in 5 Days (1-5 Lines – Dispatch)

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Dispatch POTS orders with 1 to 5 lines.

Numerator:

Count of Dispatch POTS orders with 1 to 5 lines where completion date less application date is 5 or fewer days.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T','C')or(TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND &RSPS&
      AND &Exclusions
AND &PROJECT&
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5

```

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T','C')or(TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND &RSPS&
      AND &Exclusions
AND &PROJECT&
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 5
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND TYPE IN ('N','T','C')
      AND &RTPS&
      AND &RetailExclusions
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5

```

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND TYPE IN ('N','T','C')
      AND &RTPS&
      AND &RetailExclusions
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 5
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5

```


UNE (Provisioning)

Report Labels: PR-3-09-3142 POTS - Provisioning

Parity with VZ Retail

Guidelines: PR-3 - Completed within X Days - Platform & Other (Switch & INP)

% Completed in 5 Days (1-5 Lines – Dispatch)

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Dispatch POTS orders with 1 to 5 lines.

Numerator:

Count of Dispatch POTS orders with 1 to 5 lines where completion date less application date is 5 or fewer days.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &SOUNPSPO&
      AND &PROJECT&
      AND &Exclusions&
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5
      AND CMPINTV between 0 and 200
      AND (
(ATC IN ('W') AND APPINTV between 0 and 200 AND TYPE IN
('N','T','C'))
or (type in ('R') and CLS IN ('RRM','RBM') and PON is not null and
APPINTV between 0 and 2) )

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND TYPE IN ('N','T','C')
      AND &RTPS&
      AND &RetailExclusions
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5

```

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND TYPE IN ('N','T','C')
      AND &RTPS&
      AND &RetailExclusions
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 5
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5

```


RESALE (PROVISIONING)

Report Labels: PR-3-10-2100 POTS - Provisioning - Total

Parity with VZ Retail

Guidelines: PR-3 - Completed within Specified Days

% Completed in 6 Days (1-5 Lines - Total)

Result: (Numerator / Denominator) * 100**Denominator:**

Count of orders (by specified product) with 1 to 5 lines.

Numerator:

Count of orders (by specified product) with 1 to 5 lines where completion date less application date is 6 or fewer days.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T','C')or(TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND &RSPS&
      AND &Exclusions
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5

```

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T','C')or(TYPE ='R' and
RESELLER_ACT='I' and APPINTV <= 2))
      AND &RSPS&
      AND &Exclusions
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 4
      AND (ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I'
and APPINTV <= 2))
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND TYPE IN ('N','T','C')
      AND &RTPS&
      AND &RetailExclusions
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5

```

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RTPS&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND TYPE IN ('N','T','C')
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 6
      AND ATC IN ('W')
      AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5

```


UNE (Provisioning)

Report Labels: PR-3-10-3142 POTS - Provisioning

Parity with VZ Retail

Guidelines: PR-3 - Completed within X Days - Platform & Other (Switch & INP)

% Completed in 6 Days (1-5 Lines - Total)

Result: (Numerator / Denominator) * 100**Denominator:**

Count of orders (by specified product) with 1 to 5 lines.

Numerator:

Count of orders (by specified product) with 1 to 5 lines where completion date less application date is 6 or fewer days.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &SOUNPSPO&
      AND &Exclusions
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND
decode(new_CMPINTV,null,cmpintv,new_cmpintv) between 0 and
200
      AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5
      AND nvl(CF_MAC_IND,0) <> 'Y' and nvl(cisr_mac,'') not in
('CA','CF')
AND (
(ATC IN ('W') AND
decode(new_APPINTV,null,appintv,new_appintv) between 0 and
200 AND TYPE IN ('N','T','C'))
or (type in ('R') and CLS IN ('RRM','RBM') and PON is not null and
decode(new_APPINTV,null,appintv,new_appintv) between 0 and
2) )

```

Numerator

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &SOUNPSPO&
      AND &PROJECT&
      AND &Exclusions&
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5
      AND CMPINTV between 0 and 6
      AND (
(ATC IN ('W') AND APPINTV between 0 and 200 AND TYPE IN
('N','T','C'))
or (type in ('R') and CLS IN ('RRM','RBM') and PON is not null and
APPINTV between 0 and 2) )

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND TYPE IN ('N','T','C')
      AND &RTPS&
      AND &RetailExclusions
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5

```

Numerator

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RTPS&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND TYPE IN ('N','T','C')
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 6
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5

```


UNE (Provisioning)

Report Labels: PR-3-10-3341

Complex Services - 2 Wire Digital

Parity with VZ Retail

Guidelines: PR-3 - Completed within X Days

% Completed w/in 6 Days (1-5 lines) Total

Result: (Numerator / Denominator) * 100**Denominator:**

Count of orders (by specified product) with 1 to 5 lines.

Numerator:

Count of orders (by specified product) with 1 to 5 lines where completion date less application date is 6 or fewer days.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
sum(count(distinct order_num))
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTPR&
      AND &RetailExclusions
      AND TYPE IN ('N','T','C')
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND ADL='Y'
      AND IN_FACIL >
having sum(inward_qty+chng_qty) BETWEEN 1 AND 5
group by order_num,dsp_ind,entity,cris,seller_type,seller_name

```

```

SELECT
sum(count(distinct order_num))
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTPR&
      AND &RetailExclusions
      AND TYPE IN ('N','T','C')
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 6
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND ADL='Y'
      AND IN_FACIL >
having sum(inward_qty+chng_qty) BETWEEN 1 AND 5
group by order_num,dsp_ind,entity,cris,seller_type,seller_name

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
sum(count(distinct order_num))
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTPR&
      AND &RetailExclusions
      AND TYPE IN ('N','T','C')
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND ADL='Y'
      AND IN_FACIL >
having sum(inward_qty+chng_qty) BETWEEN 1 AND 5
group by order_num,dsp_ind,entity,cris,seller_type,seller_name

```

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RTPI&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND TYPE IN ('N','T','C')
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 6
      AND ATC IN ('W')
AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5

```

UNE (Provisioning)

Report Labels: PR-3-10-3342 Complex Services - 2 Wire xDSL

Parity with VZ Retail

Guidelines: PR-3 - Completed within X Days

% Completed w/in 6 Days (1-5 lines) Total

Result: (Numerator / Denominator) * 100**Denominator:**

Count of orders (by specified product) with 1 to 5 lines.

Numerator:

Count of orders (by specified product) with 1 to 5 lines where completion date less application date is 6 or fewer days.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND TYPE IN ('N','T','C')
      AND &SOUNPD&
      AND &Exclusions
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5

```

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND TYPE IN ('N','T','C')
      AND &SOUNPD&
      AND &Exclusions
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 6
      AND ATC IN ('W')
      AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (inward_qty+chng_qty) BETWEEN 1 AND 5

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
sum(count(distinct order_num))
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTPR&
      AND &RetailExclusions
      AND TYPE IN ('N','T','C')
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 200
      AND ATC IN ('W')
      AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND ADL='Y'
      AND IN_FACIL >
having sum(inward_qty+chng_qty) BETWEEN 1 AND 5
group by order_num,dsp_ind,entity,cris,seller_type,seller_name

```

```

SELECT
sum(count(distinct order_num))
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTPR&
      AND &RetailExclusions
      AND TYPE IN ('N','T','C')
      AND NVL(CISR_MAC,1) NOT LIKE 'S%'
      AND APPINTV between 0 and 200
      AND CMPINTV between 0 and 6
      AND ATC IN ('W')
      AND &PROJECT&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND ADL='Y'
      AND IN_FACIL >
having sum(inward_qty+chng_qty) BETWEEN 1 AND 5
group by order_num,dsp_ind,entity,cris,seller_type,seller_name

```

Guidelines For: PR-4 Missed Appointments

C2C Guideline:	
Definition:	% Missed Appointment: The percentage of orders completed after the commitment date. % Missed Appointment - Trunks: The percentage of trunks completed for which there was a missed appointment. Hot Cut Measurements: Except for Metric PR-4-08, Hot Cut measurements have been transferred to Metric PR-9.
Performance Standard:	Metrics PR-4-01, 02, 04, 05, 09, 10 and 11: Parity with BA Retail.(footnote 26) Metric PR-4-06 ("Hot Cuts"): Deleted. Metric PR-4-07 LNP: 95% on Time. Metrics PR-4-03 and 08: No standard. Metrics PR-4-14 through PR-4-18, UNE 2 Wire xDSL Svcs.: 95% on Time
Exclusions:	BA Test Orders , Disconnect Orders Bell Atlantic Administrative orders Additional Segments(footnote 25) on orders (parts of a whole order are included in the whole) Orders that are not complete. (Orders are included in the month that they are complete) Suspend for non-payment and associated restore orders. For Metrics other than PR-4-03 and 08, orders not completed on time due to CLEC or end user delay.
Report Dimensions:	BA Retail, CLEC Aggregate, CLEC Specific, BA Affiliate Aggregate, BA Affiliate Specific
Geography:	POTS, 2 Wire Digital Services, and 2 Wire xDSL Services: Southern, Eastern Shore, Raritan, Suburban, Hudson-Bergen Specials, EEL and IOF: State Trunks: State
25 Segments - See Glossary	
26 Retail Comparison for IOF and EEL is total Retail Specials performance.	

RESALE (PROVISIONING)

Report Labels: PR-4-01-2200 Special Services - Provisioning

Parity with VZ Retail

Guidelines: PR-4 - Missed Appointments

% Missed Appt. – VZ – Total

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Orders Completed for product group.

Numerator:

Count of Orders where the Order completion date is greater than the order due date due to Bell Atlantic Reasons (CISR_MAC like 'C*') for product group

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &RSSS&
  AND &Exclusions&
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I'))
  AND ATC in ('K','M','R','Y','W','X','C','S')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Numerator

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &RSSS&
  AND &Exclusions&
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0
or INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0
or INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I'))
  AND NVL(CISR_MAC,0) LIKE 'C%'
  AND CMPINTV>APPINTV
  and nvl(last_comac,1) <> 'EO'
  and company_mac_days > 0
  AND ATC in ('K','M','R','Y','W','X','C','S')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &RTSS&
  AND &RetailExclusions&
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
  AND ATC in ('K','M','R','Y','W','X','C','S')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Numerator

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &RTSS&
  AND &RetailExclusions&
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0
or INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0
or INWARD_CKL>0 or CHNG_CKL>0)))
  AND NVL(CISR_MAC,0) LIKE 'C%'
  AND CMPINTV>APPINTV
  and nvl(last_comac,1) <> 'EO'
  and company_mac_days > 0
  AND ATC in ('K','M','R','Y','W','X','C','S')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

UNE (Provisioning)

Report Labels: PR-4-01-3200 Special Services Provisioning Parity with VZ Retail

Guidelines: PR-4 - Missed Appointments

% Missed Appointment – Verizon – Specials

Result: (Numerator / Denominator) * 100

Denominator: Count of Orders Completed for product group.	Numerator: Count of Orders where the Order completion date is greater than the order due date due to Bell Atlantic Reasons (CISR_MAC like 'C*') for product group
---	---

Filtered output file: ASR-UNE-SPECIAL

For the details on the above out put filtered file layout refer to File Appendix: 7 File Type: Excel

Denominator

```
SELECT
COUNT(*)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND ACT IN ('N', 'C')
AND PRODUCT_TYPE IN ('DS1', 'DS3')
AND ASR_STATUS = C
```

Numerator

```
SELECT
COUNT(*)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND ACT IN ('N', 'C')
AND PRODUCT_TYPE IN ('DS1', 'DS3')
AND CD > DD
AND NVL(SUBSTR(WFA_MFC,1,1),'X') NOT IN ('C', 'D')
AND ASR_STATUS = C
```

UNE (Provisioning)

Report Labels: PR-4-01-3510

Special Services Provisioning

Parity with VZ Retail

Guidelines: PR-4 - Missed Appointments

% Missed Appointment – Verizon – EEL

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Orders Completed for product group.

Numerator:

Count of Orders where the Order completion date is greater than the order due date due to Bell Atlantic Reasons (CISR_MAC like 'C*') for product group

Filtered output file: ASR-UNE-SPECIAL

For the details on the above out put filtered file layout refer to File Appendix: 7

File Type: Excel

Denominator

```
SELECT
COUNT(*)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND ACT IN ('N', 'C')
AND PRODUCT_TYPE = EEL
AND ASR_STATUS = C
```

Numerator

```
SELECT
COUNT(*)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND ACT IN ('N', 'C')
AND PRODUCT_TYPE = EEL
AND CD > DD
AND NVL(SUBSTR(WFA_MFC,1,1),'X') NOT IN ('C', 'D')
AND ASR_STATUS = C
```

Filtered output file: ASR-UNE-SPECIAL

For the details on the above out put filtered file layout refer to File Appendix: 7

File Type: Excel

Formula For: VERIZON**Denominator**

```
SELECT
COUNT(*)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND ACT IN ('N', 'C')
AND PRODUCT_TYPE = EEL
EEL
AND ASR_STATUS = C
```

Numerator

```
SELECT
COUNT(*)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND ACT IN ('N', 'C')
AND PRODUCT_TYPE = EEL
EEL
AND ASR_STATUS = C
AND CD > DD
AND NVL(SUBSTR(WFA_MFC,1,1),'X') NOT IN ('C', 'D')
```


UNE (Provisioning)

Report Labels: PR-4-01-3530 Special Services Provisioning Parity with VZ Retail

Guidelines: PR-4 - Missed Appointments

% Missed Appointment – Verizon – IOF

Result: (Numerator / Denominator) * 100

Denominator: Count of Orders Completed for product group.	Numerator: Count of Orders where the Order completion date is greater than the order due date due to Bell Atlantic Reasons (CISR_MAC like 'C*') for product group
---	---

Filtered output file: ASR-UNE-SPECIAL

For the details on the above out put filtered file layout refer to File Appendix: 7 File Type: Excel

Denominator

```
SELECT
COUNT(*)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND ACT IN ('N', 'C')
AND PRODUCT_TYPE = IOF
AND NVL(SUBSTR(WFA_MFC,1,1),'X') NOT IN ('C', 'D')
AND CD > DD
AND ASR_STATUS = C
```

Numerator

```
SELECT
COUNT(*)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND ACT IN ('N', 'C')
AND PRODUCT_TYPE = IOF
AND NVL(SUBSTR(WFA_MFC,1,1),'X') NOT IN ('C', 'D')
AND CD > DD
AND ASR_STATUS = C
```

TRUNKS (Aggregate)

Report Labels: PR-4-01-5000 PROVISIONING

Parity with IXC / FGD

Guidelines: PR-4 - Missed Appointment

% Missed Appointment – Verizon – Total

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Orders Completed for product group.

Numerator:

Count of Orders where the Order completion date is greater than the order due date due to Bell Atlantic Reasons (CISR_MAC like 'C*') for product group

Filtered output file: Trunking Filter Data

For the details on the above out put filtered file layout refer to File Appendix: 4 File Type: Excel

Formula For: CLEC**Denominator**

```
SELECT
SUM(NO_WFA_TRUNKS)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND SERVICE_TYPE IN ('T', 'R')
AND ORDER_STATUS = C
```

Numerator

```
SELECT
SUM(NO_WFA_TRUNKS)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND SERVICE_TYPE IN ('T', 'R')
AND ORDER_STATUS = C
AND NVL(SUBSTR(WFA_MFC,1,1),'X') NOT IN ('C', 'D')
AND WFA_DDCOMP > WFA_DDOBJ
```

Filtered output file: Trunking Filter Data

For the details on the above out put filtered file layout refer to File Appendix: 4 File Type: Excel

Formula For: VERIZON**Denominator**

```
SELECT
SUM(NO_WFA_TRUNKS)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND SERVICE_TYPE IN ('I', 'W')
AND ORDER_STATUS = C
```

Numerator

```
SELECT
SUM(NO_WFA_TRUNKS)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND SERVICE_TYPE IN ('I', 'W')
AND ORDER_STATUS = C
AND NVL(SUBSTR(WFA_MFC,1,1),'X') NOT IN ('C', 'D')
AND WFA_DDCOMP > WFA_DDOBJ
```

RESALE (PROVISIONING)

Report Labels: PR-4-02-2100 POTS - Provisioning - Total

Parity with VZ Retail

Guidelines: PR-4 - Missed Appointments

Average Delay Days – Total

Result: (Numerator / Denominator)**Denominator:**

Count of orders missed for Bell Atlantic reasons, by product group.

Numerator:

Sum of the completion date less due date for orders missed due to Bell Atlantic reasons by product group.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &SOUNPS&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,0) LIKE 'C%'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Numerator

```

SELECT
SUM(least(company_mac_days,cmpintv-appintv))
WHERE STATE = '&ST&'
      AND &SOUNPS&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,0) LIKE 'C%'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPS&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,0) LIKE 'C%'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Numerator

```

SELECT
SUM(least(company_mac_days,cmpintv-appintv))
WHERE STATE = '&ST&'
      AND &RTPS&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,0) LIKE 'C%'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

RESALE (PROVISIONING)

Report Labels: PR-4-02-2200 Special Services - Provisioning

Parity with VZ Retail

Guidelines: PR-4 - Missed Appointments

Average Delay Days – Total

Result: (Numerator / Denominator)**Denominator:**

Count of orders missed for Bell Atlantic reasons, by product group.

Numerator:

Sum of the completion date less due date for orders missed due to Bell Atlantic reasons by product group.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RSSS&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE = 'R' and
RESELLER_ACT='I' ))
      AND NVL(CISR_MAC,0) LIKE 'C%'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN
(&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Numerator

```

SELECT
SUM(least(company_mac_days,cmpintv-appintv))
WHERE STATE = '&ST&'
      AND &RSSS&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0
or INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0
or INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE = 'R' and
RESELLER_ACT='I' ))
      AND NVL(CISR_MAC,0) LIKE 'C%'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN
(&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTSS&
      AND &RetailExclusions&
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,0) LIKE 'C%'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Numerator

```

SELECT
SUM(least(company_mac_days,cmpintv-appintv))
WHERE STATE = '&ST&'
      AND &RTSS&
      AND &RetailExclusions&
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0
or INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0
or INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,0) LIKE 'C%'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

RESALE (PROVISIONING)

Report Labels: PR-4-02-2341

Complex Services - 2 Wire Digital

Parity with VZ Retail

Guidelines: PR-4 - Missed Appointment

Average Delay Days – Total

Result: (Numerator / Denominator)**Denominator:**

Count of orders missed for Bell Atlantic reasons, by product group.

Numerator:

Sum of the completion date less due date for orders missed due to Bell Atlantic reasons by product group.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RSPI&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE = 'R' and
RESELLER_ACT='I' ))
      AND NVL(CISR_MAC,0) LIKE 'C%'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
SUM(least(company_mac_days,cmpintv-appintv))
WHERE STATE = '&ST&'
      AND &RSPI&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE = 'R' and
RESELLER_ACT='I' ))
      AND NVL(CISR_MAC,0) LIKE 'C%'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPI&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0
or INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0
or INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,0) LIKE 'C%'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
SUM(least(company_mac_days,cmpintv-appintv))
WHERE STATE = '&ST&'
      AND &RTPI&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0
or INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0
or INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,0) LIKE 'C%'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

RESALE (PROVISIONING)

Report Labels: PR-4-02-2342 Complex Services - 2 Wire xDSL

Parity with VZ Retail

Guidelines: PR-4 - Missed Appointment

Average Delay Days – Total

Result: (Numerator / Denominator)**Denominator:**

Count of orders missed for Bell Atlantic reasons, by product group.

Numerator:

Sum of the completion date less due date for orders missed due to Bell Atlantic reasons by product group.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RSPD&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' ))
      AND NVL(CISR_MAC,0) LIKE 'C%'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
SUM(least(company_mac_days,cmpintv-appintv))
WHERE STATE = '&ST&'
      AND &RSPD&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0
or INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' ))
      AND NVL(CISR_MAC,0) LIKE 'C%'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPD&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,0) LIKE 'C%'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
SUM(least(company_mac_days,cmpintv-appintv))
WHERE STATE = '&ST&'
      AND &RTPD&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,0) LIKE 'C%'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

UNE (Provisioning)

Report Labels: PR-4-02-3100 POTS - Provisioning

Parity with VZ Retail

Guidelines: PR-4 - Missed Appointments

Average Delay Days – Total

Result: (Numerator / Denominator)**Denominator:**

Count of orders missed for Bell Atlantic reasons, by product group.

Numerator:

Sum of the completion date less due date for orders missed due to Bell Atlantic reasons by product group.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &SOUNPS&
  AND &Exclusions
  AND STATUS in &STATUS&
  AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
  AND NVL(CISR_MAC,0) LIKE 'C%'
  AND CMPINTV>APPINTV
  and nvl(last_comac,1) <> 'EO'
  and company_mac_days > 0
  AND ATC IN ('K','M','R','Y','W','X','C','S')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Numerator

```

SELECT
SUM(least(company_mac_days,cmpintv-appintv))
WHERE STATE = '&ST&'
  AND &SOUNPS&
  AND &Exclusions
  AND STATUS in &STATUS&
  AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
  AND NVL(CISR_MAC,0) LIKE 'C%'
  AND CMPINTV>APPINTV
  and nvl(last_comac,1) <> 'EO'
  and company_mac_days > 0
  AND ATC IN ('K','M','R','Y','W','X','C','S')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &RTPS&
  AND &RetailExclusions
  AND STATUS in &STATUS&
  AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
  AND NVL(CISR_MAC,0) LIKE 'C%'
  AND CMPINTV>APPINTV
  and nvl(last_comac,1) <> 'EO'
  and company_mac_days > 0
  AND ATC IN ('K','M','R','Y','W','X','C','S')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Numerator

```

SELECT
SUM(least(company_mac_days,cmpintv-appintv))
WHERE STATE = '&ST&'
  AND &RTPS&
  AND &RetailExclusions
  AND STATUS in &STATUS&
  AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
  AND NVL(CISR_MAC,0) LIKE 'C%'
  AND CMPINTV>APPINTV
  and nvl(last_comac,1) <> 'EO'
  and company_mac_days > 0
  AND ATC IN ('K','M','R','Y','W','X','C','S')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

UNE (Provisioning)

Report Labels:

PR-4-02-3200

Special Services Provisioning

Parity with VZ Retail

Guidelines:

PR-4 - Missed Appointments

Average Delay Days – Specials

Result: (Numerator / Denominator)	
Denominator:	Numerator:
Count of orders missed for Bell Atlantic reasons, by product group.	Sum of the completion date less due date for orders missed due to Bell Atlantic reasons by product group.

Filtered output file: ASR-UNE-SPECIAL

For the details on the above out put filtered file layout refer to File Appendix: 7 File Type: Excel

Denominator	Numerator
<div>SELECT COUNT(*) WHERE STATE = NJ AND ACTIVITY_DATE >= STARTDATE AND ACTIVITY_DATE <= ENDDATE AND ACT IN ('N', 'C') AND PRODUCT_TYPE IN ('DS1', 'DS3') AND ASR_STATUS = C</div>	<div>SELECT SUM(DELAY_DAYS) WHERE STATE = NJ AND ACTIVITY_DATE >= STARTDATE AND ACTIVITY_DATE <= ENDDATE AND ACT IN ('N', 'C') AND PRODUCT_TYPE IN ('DS1', 'DS3') AND NVL(SUBSTR(WFA_MFC,1,1),'X') NOT IN ('C', 'D') AND ASR_STATUS = C</div>

UNE (Provisioning)

Report Labels: PR-4-02-3341

Complex Services - 2 Wire Digital

Parity with VZ Retail

Guidelines: PR-4 - Missed Appointments

Average Delay Days – Total

Result: (Numerator / Denominator)**Denominator:**

Count of orders missed for Bell Atlantic reasons, by product group.

Numerator:

Sum of the completion date less due date for orders missed due to Bell Atlantic reasons by product group.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &SOUNPI&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,0) LIKE 'C%'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
SUM(least(company_mac_days,cmpintv-appintv))
WHERE STATE = '&ST&'
      AND &SOUNPI&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,0) LIKE 'C%'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPI&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0
or INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0
or INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,0) LIKE 'C%'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
SUM(least(company_mac_days,cmpintv-appintv))
WHERE STATE = '&ST&'
      AND &RTPI&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0
or INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0
or INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,0) LIKE 'C%'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

UNE (Provisioning)

Report Labels: PR-4-02-3342 Complex Services - 2 Wire xDSL

Parity with VZ Retail

Guidelines: PR-4 - Missed Appointments

Average Delay Days – Total

Result: (Numerator / Denominator)**Denominator:**

Count of orders missed for Bell Atlantic reasons, by product group.

Numerator:

Sum of the completion date less due date for orders missed due to Bell Atlantic reasons by product group.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &SOUNPD&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,0) LIKE 'C%'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
SUM(least(company_mac_days,cmpintv-appintv))
WHERE STATE = '&ST&'
      AND &SOUNPD&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0
or INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,0) LIKE 'C%'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPD&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,0) LIKE 'C%'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
SUM(least(company_mac_days,cmpintv-appintv))
WHERE STATE = '&ST&'
      AND &RTPD&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,0) LIKE 'C%'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

UNE (Provisioning)

Report Labels:

PR-4-02-3510

Special Services Provisioning

Parity with VZ Retail

Guidelines:

PR-4 - Missed Appointments

Average Delay Days – EEL

Result: (Numerator / Denominator)	
Denominator:	Numerator:
Count of orders missed for Bell Atlantic reasons, by product group.	Sum of the completion date less due date for orders missed due to Bell Atlantic reasons by product group.

Filtered output file: ASR-UNE-SPECIAL

For the details on the above out put filtered file layout refer to File Appendix: 7 File Type: Excel

Denominator	Numerator
<div>SELECT COUNT(*) WHERE STATE = NJ AND ACTIVITY_DATE >= STARTDATE AND ACTIVITY_DATE <= ENDDATE AND ACT IN ('N', 'C') AND PRODUCT_TYPE = EEL AND ASR_STATUS = C</div>	<div>SELECT SUM(DELAY_DAYS) WHERE STATE = NJ AND ACTIVITY_DATE >= STARTDATE AND ACTIVITY_DATE <= ENDDATE AND ACT IN ('N', 'C') AND PRODUCT_TYPE = EEL AND NVL(SUBSTR(WFA_MFC,1,1),'X') NOT IN ('C', 'D') AND ASR_STATUS = C</div>

UNE (Provisioning)

Report Labels: PR-4-02-3530 Special Services Provisioning Parity with VZ Retail

Guidelines: PR-4 - Missed Appointments

Average Delay Days – IOF

Result: (Numerator / Denominator)	
Denominator:	Numerator:
Count of orders missed for Bell Atlantic reasons, by product group.	Sum of the completion date less due date for orders missed due to Bell Atlantic reasons by product group.

Filtered output file: ASR-UNE-SPECIAL
For the details on the above out put filtered file layout refer to File Appendix: 7 File Type: Excel

Denominator	Numerator
<pre>SELECT COUNT(*) WHERE STATE = NJ AND ACTIVITY_DATE >= STARTDATE AND ACTIVITY_DATE <= ENDDATE AND ACT IN ('N', 'C') AND PRODUCT_TYPE = IOF AND ASR_STATUS = C</pre>	<pre>SELECT SUM(DELAY_DAYS) WHERE STATE = NJ AND ACTIVITY_DATE >= STARTDATE AND ACTIVITY_DATE <= ENDDATE AND ACT IN ('N', 'C') AND PRODUCT_TYPE = IOF AND NVL(SUBSTR(WFA_MFC,1,1),'X') NOT IN ('C', 'D') AND ASR_STATUS = C</pre>

TRUNKS (Aggregate)

Report Labels: PR-4-02-5000 PROVISIONING

Parity with IXC / FGD

Guidelines: PR-4 - Missed Appointment

Average Delay Days – Total

Result: (Numerator / Denominator)**Denominator:**

Count of orders missed for Bell Atlantic reasons, by product group.

Numerator:

Sum of the completion date less due date for orders missed due to Bell Atlantic reasons by product group.

Filtered output file: Trunking Filter Data

For the details on the above out put filtered file layout refer to File Appendix: 4 File Type: Excel

Formula For: CLEC**Denominator**

```
SELECT
SUM(NO_WFA_TRUNKS)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND SERVICE_TYPE IN ('T', 'R')
AND ORDER_STATUS = C
```

```
SELECT
SUM(NO_WFA_TRUNKS)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND SERVICE_TYPE IN ('T', 'R')
AND ORDER_STATUS = C
AND NVL(SUBSTR(WFA_MFC,1,1),'X') NOT IN ('C', 'D')
AND WFA_DDCOMP > WFA_DDOBJ
```

Numerator

```
SELECT
SUM(NO_WFA_TRUNKS)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND SERVICE_TYPE IN ('T', 'R')
AND ORDER_STATUS = C
AND NVL(SUBSTR(WFA_MFC,1,1),'X') IN ('C', 'D')
AND WFA_DDCOMP > WFA_DDOBJ
```

```
SELECT
SUM(NVL(WFA_COMPLETED_INTERVAL -
WFA_OFFERED_INTERVAL, 0)*NO_WFA_TRUNKS)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND SERVICE_TYPE IN ('T', 'R')
AND ORDER_STATUS = C
AND NVL(SUBSTR(WFA_MFC,1,1),'X') NOT IN ('C', 'D')
AND WFA_DDCOMP > WFA_DDOBJ
```

Filtered output file: Trunking Filter Data

For the details on the above out put filtered file layout refer to File Appendix: 4 File Type: Excel

Formula For: VERIZON**Denominator**

```
SELECT
SUM(NO_WFA_TRUNKS)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND SERVICE_TYPE IN ('I', 'W')
AND ORDER_STATUS = C
AND NVL(SUBSTR(WFA_MFC,1,1),'X') NOT IN ('C', 'D')
AND WFA_DDCOMP > WFA_DDOBJ
```

Numerator

```
SELECT
SUM(NVL(WFA_COMPLETED_INTERVAL -
WFA_OFFERED_INTERVAL, 0)*NO_WFA_TRUNKS)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND SERVICE_TYPE IN ('I', 'W')
AND ORDER_STATUS = C
AND NVL(SUBSTR(WFA_MFC,1,1),'X') NOT IN ('C', 'D')
AND WFA_DDCOMP > WFA_DDOBJ
```

RESALE (PROVISIONING)

Report Labels: PR-4-03-2100 POTS - Provisioning - Total

No Standard

Guidelines: PR-4 - Missed Appointments

% Missed Appt. – Customer

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Orders Completed for product group.

Numerator:

Count of Orders where the Order completion date is greater than the order due date due to Customer Reasons (CISR_MAC = 'SA','SR','SO','SL') for product group

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &RSPS&
  AND &Exclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE = 'R' and
RESELLER_ACT='I' ))
  AND ATC in ('K','M','R','Y','W','X','C','S')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Numerator

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &RSPS&
  AND &Exclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE = 'R' and
RESELLER_ACT='I' ))
  AND ATC in ('K','M','R','Y','W','X','C','S')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
  AND NVL(CISR_MAC,1) LIKE 'S%'
  AND CMPINTV>APPINTV

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &RTPS&
  AND &RetailExclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
  AND ATC in ('K','M','R','Y','W','X','C','S')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Numerator

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &RTPS&
  AND &RetailExclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
  AND ATC in ('K','M','R','Y','W','X','C','S')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
  AND NVL(CISR_MAC,1) LIKE 'S%'
  AND CMPINTV>APPINTV

```

RESALE (PROVISIONING)

Report Labels: PR-4-03-2200 Special Services - Provisioning

No Standard

Guidelines: PR-4 - Missed Appointments

% Missed Appt. – Customer

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Orders Completed for product group.

Numerator:

Count of Orders where the Order completion date is greater than the order due date due to Customer Reasons (CISR_MAC ='SA','SR','SO','SL') for product group

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```
SELECT
count(order_num)
WHERE STATE = '&ST&'
  AND &RSSS&
  AND &Exclusions&
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I'))
  AND ATC in ('K','M','R','Y','W','X','C','S')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
```

Numerator

```
SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &RSSS&
  AND &Exclusions&
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' ))
  AND ATC in ('K','M','R','Y','W','X','C','S')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
  AND NVL(CISR_MAC,1) LIKE 'S%'
  AND CMPINTV>APPINTV
```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator**

```
SELECT
count(order_num)
WHERE STATE = '&ST&'
  AND &RTSS&
  AND &RetailExclusions&
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
  AND ATC in ('K','M','R','Y','W','X','C','S')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
```

Numerator

```
SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &RTSS&
  AND &RetailExclusions&
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
  AND ATC in ('K','M','R','Y','W','X','C','S')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
  AND NVL(CISR_MAC,1) LIKE 'S%'
  AND CMPINTV>APPINTV
```

RESALE (PROVISIONING)

Report Labels: PR-4-03-2341

Complex Services - 2 Wire Digital

No Standard

Guidelines: PR-4 - Missed Appointment

% Missed Appt. – Customer

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Orders Completed for product group.

Numerator:

Count of Orders where the Order completion date is greater than the order due date due to Customer Reasons (CISR_MAC = 'SA','SR','SO','SL') for product group

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &RSPI&
  AND &Exclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' ))
  AND ATC in ('K','M','R','Y','W','X','C','S')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Numerator

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &RSPI&
  AND &Exclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' ))
  AND ATC in ('K','M','R','Y','W','X','C','S')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
  AND NVL(CISR_MAC,1) LIKE 'S%'
  AND CMPINTV>APPINTV

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &RTPI&
  AND &RetailExclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
  AND ATC in ('K','M','R','Y','W','X','C','S')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Numerator

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &RTPI&
  AND &RetailExclusions&
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
  AND ATC in ('K','M','R','Y','W','X','C','S')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
  AND NVL(CISR_MAC,1) LIKE 'S%'
  AND CMPINTV>APPINTV

```


RESALE (PROVISIONING)

Report Labels: PR-4-03-2342 Complex Services - 2 Wire xDSL

No Standard

Guidelines: PR-4 - Missed Appointment

% Missed Appt. – Customer

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Orders Completed for product group.

Numerator:

Count of Orders where the Order completion date is greater than the order due date due to Customer Reasons (CISR_MAC = 'SA','SR','SO','SL') for product group

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &RSPD&
  AND &Exclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' ))
  AND ATC in ('K','M','R','Y','W','X','C','S')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &RSPD&
  AND &Exclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' ))
  AND ATC in ('K','M','R','Y','W','X','C','S')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
  AND NVL(CISR_MAC,1) LIKE 'S%'
  AND CMPINTV>APPINTV

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &RTPD&
  AND &RetailExclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
  AND ATC in ('K','M','R','Y','W','X','C','S')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &RTPD&
  AND &RetailExclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
  AND ATC in ('K','M','R','Y','W','X','C','S')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
  AND NVL(CISR_MAC,1) LIKE 'S%'
  AND CMPINTV>APPINTV

```

UNE (Provisioning)

Report Labels: PR-4-03-3100 POTS - Provisioning

No Standard

Guidelines: PR-4 - Missed Appointments

% Missed Appointment – Customer

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Orders Completed for product group.

Numerator:

Count of Orders where the Order completion date is greater than the order due date due to Customer Reasons (CISR_MAC ='SA','SR','SO','SL') for product group

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &SOUNPS&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (
(ATC IN ('K','M','R','Y','W','X','C','S') AND ((TYPE IN ('N','T')) or
(TYPE in 'C' and (OUT_QTY=0 or INWARD_QTY>0 or
CHNG_QTY>0) and (OUTWARD_CKL=0 or INWARD_CKL>0 or
CHNG_CKL>0))))
or (type in ('R') and PON is not null and cls in ('RRM','RBM')) )

      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Numerator

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &SOUNPS&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (
(ATC IN ('K','M','R','Y','W','X','C','S') AND ((TYPE IN ('N','T')) or
(TYPE in 'C' and (OUT_QTY=0 or INWARD_QTY>0 or
CHNG_QTY>0) and (OUTWARD_CKL=0 or INWARD_CKL>0 or
CHNG_CKL>0))))
or (type in ('R') and PON is not null and cls in ('RRM','RBM')) )
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND NVL(CISR_MAC,1) LIKE 'S%'
      AND CMPINTV>APPINTV

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPS&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Numerator

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPS&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND NVL(CISR_MAC,1) LIKE 'S%'
      AND CMPINTV>APPINTV

```

UNE (Provisioning)

Report Labels: PR-4-03-3200 Special Services Provisioning No Standard

Guidelines: PR-4 - Missed Appointments

% Missed Appointment – Customer - Specials

Result: (Numerator / Denominator) * 100

Denominator: Count of Orders Completed for product group.	Numerator: Count of Orders where the Order completion date is greater than the order due date due to Customer Reasons (CISR_MAC ='SA','SR','SO','SL') for product group
---	---

Filtered output file: ASR-UNE-SPECIAL

For the details on the above out put filtered file layout refer to File Appendix: 7 File Type: Excel

Denominator

```
SELECT
COUNT(*)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND ACT IN ('N', 'C')
AND PRODUCT_TYPE IN ('DS1', 'DS3')
AND ASR_STATUS = C
```

Numerator

```
SELECT
COUNT(*)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND ACT IN ('N', 'C')
AND PRODUCT_TYPE IN ('DS1', 'DS3')
AND NVL(SUBSTR(WFA_MFC,1,1),'X') NOT IN ('C', 'D')
AND ASR_STATUS = C
AND CD > DD
```

UNE (Provisioning)

Report Labels: PR-4-03-3341

Complex Services - 2 Wire Digital

No Standard

Guidelines: PR-4 - Missed Appointments

% MA – Customer

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Orders Completed for product group.

Numerator:

Count of Orders where the Order completion date is greater than the order due date due to Customer Reasons (CISR_MAC = 'SA','SR','SO','SL') for product group

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```
SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &SOUNPI&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
```

Numerator

```
SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &SOUNPI&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND NVL(CISR_MAC,1) LIKE 'S%'
      AND CMPINTV>APPINTV
```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator**

```
SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPI&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
```

Numerator

```
SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPI&
      AND &RetailExclusions&
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND NVL(CISR_MAC,1) LIKE 'S%'
      AND CMPINTV>APPINTV
```

UNE (Provisioning)

Report Labels: PR-4-03-3342

Complex Services - 2 Wire xDSL

No Standard

Guidelines: PR-4 - Missed Appointments

% MA – Customer

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Orders Completed for product group.

Numerator:

Count of Orders where the Order completion date is greater than the order due date due to Customer Reasons (CISR_MAC ='SA','SR','SO','SL') for product group

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &SOUNPD&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,*),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &SOUNPD&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,*),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND NVL(CISR_MAC,1) LIKE 'S%'
      AND CMPINTV>APPINTV

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPD&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,*),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPD&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,*),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND NVL(CISR_MAC,1) LIKE 'S%'
      AND CMPINTV>APPINTV

```

UNE (Provisioning)

Report Labels: PR-4-03-3510 Special Services Provisioning No Standard

Guidelines: PR-4 - Missed Appointments

% Missed Appointment – Customer - EEL

Result: (Numerator / Denominator) * 100

Denominator: Count of Orders Completed for product group.	Numerator: Count of Orders where the Order completion date is greater than the order due date due to Customer Reasons (CISR_MAC ='SA','SR','SO','SL') for product group
---	---

Filtered output file: ASR-UNE-SPECIAL

For the details on the above out put filtered file layout refer to File Appendix: 7 File Type: Excel

Denominator	Numerator
<div>SELECT COUNT(*) WHERE STATE = NJ AND ACTIVITY_DATE >= STARTDATE AND ACTIVITY_DATE <= ENDDATE AND ACT IN ('N', 'C') AND PRODUCT_TYPE = EEL AND ASR_STATUS = C</div>	<div>SELECT COUNT(*) WHERE STATE = NJ AND ACTIVITY_DATE >= STARTDATE AND ACTIVITY_DATE <= ENDDATE AND ACT IN ('N', 'C') AND PRODUCT_TYPE = EEL AND NVL(SUBSTR(WFA_MFC,1,1),'X') NOT IN ('C', 'D') AND ASR_STATUS = C AND CD > DD</div>

TRUNKS (Aggregate)

Report Labels:

PR-4-03-5000

PROVISIONING

No Standard

Guidelines:

PR-4 - Missed Appointment

% Missed Appointment – Customer

Result: (Numerator / Denominator) * 100

Denominator: Count of Orders Completed for product group.	Numerator: Count of Orders where the Order completion date is greater than the order due date due to Customer Reasons (CISR_MAC ='SA','SR','SO','SL') for product group
---	---

Filtered output file: Trunking Filter Data

For the details on the above out put filtered file layout refer to File Appendix: 4 File Type: Excel

Formula For: VERIZON

Denominator	Numerator
<div>SELECT SUM(NO_WFA_TRUNKS) WHERE STATE = NJ AND ACTIVITY_DATE >= STARTDATE AND ACTIVITY_DATE <= ENDDATE AND SERVICE_TYPE IN ('I', 'W') AND ORDER_STATUS = C</div>	<div>SELECT SUM(NO_WFA_TRUNKS) WHERE STATE = NJ AND ACTIVITY_DATE >= STARTDATE AND ACTIVITY_DATE <= ENDDATE AND SERVICE_TYPE IN ('I', 'W') AND ORDER_STATUS = C AND NVL(SUBSTR(WFA_MFC,1,1),'X') IN ('C', 'D') AND WFA_DDCOMP > WFA_DDOBJ</div>

RESALE (PROVISIONING)

Report Labels: PR-4-04-2100 POTS - Provisioning - Total

Parity with VZ Retail

Guidelines: PR-4 - Missed Appointments

% Missed Appt. – VZ – Dispatch

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Dispatched Orders Completed for product group.

Numerator:

Count of Dispatched Orders where the Order completion date is greater than the order due date due to Bell Atlantic Reasons (CISR_MAC like 'C') for product group.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RSPS&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and
((INWARD_QTY>=0 or CHNG_QTY>=0) and OUT_QTY=0) or
((INWARD_QTY>0 or CHNG_QTY>0)and OUT_QTY>0)) or
(TYPE = 'R' and RESELLER_ACT='I' ))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0

```

Numerator

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RSPS&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and
((INWARD_QTY>=0 or CHNG_QTY>=0) and OUT_QTY=0) or
((INWARD_QTY>0 or CHNG_QTY>0)and OUT_QTY>0)) or
(TYPE = 'R' and RESELLER_ACT='I' ))
      AND NVL(CISR_MAC,0) LIKE 'C%'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**


```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPS&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPS&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,0) LIKE 'C%'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0

```

RESALE (PROVISIONING)

Report Labels: PR-4-04-2341

Complex Services - 2 Wire Digital

Parity with VZ Retail

Guidelines: PR-4 - Missed Appointment

% Missed Appt. – VZ – Dispatch

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Dispatched Orders Completed for product group.

Numerator:

Count of Dispatched Orders where the Order completion date is greater than the order due date due to Bell Atlantic Reasons (CISR_MAC like 'C*') for product group.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RSPI&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and
((INWARD_QTY>=0 or CHNG_QTY>=0) and OUT_QTY=0) or
((INWARD_QTY>0 or CHNG_QTY>0)and OUT_QTY>0)) or
(TYPE = 'R' and RESELLER_ACT='I' ))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RSPI&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and
((INWARD_QTY>=0 or CHNG_QTY>=0) and OUT_QTY=0) or
((INWARD_QTY>0 or CHNG_QTY>0)and OUT_QTY>0)) or
(TYPE = 'R' and RESELLER_ACT='I' ))
      AND NVL(CISR_MAC,0) LIKE 'C%'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPI&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPI&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,0) LIKE 'C%'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0

```

RESALE (PROVISIONING)

Report Labels: PR-4-04-2342

Complex Services - 2 Wire xDSL

Parity with VZ Retail

Guidelines: PR-4 - Missed Appointment

% Missed Appt. – VZ – Dispatch

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Dispatched Orders Completed for product group.

Numerator:

Count of Dispatched Orders where the Order completion date is greater than the order due date due to Bell Atlantic Reasons (CISR_MAC like 'C') for product group.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RSPD&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and
((INWARD_QTY>=0 or CHNG_QTY>=0) and OUT_QTY=0) or
((INWARD_QTY>0 or CHNG_QTY>0)and OUT_QTY>0)) or
(TYPE = 'R' and RESELLER_ACT='I' ))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RSPD&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and
((INWARD_QTY>=0 or CHNG_QTY>=0) and OUT_QTY=0) or
((INWARD_QTY>0 or CHNG_QTY>0)and OUT_QTY>0)) or
(TYPE = 'R' and RESELLER_ACT='I' ))
      AND NVL(CISR_MAC,0) LIKE 'C%'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPD&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPD&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,0) LIKE 'C%'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0

```

UNE (Provisioning)

Report Labels: PR-4-04-3113 POTS - Provisioning

Parity with VZ Retail

Guidelines: PR-4 - Missed Appointments

% Missed Appointment – Verizon – Dispatch - Loop New

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Dispatched Orders Completed for product group.

Numerator:

Count of Dispatched Orders where the Order completion date is greater than the order due date due to Bell Atlantic Reasons (CISR_MAC like 'C') for product group.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &SOUNPSLN&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND TYPE IN ('N','T','C')
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0

```

Numerator

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &SOUNPSLN&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND TYPE IN ('N','T','C')
      AND NVL(CISR_MAC,0) LIKE 'C%'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPS&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0

```

Numerator

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPS&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,0) LIKE 'C%'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0

```

UNE (Provisioning)

Report Labels: PR-4-04-3140 POTS - Provisioning

Parity with VZ Retail

Guidelines: PR-4 - Missed Appointments

% Missed Appointment – Verizon – Dispatch - Platform

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Dispatched Orders Completed for product group.

Numerator:

Count of Dispatched Orders where the Order completion date is greater than the order due date due to Bell Atlantic Reasons (CISR_MAC like 'C*') for product group.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```
SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
AND &SOUNPSP&
AND &Exclusions
AND STATUS in &STATUS&
AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
AND (
(ATC IN ('K','M','R','Y','W','X','C','S') AND ((TYPE IN ('N','T')) or
(TYPE in 'C' and (OUT_QTY=0 or INWARD_QTY>0 or
CHNG_QTY>0) and (OUTWARD_CKL=0 or INWARD_CKL>0 or
CHNG_CKL>0))))
or (type in ('R') and PON is not null) )
```

```
SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
AND &SOUNPSP&
AND &Exclusions
AND STATUS in &STATUS&
AND NVL(CISR_MAC,0) LIKE 'C%'
AND CMPINTV>APPINTV
and nvl(last_comac,1) <> 'EO'
and company_mac_days > 0
AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
AND (
(ATC IN ('K','M','R','Y','W','X','C','S') AND ((TYPE IN ('N','T')) or
(TYPE in 'C' and (OUT_QTY=0 or INWARD_QTY>0 or
CHNG_QTY>0) and (OUTWARD_CKL=0 or INWARD_CKL>0 or
CHNG_CKL>0))))
or (type in ('R') and PON is not null) )
```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPS&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPS&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,0) LIKE 'C%'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0

```


UNE (Provisioning)

Report Labels: PR-4-04-3341

Complex Services - 2 Wire Digital

Parity with VZ Retail

Guidelines: PR-4 - Missed Appointments

% MA – VZ – Dispatch

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Dispatched Orders Completed for product group.

Numerator:

Count of Dispatched Orders where the Order completion date is greater than the order due date due to Bell Atlantic Reasons (CISR_MAC like 'C') for product group.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &SOUNPI&
  AND &Exclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
  AND ATC in ('K','M','R','Y','W','X','C','S')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &SOUNPI&
  AND &Exclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
  AND NVL(CISR_MAC,0) LIKE 'C%'
  AND CMPINTV>APPINTV
  and nvl(last_comac,1) <> 'EO'
  and company_mac_days > 0
  AND ATC in ('K','M','R','Y','W','X','C','S')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &RTPI&
  AND &RetailExclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
  AND ATC in ('K','M','R','Y','W','X','C','S')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
  AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &RTPI&
  AND &RetailExclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
  AND NVL(CISR_MAC,0) LIKE 'C%'
  AND CMPINTV>APPINTV
  and nvl(last_comac,1) <> 'EO'
  and company_mac_days > 0
  AND ATC in ('K','M','R','Y','W','X','C','S')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
  AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0

```

UNE (Provisioning)

Report Labels: PR-4-04-3342

Complex Services - 2 Wire xDSL

Parity with VZ Retail

Guidelines: PR-4 - Missed Appointments

% MA – VZ – Dispatch

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Dispatched Orders Completed for product group.

Numerator:

Count of Dispatched Orders where the Order completion date is greater than the order due date due to Bell Atlantic Reasons (CISR_MAC like 'C') for product group.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &SOUNPD&
  AND &Exclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
  AND ATC in ('K','M','R','Y','W','X','C','S')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &SOUNPD&
  AND &Exclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
  AND NVL(CISR_MAC,0) LIKE 'C%'
  AND CMPINTV>APPINTV
  and nvl(last_comac,1) <> 'EO'
  and company_mac_days > 0
  AND ATC in ('K','M','R','Y','W','X','C','S')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &RTPD&
  AND &RetailExclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
  AND ATC in ('K','M','R','Y','W','X','C','S')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
  AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &RTPD&
  AND &RetailExclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
  AND NVL(CISR_MAC,0) LIKE 'C%'
  AND CMPINTV>APPINTV
  and nvl(last_comac,1) <> 'EO'
  and company_mac_days > 0
  AND ATC in ('K','M','R','Y','W','X','C','S')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
  AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0

```

RESALE (PROVISIONING)

Report Labels: PR-4-05-2100 POTS - Provisioning - Total

Parity with VZ Retail

Guidelines: PR-4 - Missed Appointments

% Missed Appt. – VZ – No Dispatch

Result: (Numerator / Denominator) * 100**Denominator:**

Count of No Dispatch Orders Completed for product group.

Numerator:

Count of No Dispatch Orders where the Order completion date is greater than the order due date due to Bell Atlantic Reasons (CISR_MAC like 'C') for product group.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```
SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &RSPS&
  AND &Exclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' ))
  AND ATC in ('K','M','R','Y','W','X','C','S')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
```

Numerator

```
SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &RSPS&
  AND &Exclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' ))
  AND NVL(CISR_MAC,0) LIKE 'C%'
  AND CMPINTV>APPINTV
  and nvl(last_comac,1) <> 'EO'
  and company_mac_days > 0
  AND ATC in ('K','M','R','Y','W','X','C','S')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPS&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPS&
      AND &RetailExclusions
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUS&
      AND NVL(CISR_MAC,0) LIKE 'C%'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0

```

RESALE (PROVISIONING)

Report Labels: PR-4-05-2341

Complex Services - 2 Wire Digital

Parity with VZ Retail

Guidelines: PR-4 - Missed Appointment

% Missed Appt. – VZ – No Dispatch

Result: (Numerator / Denominator) * 100**Denominator:**

Count of No Dispatch Orders Completed for product group.

Numerator:

Count of No Dispatch Orders where the Order completion date is greater than the order due date due to Bell Atlantic Reasons (CISR_MAC like 'C') for product group.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```
SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &RSPI&
  AND &Exclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' ))
  AND ATC in ('K','M','R','Y','W','X','C','S')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
  AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
```

Numerator

```
SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &RSPI&
  AND &Exclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' ))
  AND NVL(CISR_MAC,0) LIKE 'C%'
  AND CMPINTV>APPINTV
  and nvl(last_comac,1) <> 'EO'
  and company_mac_days > 0
  AND ATC in ('K','M','R','Y','W','X','C','S')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
  AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPI&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPI&
      AND &RetailExclusions
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUS&
      AND NVL(CISR_MAC,0) LIKE 'C%'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0

```

RESALE (PROVISIONING)

Report Labels: PR-4-05-2342

Complex Services - 2 Wire xDSL

Parity with VZ Retail

Guidelines: PR-4 - Missed Appointment

% Missed Appt. – VZ – No Dispatch

Result: (Numerator / Denominator) * 100**Denominator:**

Count of No Dispatch Orders Completed for product group.

Numerator:

Count of No Dispatch Orders where the Order completion date is greater than the order due date due to Bell Atlantic Reasons (CISR_MAC like 'C*') for product group.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```
SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &RSPD&
  AND &Exclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' ))
  AND ATC in ('K','M','R','Y','W','X','C','S')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
  AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
```

Numerator

```
SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &RSPD&
  AND &Exclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' ))
  AND NVL(CISR_MAC,0) LIKE 'C%'
  AND CMPINTV>APPINTV
  and nvl(last_comac,1) <> 'EO'
  and company_mac_days > 0
  AND ATC in ('K','M','R','Y','W','X','C','S')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
  AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPD&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPD&
      AND &RetailExclusions
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUS&
      AND NVL(CISR_MAC,0) LIKE 'C%'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0

```


UNE (Provisioning)

Report Labels: PR-4-05-3123

POTS - Provisioning

Parity with VZ Retail

Guidelines: PR-4 - Missed Appointments

% Missed Appointment – Verizon – No Dispatch - Other than Platform & Hot Cut

Result: (Numerator / Denominator) * 100**Denominator:**

Count of No Dispatch Orders Completed for product group.

Numerator:

Count of No Dispatch Orders where the Order completion date is greater than the order due date due to Bell Atlantic Reasons (CISR_MAC like 'C*') for product group.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &SOUNPSNPH&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &SOUNPSNPH&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,0) LIKE 'C%'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPS&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPS&
      AND &RetailExclusions
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUS&
      AND NVL(CISR_MAC,0) LIKE 'C%'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0

```


UNE (Provisioning)

Report Labels: PR-4-05-3140

POTS - Provisioning

Parity with VZ Retail

Guidelines: PR-4 - Missed Appointments

% Missed Appointment – Verizon – No Dispatch - Platform

Result: (Numerator / Denominator) * 100**Denominator:**

Count of No Dispatch Orders Completed for product group.

Numerator:

Count of No Dispatch Orders where the Order completion date is greater than the order due date due to Bell Atlantic Reasons (CISR_MAC like 'C**') for product group.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &SOUNPSP&
  AND &Exclusions
  AND STATUS in &STATUS&
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
  AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
  AND (
(ATC IN ('K','M','R','Y','W','X','C','S') AND ((TYPE IN ('N','T')) or
(TYPE in 'C' and (OUT_QTY=0 or INWARD_QTY>0 or
CHNG_QTY>0) and (OUTWARD_CKL=0 or INWARD_CKL>0 or
CHNG_CKL>0))))
or (type in ('R') and PON is not null) )

```

Numerator

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &SOUNPSP&
  AND &Exclusions
  AND STATUS in &STATUS&
  AND NVL(CISR_MAC,0) LIKE 'C%'
  AND CMPINTV>APPINTV
  and nvl(last_comac,1) <> 'EO'
  and company_mac_days > 0
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
  AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
  AND (
(ATC IN ('K','M','R','Y','W','X','C','S') AND ((TYPE IN ('N','T')) or
(TYPE in 'C' and (OUT_QTY=0 or INWARD_QTY>0 or
CHNG_QTY>0) and (OUTWARD_CKL=0 or INWARD_CKL>0 or
CHNG_CKL>0))))
or (type in ('R') and PON is not null) )

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPS&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPS&
      AND &RetailExclusions
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUS&
      AND NVL(CISR_MAC,0) LIKE 'C%'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0

```

UNE (Provisioning)

Report Labels: PR-4-05-3341

Complex Services - 2 Wire Digital

Parity with VZ Retail

Guidelines: PR-4 - Missed Appointments

% MA – VZ – No Dispatch

Result: (Numerator / Denominator) * 100**Denominator:**

Count of No Dispatch Orders Completed for product group.

Numerator:

Count of No Dispatch Orders where the Order completion date is greater than the order due date due to Bell Atlantic Reasons (CISR_MAC like 'C') for product group.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```
SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
AND &SOUNPI&
AND &Exclusions
AND STATUS in &STATUS&
AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
AND ATC in ('K','M','R','Y','W','X','C','S')
AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0 AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
```

Numerator

```
SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
AND &SOUNPI&
AND &Exclusions
AND STATUS in &STATUS&
AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
AND NVL(CISR_MAC,0) LIKE 'C%'
AND CMPINTV>APPINTV
and nvl(last_comac,1) <> 'EO'
and company_mac_days > 0
AND ATC in ('K','M','R','Y','W','X','C','S')
AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0 AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPI&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPI&
      AND &RetailExclusions
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUS&
      AND NVL(CISR_MAC,0) LIKE 'C%'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0

```

UNE (Provisioning)

Report Labels: PR-4-05-3342

Complex Services - 2 Wire xDSL

Parity with VZ Retail

Guidelines: PR-4 - Missed Appointments

% MA – VZ – No Dispatch

Result: (Numerator / Denominator) * 100**Denominator:**

Count of No Dispatch Orders Completed for product group.

Numerator:

Count of No Dispatch Orders where the Order completion date is greater than the order due date due to Bell Atlantic Reasons (CISR_MAC like 'C') for product group.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```
SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &SOUNPD&
  AND &Exclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
  AND ATC in ('K','M','R','Y','W','X','C','S')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0 AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
```

Numerator

```
SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &SOUNPD&
  AND &Exclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
  AND NVL(CISR_MAC,0) LIKE 'C%'
  AND CMPINTV>APPINTV
  and nvl(last_comac,1) <> 'EO'
  and company_mac_days > 0
  AND ATC in ('K','M','R','Y','W','X','C','S')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0 AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPD&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPD&
      AND &RetailExclusions
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND STATUS in &STATUS&
      AND NVL(CISR_MAC,0) LIKE 'C%'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0

```


UNE (Provisioning)

Report Labels:

PR-4-07-3540

POTS - Provisioning

95% On Time

Guidelines:

PR-4 - Missed Appointments

% On Time Performance - LNP

Result: (Numerator / Denominator) * 100

Denominator: Count of LNP orders completed. (Manual count)	Numerator: Count of LNP orders, where port trigger is completed before frame due time (as scheduled on order) and retail disconnect is completed on or after committed time frame. (manual count)
--	---

Filtered output file: LNP Filtered Data

For the details on the above out put filtered file layout refer to File Appendix: 5 File Type: Excel

Denominator	Numerator
<div>SELECT COUNT(DISTINCT TN) WHERE STATE = NJ AND ACT_DATE_NUM >= STARTDATE AND ACT_DATE_NUM <= ENDDATE</div>	<div>SELECT COUNT(DISTINCT TN) WHERE STATE = NJ AND MET_MISS = MET AND ACT_DATE_NUM >= STARTDATE AND ACT_DATE_NUM <= ENDDATE</div>

RESALE (PROVISIONING)

Report Labels: PR-4-08-2100

POTS - Provisioning - Total

No Standard

Guidelines: PR-4 - Missed Appointments

% Missed Appt. – Customer – Due to Late Order Confirmation

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Orders Completed for product group.

Numerator:

Count of Orders where the Order completion date is greater than the order due date due to Customer Reasons (for late Order Confirmation) for product group

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```
SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RSPS&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' ))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
```

```
SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RSPS&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' ))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND NVL(CISR_MAC,1) LIKE 'S%'
      AND CMPINTV>APPINTV
      and dcas_delay_foc = 'Y'
```

RESALE (PROVISIONING)

Report Labels: PR-4-08-2200

Special Services - Provisioning

No Standard

Guidelines: PR-4 - Missed Appointments

% Missed Appt. – Customer – Due to Late Order Confirmation

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Orders Completed for product group.

Numerator:

Count of Orders where the Order completion date is greater than the order due date due to Customer Reasons (for late Order Confirmation) for product group

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RSSS&
      AND &Exclusions&
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I'))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RSSS&
      AND &Exclusions&
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0
or INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0
or INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' ))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND NVL(CISR_MAC,1) LIKE 'S%'
      AND CMPINTV>APPINTV
and dcas_delay_foc = 'Y'

```

RESALE (PROVISIONING)

Report Labels: PR-4-08-2341

Complex Services - 2 Wire Digital

No Standard

Guidelines: PR-4 - Missed Appointment

% Missed Appt. – Customer – Due to Late Order Confirmation

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Orders Completed for product group.

Numerator:

Count of Orders where the Order completion date is greater than the order due date due to Customer Reasons (for late Order Confirmation) for product group

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RSPI&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' ))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RSPI&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' ))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND NVL(CISR_MAC,1) LIKE 'S%'
      AND CMPINTV>APPINTV
      and dcas_delay_foc = 'Y'

```

RESALE (PROVISIONING)

Report Labels: PR-4-08-2342

Complex Services - 2 Wire xDSL

No Standard

Guidelines: PR-4 - Missed Appointment

% Missed Appt. – Customer – Due to Late Order Confirmation

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Orders Completed for product group.

Numerator:

Count of Orders where the Order completion date is greater than the order due date due to Customer Reasons (for late Order Confirmation) for product group

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RSPI&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' ))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RSPD&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' ))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND NVL(CISR_MAC,1) LIKE 'S%'
      AND CMPINTV>APPINTV
      and dcas_delay_foc = 'Y'

```

UNE (Provisioning)

Report Labels: PR-4-08-3111 POTS - Provisioning No Standard

Guidelines: PR-4 - Missed Appointments

% MA – Customer – Due to Late Order Conf. - Hot Cut Loop

Result: (Numerator / Denominator) * 100

Denominator: Count of Orders Completed for product group.	Numerator: Count of Orders where the Order completion date is greater than the order due date due to Customer Reasons (for late Order Confirmation) for product group
---	---

Filtered output file: Service Order Record Data Layout
For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON

Denominator	Numerator
--------------------	------------------

UNE (Provisioning)

Report Labels: PR-4-08-3123

POTS - Provisioning

No Standard

Guidelines: PR-4 - Missed Appointments

% MA – Customer – Due to Late Order Conf. - Other than Platform & Hot Cut

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Orders Completed for product group.

Numerator:

Count of Orders where the Order completion date is greater than the order due date due to Customer Reasons (for late Order Confirmation) for product group

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &SOUNPSNPH&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &SOUNPSNPH&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND NVL(CISR_MAC,1) LIKE 'S%'
      AND CMPINTV>APPINTV
and dcas_delay_foc = 'Y'

```

UNE (Provisioning)

Report Labels: PR-4-08-3140 POTS - Provisioning No Standard

Guidelines: PR-4 - Missed Appointments

% MA – Customer – Due to Late Order Conf. - Platform

Result: (Numerator / Denominator) * 100	
Denominator:	Numerator:
Count of Orders Completed for product group.	Count of Orders where the Order completion date is greater than the order due date due to Customer Reasons (for late Order Confirmation) for product group

Filtered output file: Service Order Record Data Layout	
For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text	
Formula For:	VERIZON

Denominator Numerator

UNE (Provisioning)

Report Labels: PR-4-08-3200 Special Services Provisioning No Standard

Guidelines: PR-4 - Missed Appointments

% MA – Customer – Due to Late Order Confirmation - Specials

Result: (Numerator / Denominator) * 100

Denominator: Count of Orders Completed for product group.	Numerator: Count of Orders where the Order completion date is greater than the order due date due to Customer Reasons (for late Order Confirmation) for product group
---	---

Filtered output file: ASR-UNE-SPECIAL

For the details on the above out put filtered file layout refer to File Appendix: 7 File Type: Excel

Denominator

```
SELECT
COUNT(*)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND ACT IN ('N', 'C')
AND PRODUCT_TYPE IN ('DS1', 'DS3')
AND ASR_STATUS = C
```

Numerator

```
SELECT
COUNT(*)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND ACT IN ('N', 'C')
AND PRODUCT_TYPE IN ('DS1', 'DS3')
AND NVL(SUBSTR(WFA_MFC,1,1),'X') NOT IN ('C', 'D')
AND ASR_STATUS = C
AND CD > DD
AND LATE_FOC_YN = Y
```

UNE (Provisioning)

Report Labels: PR-4-08-3341

Complex Services - 2 Wire Digital

No Standard

Guidelines: PR-4 - Missed Appointments

% MA – Customer – Due to Late Order Confirmation

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Orders Completed for product group.

Numerator:

Count of Orders where the Order completion date is greater than the order due date due to Customer Reasons (for late Order Confirmation) for product group

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```
SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &SOUNPI&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
```

UNE (Provisioning)

Report Labels: PR-4-08-3342

Complex Services - 2 Wire xDSL

No Standard

Guidelines: PR-4 - Missed Appointments

% MA – Customer – Due to Late Order Confirmation

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Orders Completed for product group.

Numerator:

Count of Orders where the Order completion date is greater than the order due date due to Customer Reasons (for late Order Confirmation) for product group

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&STATE&'
      AND &SOUNDL&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

RESALE (PROVISIONING)

Report Labels: PR-4-09-2200

Special Services - Provisioning

Parity with VZ Retail

Guidelines: PR-4 - Missed Appointments

% Missed Appt. – VZ – Standard Interval (W Coded) Orders –Total

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Orders Completed for product group.

Numerator:

Count of Orders where the Order completion date is greater than the order due date due to Bell Atlantic Reasons (CISR_MAC like 'C*') for product group

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &RSSS&
  AND &Exclusions
  AND STATUS in &STATUS&
  AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' ))
  AND(ATC IN ('W')or(TYPE ='R' and RESELLER_ACT='I' ))
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Numerator

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &RSSS&
  AND &Exclusions
  AND STATUS in &STATUS&
  AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0
or INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0
or INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' ))
  AND NVL(CISR_MAC,0) LIKE 'C%'
  AND CMPINTV>APPINTV
  and nvl(last_comac,1) <> 'EO'
  and company_mac_days > 0
  AND (ATC IN ('W') or(TYPE ='R' and RESELLER_ACT='I' ))
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &RTSS&
  AND &RetailExclusions
  AND STATUS in &STATUS&
  AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
  AND ATC IN ('W')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Numerator

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &RTSS&
  AND &RetailExclusions
  AND STATUS in &STATUS&
  AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
  AND NVL(CISR_MAC,0) LIKE 'C%'
  AND CMPINTV>APPINTV
  and nvl(last_comac,1) <> 'EO'
  and company_mac_days > 0
  AND ATC IN ('W')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

UNE (Provisioning)

Report Labels: PR-4-09-3200 Special Services Provisioning No Standard

Guidelines: PR-4 - Missed Appointments

% MA – Verizon – Standard Interval (W Coded) Orders – Specials

Result: (Numerator / Denominator) * 100

Denominator: Count of Orders Completed for product group.	Numerator: Count of Orders where the Order completion date is greater than the order due date due to Bell Atlantic Reasons (CISR_MAC like 'C*') for product group
---	---

Filtered output file: ASR-UNE-SPECIAL

For the details on the above out put filtered file layout refer to File Appendix: 7 File Type: Excel

Denominator	Numerator
<div>SELECT COUNT(*) WHERE STATE = NJ AND ACTIVITY_DATE >= STARTDATE AND ACTIVITY_DATE <= ENDDATE AND ACT IN ('N', 'C') AND PRODUCT_TYPE IN ('DS1', 'DS3') AND ASR_STATUS = C AND W_CODED_YN = Y</div>	<div>SELECT COUNT(*) WHERE STATE = NJ AND ACTIVITY_DATE >= STARTDATE AND ACTIVITY_DATE <= ENDDATE AND ACT IN ('N', 'C') AND PRODUCT_TYPE IN ('DS1', 'DS3') AND NVL(SUBSTR(WFA_MFC,1,1),'X') NOT IN ('C', 'D') AND ASR_STATUS = C AND CD > DD AND W_CODED_YN = Y</div>

UNE (Provisioning)

Report Labels:

PR-4-09-3510

Special Services Provisioning

Parity with VZ Retail

Guidelines:

PR-4 - Missed Appointments

% MA – Verizon – Standard Interval (W Coded) Orders – EEL

Result: (Numerator / Denominator) * 100

Denominator: Count of Orders Completed for product group.	Numerator: Count of Orders where the Order completion date is greater than the order due date due to Bell Atlantic Reasons (CISR_MAC like 'C*') for product group
---	---

Filtered output file: ASR-UNE-SPECIAL

For the details on the above out put filtered file layout refer to File Appendix: 7 File Type: Excel

Denominator	Numerator
<div>SELECT COUNT(*) WHERE STATE = NJ AND ACTIVITY_DATE >= STARTDATE AND ACTIVITY_DATE <= ENDDATE AND ACT IN ('N', 'C') AND PRODUCT_TYPE IN ('EEL') AND ASR_STATUS = C AND W_CODED_YN = Y</div>	<div>SELECT COUNT(*) WHERE STATE = NJ AND ACTIVITY_DATE >= STARTDATE AND ACTIVITY_DATE <= ENDDATE AND ACT IN ('N', 'C') AND PRODUCT_TYPE IN ('EEL') AND NVL(SUBSTR(WFA_MFC,1,1),'X') NOT IN ('C', 'D') AND ASR_STATUS = C AND CD > DD AND W_CODED_YN = Y</div>

UNE (Provisioning)

Report Labels: PR-4-09-3530

Special Services Provisioning

Parity with VZ Retail

Guidelines: PR-4 - Missed Appointments

% MA – Verizon – Standard Interval (W Coded) Orders – IOF

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Orders Completed for product group.

Numerator:

Count of Orders where the Order completion date is greater than the order due date due to Bell Atlantic Reasons (CISR_MAC like 'C*') for product group

Filtered output file: ASR-UNE-SPECIAL

For the details on the above out put filtered file layout refer to File Appendix: 7

File Type: Excel

Denominator

```
SELECT
COUNT(*)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND ACT IN ('N', 'C')
AND PRODUCT_TYPE IN ('IOF')
AND ASR_STATUS = C
AND W_CODED_YN = Y
```

Numerator

```
SELECT
COUNT(*)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND ACT IN ('N', 'C')
AND PRODUCT_TYPE IN ('IOF')
AND NVL(SUBSTR(WFA_MFC,1,1),'X') NOT IN ('C', 'D')
AND ASR_STATUS = C
AND CD > DD
AND W_CODED_YN = Y
```

TRUNKS (Aggregate)

Report Labels: PR-4-09-5000

PROVISIONING

Parity with IXC / FGD

Guidelines: PR-4 - Missed Appointment

% MA – VZ – Std. Interval (W Coded) Orders –Total

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Orders Completed for product group.

Numerator:

Count of Orders where the Order completion date is greater than the order due date due to Bell Atlantic Reasons (CISR_MAC like 'C*') for product group

Filtered output file: Trunking Filter Data

For the details on the above out put filtered file layout refer to File Appendix: 4

File Type: Excel

Formula For: CLEC**Denominator**

```
SELECT
SUM(NO_WFA_TRUNKS)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND SERVICE_TYPE IN ('T', 'R')
AND ORDER_STATUS = C
AND CNR_YN = N
AND PROJECT_YN = N
AND NEW_OR_AUGMENT = A
AND ASR_TRUNK_SIZE <= 192
AND FORECAST_YN = Y
AND CREATE_CDDD_INTERVAL <= 18
```

Numerator

```
SELECT
SUM(NO_WFA_TRUNKS)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND SERVICE_TYPE IN ('T', 'R')
AND ORDER_STATUS = C
AND NVL(SUBSTR(WFA_MFC,1,1),'X') IN ('C', 'D')
AND WFA_DDCOMP > WFA_DDOBJ
AND CNR_YN = N
AND PROJECT_YN = N
AND NEW_OR_AUGMENT = A
AND ASR_TRUNK_SIZE <= 192
AND FORECAST_YN = Y
AND CREATE_CDDD_INTERVAL <= 18
```

Filtered output file: Trunking Filter Data

For the details on the above out put filtered file layout refer to File Appendix: 4

File Type: Excel

Formula For: VERIZON**Denominator**

```
SELECT
SUM(NO_WFA_TRUNKS)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND SERVICE_TYPE IN ('I', 'W')
AND ORDER_STATUS = C
AND CNR_YN = N
AND PROJECT_YN = N
AND NEW_OR_AUGMENT = A
AND ASR_TRUNK_SIZE <= 192
AND FORECAST_YN = Y
AND CREATE_CDDD_INTERVAL <= 18
```

Numerator

```
SELECT
SUM(NO_WFA_TRUNKS)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND SERVICE_TYPE IN ('I', 'W')
AND ORDER_STATUS = C
AND NVL(SUBSTR(WFA_MFC,1,1),'X') IN ('C', 'D')
AND WFA_DDCOMP > WFA_DDOBJ
AND CNR_YN = N
AND PROJECT_YN = N
AND NEW_OR_AUGMENT = A
AND ASR_TRUNK_SIZE <= 192
AND FORECAST_YN = Y
AND CREATE_CDDD_INTERVAL <= 18
```


RESALE (PROVISIONING)

Report Labels: PR-4-10-2100

POTS - Provisioning - Total

Parity with VZ Retail

Guidelines: PR-4 - Missed Appointments

% Missed Appt. – VZ – Standard Interval (W Coded) Orders – Dispatch

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Dispatched Orders Completed for product group.

Numerator:

Count of Dispatched Orders where the Order completion date is greater than the order due date due to Bell Atlantic Reasons (CISR_MAC like 'C*') for product group.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &RSPS&
  AND &Exclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' ))
  AND (ATC in ('W')or(TYPE ='R' and RESELLER_ACT='I' ))
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0

```

Numerator

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &RSPS&
  AND &Exclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' ))
  AND NVL(CISR_MAC,0) LIKE 'C%'
  AND CMPINTV>APPINTV
  and nvl(last_comac,1) <> 'EO'
  and company_mac_days > 0
  AND (ATC in ('W') or (TYPE ='R' and RESELLER_ACT='I' ))
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPS&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPS&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,0) LIKE 'C%'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0

```

RESALE (PROVISIONING)

Report Labels: PR-4-10-2341

Complex Services - 2 Wire Digital

Parity with VZ Retail

Guidelines: PR-4 - Missed Appointment

% Missed Appt. – VZ – Std. Int. (W Coded) Orders – Dispatch

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Dispatched Orders Completed for product group.

Numerator:

Count of Dispatched Orders where the Order completion date is greater than the order due date due to Bell Atlantic Reasons (CISR_MAC like 'C*') for product group.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &RSPI&
  AND &Exclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' ))
  AND (ATC in ('W')or(TYPE ='R' and RESELLER_ACT='I' ))
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &RSPI&
  AND &Exclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' ))
  AND NVL(CISR_MAC,0) LIKE 'C%'
  AND CMPINTV>APPINTV
  and nvl(last_comac,1) <> 'EO'
  and company_mac_days > 0
  AND (ATC in ('W') or (TYPE ='R' and RESELLER_ACT='I' ))
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPI&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPI&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,0) LIKE 'C%'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0

```

RESALE (PROVISIONING)

Report Labels: PR-4-10-2342

Complex Services - 2 Wire xDSL

Parity with VZ Retail

Guidelines: PR-4 - Missed Appointment

% Missed Appt. – VZ – Std. Int. (W Coded) Orders – Dispatch

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Dispatched Orders Completed for product group.

Numerator:

Count of Dispatched Orders where the Order completion date is greater than the order due date due to Bell Atlantic Reasons (CISR_MAC like 'C*') for product group.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &RSPD&
  AND &Exclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' ))
  AND (ATC in ('W')or(TYPE ='R' and RESELLER_ACT='I' ))
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &RSPD&
  AND &Exclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' ))
  AND NVL(CISR_MAC,0) LIKE 'C%'
  AND CMPINTV>APPINTV
  and nvl(last_comac,1) <> 'EO'
  and company_mac_days > 0
  AND (ATC in ('W') or (TYPE ='R' and RESELLER_ACT='I' ))
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPD&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPD&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,0) LIKE 'C%'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0

```

UNE (Provisioning)

Report Labels: PR-4-10-3113 POTS - Provisioning

Parity with VZ Retail

Guidelines: PR-4 - Missed Appointments

% MA – VZ – Std. Interval (W Coded) Orders – Disp. - Loop New

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Dispatched Orders Completed for product group.

Numerator:

Count of Dispatched Orders where the Order completion date is greater than the order due date due to Bell Atlantic Reasons (CISR_MAC like 'C*') for product group.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &SOUNPSLN&
  AND &Exclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
  AND ATC in ('W')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0

```

Numerator

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &SOUNPSLN&
  AND &Exclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
  AND NVL(CISR_MAC,0) LIKE 'C%'
  AND CMPINTV>APPINTV
  and nvl(last_comac,1) <> 'EO'
  and company_mac_days > 0
  AND ATC in ('W')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
  AND NVL(CLS,0) NOT IN ('DB2','DB5','MMS','MUZ','SU2','ZZO')
  AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &RTPS&
  AND &RetailExclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
  AND ATC in ('W')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0

```

Numerator

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &RTPS&
  AND &RetailExclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
  AND NVL(CISR_MAC,0) LIKE 'C%'
  AND CMPINTV>APPINTV
  and nvl(last_comac,1) <> 'EO'
  and company_mac_days > 0
  AND ATC in ('W')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
  AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0

```


UNE (Provisioning)

Report Labels: PR-4-10-3140 POTS - Provisioning

Parity with VZ Retail

Guidelines: PR-4 - Missed Appointments

% MA – VZ – Std. Interval (W Coded) Orders – Disp. - Platform

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Dispatched Orders Completed for product group.

Numerator:

Count of Dispatched Orders where the Order completion date is greater than the order due date due to Bell Atlantic Reasons (CISR_MAC like 'C**') for product group.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```
SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &SOUNPSP&
  AND &Exclusions
  AND STATUS in &STATUS&
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND SNPRES_IND IS NULL
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
  AND
  (
    (TYPE IN ('N','T') or (TYPE =
      AND (OUT_QTY=0 or INWARD_QTY>0
CHNG_QTY>0)
      AND (OUTWARD_CKL =
        OR INWARD_CKL > 0
        OR CHNG_CKL > 0)))
      AND ATC = 'W'
    OR
    (TYPE = 'R
      AND PON IS NOT NULL)
```

Numerator

```
SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &SOUNPSP&
  AND &Exclusions
  AND STATUS in &STATUS&
  AND NVL(CISR_MAC,0) LIKE 'C%'
  AND CMPINTV>APPINTV
  and nvl(last_comac,1) <> 'EO'
  and company_mac_days > 0
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
AND NVL(CLS,0) NOT IN ('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
  AND
  (
    (TYPE IN ('N','T') or (TYPE =
      AND (OUT_QTY=0 or INWARD_QTY>0
CHNG_QTY>0)
      AND (OUTWARD_CKL =
        OR INWARD_CKL > 0
        OR CHNG_CKL > 0)))
      AND ATC = 'W'
    OR
    (TYPE = 'R
      AND PON IS NOT NULL)
```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPS&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPS&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,0) LIKE 'C%'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0

```

UNE (Provisioning)

Report Labels: PR-4-10-3341

Complex Services - 2 Wire Digital

Parity with VZ Retail

Guidelines: PR-4 - Missed Appointments

% MA – VZ – Std. Interval (W Coded) Orders – Dispatch

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Dispatched Orders Completed for product group.

Numerator:

Count of Dispatched Orders where the Order completion date is greater than the order due date due to Bell Atlantic Reasons (CISR_MAC like 'C*') for product group.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &SOUNPI&
  AND &Exclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
  AND ATC in ('W')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Numerator

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &SOUNPI&
  AND &Exclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
  AND NVL(CISR_MAC,0) LIKE 'C%'
  AND CMPINTV>APPINTV
  and nvl(last_comac,1) <> 'EO'
  and company_mac_days > 0
  AND ATC in ('W')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &RTPI&
  AND &RetailExclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
  AND ATC in ('W')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
  AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0

```

Numerator

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &RTPI&
  AND &RetailExclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
  AND NVL(CISR_MAC,0) LIKE 'C%'
  AND CMPINTV>APPINTV
  and nvl(last_comac,1) <> 'EO'
  and company_mac_days > 0
  AND ATC in ('W')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
  AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0

```

UNE (Provisioning)

Report Labels: PR-4-10-3342

Complex Services - 2 Wire xDSL

Parity with VZ Retail

Guidelines: PR-4 - Missed Appointments

% MA – VZ – Std. Interval (W Coded) Orders – Dispatch

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Dispatched Orders Completed for product group.

Numerator:

Count of Dispatched Orders where the Order completion date is greater than the order due date due to Bell Atlantic Reasons (CISR_MAC like 'C*') for product group.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```
SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &SOUNPD&
  AND &Exclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
  AND ATC in ('W')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
```

Numerator

```
SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &SOUNPD&
  AND &Exclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
  AND NVL(CISR_MAC,0) LIKE 'C%'
  AND CMPINTV>APPINTV
  and nvl(last_comac,1) <> 'EO'
  and company_mac_days > 0
  AND ATC in ('W')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator**

```
SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &RTPD&
  AND &RetailExclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
  AND ATC in ('W')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
```

Numerator

```
SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &RTPD&
  AND &RetailExclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
  AND NVL(CISR_MAC,0) LIKE 'C%'
  AND CMPINTV>APPINTV
  and nvl(last_comac,1) <> 'EO'
  and company_mac_days > 0
  AND ATC in ('W')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
```

RESALE (PROVISIONING)

Report Labels: PR-4-11-2100

POTS - Provisioning - Total

Parity with VZ Retail

Guidelines: PR-4 - Missed Appointments

% Missed Appt. – VZ – Standard Interval (W Coded) Orders – No Dispatch

Result: (Numerator / Denominator) * 100**Denominator:**

Count of No Dispatch Orders Completed for product group.

Numerator:

Count of No Dispatch Orders where the Order completion date is greater than the order due date due to Bell Atlantic Reasons (CISR_MAC like 'C*') for product group.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &RSPS&
  AND &Exclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' ))
  AND (ATC in ('W')or (TYPE ='R' and RESELLER_ACT='I' ))
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &RSPS&
  AND &Exclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' ))
  AND NVL(CISR_MAC,0) LIKE 'C%'
  AND CMPINTV>APPINTV
  and nvl(last_comac,1) <> 'EO'
  and company_mac_days > 0
  AND (ATC in ('W') or (TYPE ='R' and RESELLER_ACT='I'
))
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPS&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPS&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,0) LIKE 'C%'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0

```

RESALE (PROVISIONING)

Report Labels: PR-4-11-2341

Complex Services - 2 Wire Digital

Parity with VZ Retail

Guidelines: PR-4 - Missed Appointment

% Missed Appt. – VZ – Std. Int. (W Coded) Orders – No Dispatch

Result: (Numerator / Denominator) * 100**Denominator:**

Count of No Dispatch Orders Completed for product group.

Numerator:

Count of No Dispatch Orders where the Order completion date is greater than the order due date due to Bell Atlantic Reasons (CISR_MAC like 'C*') for product group.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &RSPI&
  AND &Exclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' ))
  AND (ATC in ('W')or (TYPE ='R' and RESELLER_ACT='I' ))
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &RSPI&
  AND &Exclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' ))
  AND NVL(CISR_MAC,0) LIKE 'C%'
  AND CMPINTV>APPINTV
  and nvl(last_comac,1) <> 'EO'
  and company_mac_days > 0
  AND (ATC in ('W') or (TYPE ='R' and RESELLER_ACT='I'
))
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPI&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPI&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,0) LIKE 'C%'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0

```


RESALE (PROVISIONING)

Report Labels: PR-4-11-2342

Complex Services - 2 Wire xDSL

Parity with VZ Retail

Guidelines: PR-4 - Missed Appointment

% Missed Appt. – VZ – Std. Int. (W Coded) Orders – No Dispatch

Result: (Numerator / Denominator) * 100**Denominator:**

Count of No Dispatch Orders Completed for product group.

Numerator:

Count of No Dispatch Orders where the Order completion date is greater than the order due date due to Bell Atlantic Reasons (CISR_MAC like 'C') for product group.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```
SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &RSPD&
  AND &Exclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' ))
  AND (ATC in ('W')or (TYPE ='R' and RESELLER_ACT='I' ))
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
```

Numerator

```
SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &RSPD&
  AND &Exclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' ))
  AND NVL(CISR_MAC,0) LIKE 'C%'
  AND CMPINTV>APPINTV
  and nvl(last_comac,1) <> 'EO'
  and company_mac_days > 0
  AND (ATC in ('W') or (TYPE ='R' and RESELLER_ACT='I'
))
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
AND NVL(CLS,0) NOT IN ('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0
```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPD&
      AND &RetailExclusions&
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPD&
      AND &RetailExclusions&
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,0) LIKE 'C%'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0

```

UNE (Provisioning)

Report Labels: PR-4-11-3123 POTS - Provisioning

Parity with VZ Retail

Guidelines: PR-4 - Missed Appointments

% MA – VZ – Std. Interval (W Coded) Orders – No Disp. - Other than Platform & Hot Cut

Result: (Numerator / Denominator) * 100**Denominator:**

Count of No Dispatch Orders Completed for product group.

Numerator:

Count of No Dispatch Orders where the Order completion date is greater than the order due date due to Bell Atlantic Reasons (CISR_MAC like 'C*') for product group.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &SOUNPSNPH&
  AND &Exclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
  AND ATC in ('W')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0

```

Numerator

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &SOUNPSNPH&
  AND &Exclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
  AND NVL(CISR_MAC,0) LIKE 'C%'
  AND CMPINTV>APPINTV
  and nvl(last_comac,1) <> 'EO'
  and company_mac_days > 0
  AND ATC in ('W')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &RTPS&
  AND &RetailExclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
  AND ATC in ('W')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0

```

Numerator

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &RTPS&
  AND &RetailExclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
  AND NVL(CISR_MAC,0) LIKE 'C%'
  AND CMPINTV>APPINTV
  and nvl(last_comac,1) <> 'EO'
  and company_mac_days > 0
  AND ATC in ('W')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0

```


UNE (Provisioning)

Report Labels: PR-4-11-3140 POTS - Provisioning

Parity with VZ Retail

Guidelines: PR-4 - Missed Appointments

% MA – VZ – Std. Interval (W Coded) Orders – No Disp. - Platform

Result: (Numerator / Denominator) * 100**Denominator:**

Count of No Dispatch Orders Completed for product group.

Numerator:

Count of No Dispatch Orders where the Order completion date is greater than the order due date due to Bell Atlantic Reasons (CISR_MAC like 'C') for product group.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```
SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &SOUNPSP&
  AND &Exclusions
  AND STATUS in &STATUS&
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_NUM_DO)=0
  AND (
(ATC IN ('W') AND ((TYPE IN ('N','T')) or (TYPE in 'C' and
(OUT_QTY=0 or INWARD_QTY>0 or CHNG_QTY>0) and
(OUTWARD_CKL=0 or INWARD_CKL>0 or CHNG_CKL>0))))
or (type in ('R') and PON is not null) )
```

Numerator

```
SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &SOUNPSP&
  AND &Exclusions
  AND STATUS in &STATUS&
  AND NVL(CISR_MAC,0) LIKE 'C%'
  AND CMPINTV>APPINTV
  and nvl(last_comac,1) <> 'EO'
  and company_mac_days > 0
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_NUM_DO)=0
  AND (
(ATC IN ('W') AND ((TYPE IN ('N','T')) or (TYPE in 'C' and
(OUT_QTY=0 or INWARD_QTY>0 or CHNG_QTY>0) and
(OUTWARD_CKL=0 or INWARD_CKL>0 or CHNG_CKL>0))))
or (type in ('R') and PON is not null) )
```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPS&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPS&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,0) LIKE 'C%'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0

```

UNE (Provisioning)

Report Labels: PR-4-11-3341

Complex Services - 2 Wire Digital

Parity with VZ Retail

Guidelines: PR-4 - Missed Appointments

% MA – VZ – Std. Interval (W Coded) Orders – No Dispatch

Result: (Numerator / Denominator) * 100**Denominator:**

Count of No Dispatch Orders Completed for product group.

Numerator:

Count of No Dispatch Orders where the Order completion date is greater than the order due date due to Bell Atlantic Reasons (CISR_MAC like 'C') for product group.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &SOUNPI&
  AND &Exclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
  AND ATC in ('W')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0 AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0

```

Numerator

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &SOUNPI&
  AND &Exclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
  AND NVL(CISR_MAC,0) LIKE 'C%'
  AND CMPINTV>APPINTV
  and nvl(last_comac,1) <> 'EO'
  and company_mac_days > 0
  AND ATC in ('W')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0 AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPI&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPI&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,0) LIKE 'C%'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0

```


UNE (Provisioning)

Report Labels: PR-4-11-3342

Complex Services - 2 Wire xDSL

Parity with VZ Retail

Guidelines: PR-4 - Missed Appointments

% MA – VZ – Std. Interval (W Coded) Orders – No Dispatch

Result: (Numerator / Denominator) * 100**Denominator:**

Count of No Dispatch Orders Completed for product group.

Numerator:

Count of No Dispatch Orders where the Order completion date is greater than the order due date due to Bell Atlantic Reasons (CISR_MAC like 'C') for product group.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &SOUNPD&
  AND &Exclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
  AND ATC in ('W')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0 AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0

```

Numerator

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
  AND &SOUNPD&
  AND &Exclusions
  AND STATUS in &STATUS&
  AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
  AND NVL(CISR_MAC,0) LIKE 'C%'
  AND CMPINTV>APPINTV
  and nvl(last_comac,1) <> 'EO'
  and company_mac_days > 0
  AND ATC in ('W')
  AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
  AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
  AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0 AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPD&
      AND &RetailExclusions&
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPD&
      AND &RetailExclusions&
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND NVL(CISR_MAC,0) LIKE 'C%'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC IN ('W')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)=0

```

UNE (Provisioning)

Report Labels: PR-4-14-3342

Complex Services - 2 Wire xDSL

95% on Time

Guidelines: PR-4 - Missed Appointments

% Completed On Time - With DD-2 Test Rslts, with 800 #& Serial#

Result: (Numerator / Denominator) * 100**Denominator:**

UNE: Count of completed orders with DD-2 test results, with 800 number, and with CLEC serial number. Retail: Count of completed orders.

Numerator:

UNE: Count of all orders completed on or before the due date with DD-2 test results, with 800 number, and with CLEC serial number. Retail: Count of all orders completed on or before the due date.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```
SELECT
count(order_num)
WHERE STATE = '&STATE&'
      AND STATUS in &STATUS&
      AND &SOUNDL&
      AND &Exclusions
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC in ('M','W','X','E','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
```

```
SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&STATE&'
      AND STATUS in &STATUS&
      AND &SOUNDL&
      AND &Exclusions
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND CMP<=DU
      AND ATC in ('M','W','X','E','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```
SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTPR&
      AND &RetailExclusions
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC in ('M','W','X','E','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND IN_FACIL>
      AND ADL = 'Y'
```

```
SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND STATUS in &STATUS&
      AND &RTPR&
      AND &RetailExclusions
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND CMP<=DU
      AND ATC in ('M','W','X','E','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND IN_FACIL>
      AND ADL = 'Y'
```

UNE (Provisioning)

Report Labels: PR-4-15-3342 Complex Services - 2 Wire xDSL 95% on Time

Guidelines: PR-4 - Missed Appointments

% Completed On Time - With DD-2 Test Rslts, with 800 # & with/without Serial #

Result: (Numerator / Denominator) * 100

Denominator:
Count of all orders completed on or before the due date with DD-2 test results, with 800 number, and with or without CLEC serial number.

Numerator:
Count of all orders completed on or before the due date with DD-2 test results, with 800 number, and with or without CLEC serial number.

Filtered output file: PR-14-18 NJ -Individual States by AREA Prompt

For the details on the above out put filtered file layout refer to File Appendix: 58 File Type: Access DB (P)

Formula For: VERIZON

Denominator

Numerator

UNE (Provisioning)

Report Labels: PR-4-16-3342 Complex Services - 2 Wire xDSL

95% on Time

Guidelines: PR-4 - Missed Appointments

% Completed On Time - Without DD-2 Test,with 800 # & Serial #

Result: (Numerator / Denominator) * 100**Denominator:**

Count of completed orders without DD-2 test results, with 800 number, and with CLEC serial number.

Numerator:

Count of all orders completed on or before the due date without DD-2 test results, with 800 number, and with CLEC serial number.

Filtered output file: PR-14-18 NJ -Individual States by AREA Prompt

For the details on the above out put filtered file layout refer to File Appendix: 58 File Type: Access DB (P

Formula For: CLEC**Denominator****Numerator**

```
SELECT
SUM(CMP - LATE CUST)
WHERE STATE = NJ
AND TESTING = TRUE
```

```
SELECT
sum(on time)
WHERE STATE = NJ
AND TESTING = TRUE
```

Filtered output file: PR-14-18 NJ -Individual States by AREA Prompt

For the details on the above out put filtered file layout refer to File Appendix: 58 File Type: Access DB (P

Formula For: VERIZON**Denominator****Numerator**

```
SELECT
SUM(CMP - LATE CUST)
WHERE STATE = NJ
AND TESTING = TRUE
```

```
SELECT
sum(on time)
WHERE STATE = NJ
AND TESTING = TRUE
```

UNE (Provisioning)

Report Labels: PR-4-17-3342

Complex Services - 2 Wire xDSL

95% on Time

Guidelines: PR-4 - Missed Appointments

% Completed On Time - Without DD-2 Test Rslts, with 800 # & with/without Serial #

Result: (Numerator / Denominator) * 100**Denominator:**

Count of completed orders without DD-2 test results, with 800 number, and with or without CLEC serial number.

Numerator:

Count of all orders completed on or before the due date without DD-2 test results, with 800 number, and with or without CLEC serial number.

Filtered output file: PR-14-18 NJ -Individual States by AREA Prompt

For the details on the above out put filtered file layout refer to File Appendix: 58 File Type: Access DB (P

Formula For: CLEC**Denominator****Numerator**

```
SELECT
SUM(CMP - LATE CUST)
WHERE TESTING = TRUE
AND STATE = NJ
```

```
SELECT
sum(on time)
WHERE TESTING = TRUE
AND STATE = NJ
```

Filtered output file: PR-14-18 NJ -Individual States by AREA Prompt

For the details on the above out put filtered file layout refer to File Appendix: 58 File Type: Access DB (P

Formula For: VERIZON**Denominator****Numerator**

```
SELECT
SUM(CMP - LATE CUST)
WHERE STATE = NJ
AND TESTING = TRUE
```

```
SELECT
sum(on time)
WHERE STATE = NJ
AND TESTING = TRUE
```

UNE (Provisioning)

Report Labels: PR-4-18-3342 Complex Services - 2 Wire xDSL 95% on Time

Guidelines: PR-4 - Missed Appointments

% Completed On Time - Without DD-2 Test Rslts, without 800 # & without Serial #

Result: (Numerator / Denominator) * 100

Denominator: Count of completed orders without DD-2 test results, without 800 number, and without CLEC serial number.	Numerator: Count of all orders completed on or before the due date without DD-2 test results, without 800 number, and without CLEC serial number.
---	---

Filtered output file: PR-14-18 NJ -Individual States by AREA Prompt
For the details on the above out put filtered file layout refer to File Appendix: 58 File Type: Access DB (P)

Formula For: VERIZON

Denominator	Numerator
--------------------	------------------

Guidelines For: PR-5 Facility Missed Orders

C2C Guideline:	
Definition:	% Facility Miss: The percentage of orders completed after the commitment date, where the cause of the delay is lack of BA facilities. % Facility Orders > 15 or 60 Days: The percentage of orders missed for lack of BA facilities where the completion date minus the appointment date is greater than 15 or 60 calendar days. Trunks: The percentage of trunks completed after the commitment date, where the cause of the delay is lack of BA facilities.
Performance Standard:	Parity with BA Retail.
Exclusions:	BA Test Orders , Disconnect Orders, Bell Atlantic Administrative orders , Additional Segments on orders (parts of a whole order are included in the whole), Orders that are not complete. (Orders are included in the month that they are complete), Suspend for non-payment and associated restore orders.
Report Dimensions:	BA Retail, CLEC Aggregate, CLEC Specific, BA Affiliate Aggregate, BA Affiliate Specific
Geography:	POTS, 2 Wire Digital Services, and 2 Wire xDSL Services: Southern, Eastern Shore, Raritan, Suburban, Hudson-Bergen Specials: State Trunks: State

RESALE (PROVISIONING)

Report Labels:

PR-5-01-2100

POTS - Provisioning - Total

Parity with VZ Retail

Guidelines:

PR-5 - Facility Missed Orders

% Missed Appointment – Verizon – Facilities

Result: (Numerator / Denominator) * 100

Denominator: Count of Orders Completed for product group.	Numerator: Count of Orders where the Order completion date is greater than the order due date due to Bell Atlantic Facility Reasons for product group.
---	--

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC

Denominator	Numerator
--------------------	------------------

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON

Denominator	Numerator
--------------------	------------------

RESALE (PROVISIONING)

Report Labels: PR-5-01-2200 Special Services - Provisioning

Parity with VZ Retail

Guidelines: PR-5- Facility Missed Orders

% Missed Appointment – Verizon – Facilities

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Orders Completed for product group.

Numerator:

Count of Orders where the Order completion date is greater than the order due date due to Bell Atlantic Facility Reasons for product group.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RSPS&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE = 'R' and
RESELLER_ACT='I' ))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RSSS&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0
or INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0
or INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE = 'R' and
RESELLER_ACT='I' ))
      AND CISR_MAC = 'CF'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RTSS&
      AND &RetailExclusions&
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RTPS&
      AND &RetailExclusions&
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND CISR_MAC = 'CF'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

RESALE (PROVISIONING)

Report Labels: PR-5-01-2341

Complex Services - 2 Wire Digital

Parity with VZ Retail

Guidelines: PR-5 - Facility Missed Orders

% Missed Appointment – Verizon – Facilities

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Orders Completed for product group.

Numerator:

Count of Orders where the Order completion date is greater than the order due date due to Bell Atlantic Facility Reasons for product group.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RSPI&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE = 'R' and
RESELLER_ACT='I' ))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Numerator

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RSPI&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE = 'R' and
RESELLER_ACT='I' ))
      AND CISR_MAC = 'CF'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPI&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND CISR_MAC = 'CF'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

RESALE (PROVISIONING)

Report Labels: PR-5-01-2342 Complex Services - 2 Wire xDSL

Parity with VZ Retail

Guidelines: PR-5 - Facility Missed Orders

% Missed Appointment – Verizon – Facilities

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Orders Completed for product group.

Numerator:

Count of Orders where the Order completion date is greater than the order due date due to Bell Atlantic Facility Reasons for product group.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RSPD&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE = 'R' and
RESELLER_ACT='I' ))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RSPD&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE = 'R' and
RESELLER_ACT='I' ))
      AND CISR_MAC = 'CF'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RSPD&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE = 'R' and
RESELLER_ACT='I' ))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPD&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND CISR_MAC = 'CF'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

UNE (Provisioning)

Report Labels: PR-5-01-3112 POTS - Provisioning

Parity with VZ Retail

Guidelines: PR-5- Facility Missed Orders

% Missed Appointment – Verizon – Facilities - Loop

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Orders Completed for product group.

Numerator:

Count of Orders where the Order completion date is greater than the order due date due to Bell Atlantic Facility Reasons for product group.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```
SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &SOUNPSL&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
```

Numerator

```
SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &SOUNPSL&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND CISR_MAC = 'CF'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

UNE (Provisioning)

Report Labels: PR-5-01-3140 POTS - Provisioning

Parity with VZ Retail

Guidelines: PR-5- Facility Missed Orders

% Missed Appointment – Verizon – Facilities - Platform

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Orders Completed for product group.

Numerator:

Count of Orders where the Order completion date is greater than the order due date due to Bell Atlantic Facility Reasons for product group.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &SOUNPSP&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (
(ATC IN ('K','M','R','Y','W','X','C','S') AND ((TYPE IN ('N','T')) or
(TYPE in 'C' and (OUT_QTY=0 or INWARD_QTY>0 or
CHNG_QTY>0) and (OUTWARD_CKL=0 or INWARD_CKL>0 or
CHNG_CKL>0))))
or (type in ('R') and PON is not null ) )

```

Numerator

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &SOUNPSP&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND CISR_MAC = 'CF'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,'*'),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (
(ATC IN ('K','M','R','Y','W','X','C','S') AND ((TYPE IN ('N','T')) or
(TYPE in 'C' and (OUT_QTY=0 or INWARD_QTY>0 or
CHNG_QTY>0) and (OUTWARD_CKL=0 or INWARD_CKL>0 or
CHNG_CKL>0))))
or (type in ('R') and PON is not null ) )

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

UNE (Provisioning)

Report Labels: PR-5-01-3200 Special Services Provisioning Parity with VZ Retail

Guidelines: PR 5 - % Missed Appointment – Verizon – Facilities
% Missed Appointment – Verizon – Facilities

Result: (Numerator / Denominator) * 100

Denominator: Count of Orders Completed for product group.	Numerator: Count of Orders where the Order completion date is greater than the order due date due to Bell Atlantic Facility Reasons for product group.
---	--

Filtered output file: ASR-UNE-SPECIAL
For the details on the above out put filtered file layout refer to File Appendix: 7 File Type: Excel

Denominator Numerator

SELECT
COUNT(*)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND ACT IN ('N', 'C')
AND PRODUCT_TYPE IN ('DS1', 'DS3')
AND ASR_STATUS = C

SELECT
COUNT(*)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND ACT IN ('N', 'C')
AND PRODUCT_TYPE IN ('DS1', 'DS3')
AND CD > DD
AND NVL(SUBSTR(WFA_MFC,1,1),'X') IN ('G', 'H')
AND ASR_STATUS = C

UNE (Provisioning)

Report Labels: PR-5-01-3341

Complex Services - 2 Wire Digital

Parity with VZ Retail

Guidelines: PR-5 - Facility Missed Orders

% Missed Appointment – Verizon – Facilities

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Orders Completed for product group.

Numerator:

Count of Orders where the Order completion date is greater than the order due date due to Bell Atlantic Facility Reasons for product group.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &SOUNPI&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC in ('K','M','R','Y','W','X','C','S')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Numerator

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &SOUNPI&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND CISR_MAC = 'CF'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC in ('K','M','R','Y','W','X','C','S')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPI&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND CISR_MAC = 'CF'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```


UNE (Provisioning)

Report Labels: PR-5-01-3342

Complex Services - 2 Wire xDSL

Parity with VZ Retail

Guidelines: PR-5 - Facility Missed Orders

% Missed Appointment – Verizon – Facilities

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Orders Completed for product group.

Numerator:

Count of Orders where the Order completion date is greater than the order due date due to Bell Atlantic Facility Reasons for product group.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```
SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &SOUNPD&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
```

Numerator

```
SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &SOUNPD&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND CISR_MAC = 'CF'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator**

```
SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &SOUNPD&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
```

Numerator

```
SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPD&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND CISR_MAC = 'CF'
      AND CMPINTV>APPINTV
      and nvl(last_comac,1) <> 'EO'
      and company_mac_days > 0
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
```

TRUNKS (Aggregate)

Report Labels: PR-5-01-5000

PROVISIONING

Parity with IXC / FGD

Guidelines: PR-5 - Facility Missed Orders

% Missed Appointment – Verizon – Facilities

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Orders Completed for product group.

Numerator:

Count of Orders where the Order completion date is greater than the order due date due to Bell Atlantic Facility Reasons for product group.

Filtered output file: Trunking Filter Data

For the details on the above out put filtered file layout refer to File Appendix: 4 File Type: Excel

Formula For: CLEC**Denominator**

```
SELECT
SUM(NO_WFA_TRUNKS)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND SERVICE_TYPE = T
AND ORDER_STATUS = C
```

Numerator

```
SELECT
SUM(NO_WFA_TRUNKS)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND SERVICE_TYPE = T
AND ORDER_STATUS = C
AND NVL(SUBSTR(WFA_MFC,1,1),'X') = H
AND WFA_COMPLETED_INTERVAL >
WFA_OFFERED_INTERVAL
```

Filtered output file: Trunking Filter Data

For the details on the above out put filtered file layout refer to File Appendix: 4 File Type: Excel

Formula For: VERIZON**Denominator**

```
SELECT
SUM(NO_WFA_TRUNKS)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND SERVICE_TYPE IN ('I', 'W')
AND ORDER_STATUS = C
```

Numerator

```
SELECT
SUM(NO_WFA_TRUNKS)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND SERVICE_TYPE IN ('I', 'W')
AND ORDER_STATUS = C
AND NVL(SUBSTR(WFA_MFC,1,1),'X') = H
AND WFA_COMPLETED_INTERVAL >
WFA_OFFERED_INTERVAL
```

RESALE (PROVISIONING)

Report Labels: PR-5-02-2100 POTS - Provisioning - Total

Parity with VZ Retail

Guidelines: PR-5 - Facility Missed Orders

% Orders Held for Facilities > 15 Days

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Orders Completed for product group.

Numerator:

Count of Orders where the completion date less due date is more than 15 days for Bell Atlantic Facility Reasons for product group.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RSPS&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE = 'R' and
RESELLER_ACT='I' ))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RSPS&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE = 'R' and
RESELLER_ACT='I' ))
      AND CISR_MAC = 'CF'
      AND (company_mac_days) > 15
      AND CMPINTV - APPINTV > 1
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RSPS&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE = 'R' and
RESELLER_ACT='I' ))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

RESALE (PROVISIONING)

Report Labels: PR-5-02-2200 Special Services - Provisioning

Parity with VZ Retail

Guidelines: PR-5- Facility Missed Orders

% Orders Held for Facilities > 15 Days

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Orders Completed for product group.

Numerator:

Count of Orders where the completion date less due date is more than 15 days for Bell Atlantic Facility Reasons for product group.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RSSS&
      AND &Exclusions&
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE =R' and
RESELLER_ACT='I'))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Numerator

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RSSS&
      AND &Exclusions&
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0
or INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0
or INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE =R' and
RESELLER_ACT='I' ))
      AND CISR_MAC = 'CF'
      AND (company_mac_days) > 15
      AND CMPINTV - APPINTV > 1
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RSSS&
      AND &Exclusions&
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE =R' and
RESELLER_ACT='I'))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Numerator

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTSS&
      AND &RetailExclusions&
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND CISR_MAC = 'CF'
      AND (company_mac_days) > 15
      AND CMPINTV - APPINTV > 1
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

RESALE (PROVISIONING)

Report Labels: PR-5-02-2341

Complex Services - 2 Wire Digital

Parity with VZ Retail

Guidelines: PR-5 - Facility Missed Orders

% Orders Held for Facilities > 15 Days

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Orders Completed for product group.

Numerator:

Count of Orders where the completion date less due date is more than 15 days for Bell Atlantic Facility Reasons for product group.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RSPI&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE = 'R' and
RESELLER_ACT='I' ))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RSPI&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE = 'R' and
RESELLER_ACT='I' ))
      AND CISR_MAC = 'CF'
      AND (company_mac_days) > 15
      AND CMPINTV - APPINTV > 1
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RTPI&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPI&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND CISR_MAC = 'CF'
      AND (company_mac_days) > 15
      AND CMPINTV - APPINTV > 1
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

RESALE (PROVISIONING)

Report Labels: PR-5-02-2342

Complex Services - 2 Wire xDSL

Parity with VZ Retail

Guidelines: PR-5 - Facility Missed Orders

% Orders Held for Facilities > 15 Days

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Orders Completed for product group.

Numerator:

Count of Orders where the completion date less due date is more than 15 days for Bell Atlantic Facility Reasons for product group.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RTPD&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Numerator

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RSPD&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' ))
      AND CISR_MAC = 'CF'
      AND (company_mac_days) > 15
      AND CMPINTV - APPINTV > 1
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RTPD&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Numerator

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPD&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND CISR_MAC = 'CF'
      AND (company_mac_days) > 15
      AND CMPINTV - APPINTV > 1
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

UNE (Provisioning)

Report Labels: PR-5-02-3112 POTS - Provisioning

Parity with VZ Retail

Guidelines: PR-5- Facility Missed Orders

% Orders Held for Facilities > 15 Days - Loop

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Orders Completed for product group.

Numerator:

Count of Orders where the completion date less due date is more than 15 days for Bell Atlantic Facility Reasons for product group.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```
SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &SOUNPSP&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
```

Numerator

```
SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &SOUNPSL&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND CISR_MAC = 'CF'
      AND (company_mac_days) > 15
      AND CMPINTV - APPINTV > 1
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

UNE (Provisioning)

Report Labels: PR-5-02-3140 POTS - Provisioning

Parity with VZ Retail

Guidelines: PR-5- Facility Missed Orders

% Orders Held for Facilities > 15 Days - Platform

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Orders Completed for product group.

Numerator:

Count of Orders where the completion date less due date is more than 15 days for Bell Atlantic Facility Reasons for product group.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &SOUNPSP&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (
(ATC IN ('K','M','R','Y','W','X','C','S') AND ((TYPE IN ('N','T')) or
(TYPE in 'C' and (OUT_QTY=0 or INWARD_QTY>0 or
CHNG_QTY>0) and (OUTWARD_CKL=0 or INWARD_CKL>0 or
CHNG_CKL>0))))
or (type in ('R') and PON is not null ) )

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &SOUNPSP&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND CISR_MAC = 'CF'
      AND (company_mac_days) > 15
      AND CMPINTV - APPINTV > 1
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (
(ATC IN ('K','M','R','Y','W','X','C','S') AND ((TYPE IN ('N','T')) or
(TYPE in 'C' and (OUT_QTY=0 or INWARD_QTY>0 or
CHNG_QTY>0) and (OUTWARD_CKL=0 or INWARD_CKL>0 or
CHNG_CKL>0))))
or (type in ('R') and PON is not null ) )

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RTPS&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```


UNE (Provisioning)

Report Labels: PR-5-02-3200 Special Services Provisioning Parity with VZ Retail

Guidelines: PR 5 - % Missed Appointment – Verizon – Facilities

% Orders Held for Facilities > 15 Days

Result: (Numerator / Denominator) * 100

Denominator: Count of Orders Completed for product group.	Numerator: Count of Orders where the completion date less due date is more than 15 days for Bell Atlantic Facility Reasons for product group.
---	---

Filtered output file: ASR-UNE-SPECIAL

For the details on the above out put filtered file layout refer to File Appendix: 7 File Type: Excel

Denominator Numerator

SELECT
COUNT(*)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND ACT IN ('N', 'C')
AND PRODUCT_TYPE IN ('DS1', 'DS3')
AND ASR_STATUS = C

SELECT
COUNT(*)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND ACT IN ('N', 'C')
AND PRODUCT_TYPE IN ('DS1', 'DS3')
AND CD > DD + 15
AND NVL(SUBSTR(WFA_MFC,1,1),'X') IN ('G', 'H')
AND ASR_STATUS = C

UNE (Provisioning)

Report Labels: PR-5-02-3341

Complex Services - 2 Wire Digital

Parity with VZ Retail

Guidelines: PR-5 - Facility Missed Orders

% Orders Held for Facilities > 15 Days

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Orders Completed for product group.

Numerator:

Count of Orders where the completion date less due date is more than 15 days for Bell Atlantic Facility Reasons for product group.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```
SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &SOUNPI&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
```

Numerator

```
SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &SOUNPI&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND CISR_MAC = 'CF'
      AND (company_mac_days) > 15
      AND CMPINTV - APPINTV > 1
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
      decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator**

```
SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RTPI&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
```

Numerator

```
SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPI&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND CISR_MAC = 'CF'
      AND (company_mac_days) > 15
      AND CMPINTV - APPINTV > 1
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
```

UNE (Provisioning)

Report Labels: PR-5-02-3342

Complex Services - 2 Wire xDSL

Parity with VZ Retail

Guidelines: PR-5 - Facility Missed Orders

% Orders Held for Facilities > 15 Days

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Orders Completed for product group.

Numerator:

Count of Orders where the completion date less due date is more than 15 days for Bell Atlantic Facility Reasons for product group.

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &SOUNPD&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,*),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RTPD&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,*),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPD&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND CISR_MAC = 'CF'
      AND (company_mac_days) > 15
      AND CMPINTV - APPINTV > 1
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,*),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

TRUNKS (Aggregate)

Report Labels: PR-5-02-5000

PROVISIONING

Parity with IXC / FGD

Guidelines: PR-5 - Facility Missed Orders

% Orders Held for Facilities > 15 Days

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Orders Completed for product group.

Numerator:

Count of Orders where the completion date less due date is more than 15 days for Bell Atlantic Facility Reasons for product group.

Filtered output file: Trunking Filter Data

For the details on the above out put filtered file layout refer to File Appendix: 4 File Type: Excel

Formula For: CLEC**Denominator**

```
SELECT
SUM(NO_WFA_TRUNKS)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND SERVICE_TYPE = T
AND ORDER_STATUS = C
```

Numerator

```
SELECT
SUM(NO_WFA_TRUNKS)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND SERVICE_TYPE = T
AND ORDER_STATUS = C
AND NVL(SUBSTR(WFA_MFC,1,1),'X') = H
AND WFA_COMPLETED_INTERVAL >
WFA_OFFERED_INTERVAL + 15
```

Filtered output file: Trunking Filter Data

For the details on the above out put filtered file layout refer to File Appendix: 4 File Type: Excel

Formula For: VERIZON**Denominator**

```
SELECT
SUM(NO_WFA_TRUNKS)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND SERVICE_TYPE IN ('I', 'W')
AND ORDER_STATUS = C
```

Numerator

```
SELECT
SUM(NO_WFA_TRUNKS)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND SERVICE_TYPE IN ('I', 'W')
AND ORDER_STATUS = C
AND NVL(SUBSTR(WFA_MFC,1,1),'X') = H
AND WFA_COMPLETED_INTERVAL >
WFA_OFFERED_INTERVAL + 15
```

RESALE (PROVISIONING)

Report Labels: PR-5-03-2100 POTS - Provisioning - Total

Parity with VZ Retail

Guidelines: PR-5 - Facility Missed Orders

% Orders Held for Facilities > 60 Days

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Orders Completed for product group.

Numerator:

Count of Orders where the completion date less due date is more than 60 days for Bell Atlantic Facility Reasons for product group

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RSPS&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE = 'R' and
RESELLER_ACT='I' ))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RSPS&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE = 'R' and
RESELLER_ACT='I' ))
      AND CISR_MAC = 'CF'
      AND (company_mac_days) > 60
      AND CMPINTV - APPINTV > 6
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RTPS&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPS&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND CISR_MAC = 'CF'
      AND (company_mac_days) > 60
      AND CMPINTV - APPINTV > 6
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

RESALE (PROVISIONING)

Report Labels: PR-5-03-2200 Special Services - Provisioning

Parity with VZ Retail

Guidelines: PR-5- Facility Missed Orders

% Orders Held for Facilities > 60 Days

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Orders Completed for product group.

Numerator:

Count of Orders where the completion date less due date is more than 60 days for Bell Atlantic Facility Reasons for product group

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RSSS&
      AND &Exclusions&
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE = 'R' and
RESELLER_ACT='I'))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Numerator

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RSSS&
      AND &Exclusions&
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 o
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE = 'R' and
RESELLER_ACT='I' ))
      AND CISR_MAC = 'CF'
      AND (company_mac_days) > 60
      AND CMPINTV - APPINTV > 6
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RTSS&
      AND &RetailExclusions&
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Numerator

RESALE (PROVISIONING)

Report Labels: PR-5-03-2341

Complex Services - 2 Wire Digital

Parity with VZ Retail

Guidelines: PR-5 - Facility Missed Orders

% Orders Held for Facilities > 60 Days

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Orders Completed for product group.

Numerator:

Count of Orders where the completion date less due date is more than 60 days for Bell Atlantic Facility Reasons for product group

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RSPI&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE = 'R' and
RESELLER_ACT='I' ))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Numerator

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RSPI&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE = 'R' and
RESELLER_ACT='I' ))
      AND CISR_MAC = 'CF'
      AND (company_mac_days) > 60
      AND CMPINTV - APPINTV > 6
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RTPI&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Numerator

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPI&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND CISR_MAC = 'CF'
      AND (company_mac_days) > 60
      AND CMPINTV - APPINTV > 6
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

RESALE (PROVISIONING)

Report Labels: PR-5-03-2342

Complex Services - 2 Wire xDSL

Parity with VZ Retail

Guidelines: PR-5 - Facility Missed Orders

% Orders Held for Facilities > 60 Days

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Orders Completed for product group.

Numerator:

Count of Orders where the completion date less due date is more than 60 days for Bell Atlantic Facility Reasons for product group

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```
SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RSPD&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE = 'R' and
RESELLER_ACT='I' ))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
```

Numerator

```
SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RSPD&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE = 'R' and
RESELLER_ACT='I' ))
      AND CISR_MAC = 'CF'
      AND (company_mac_days) > 60
      AND CMPINTV - APPINTV > 6
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator**

```
SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RTPD&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
```

Numerator

```
SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPD&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND CISR_MAC = 'CF'
      AND (company_mac_days) > 60
      AND CMPINTV - APPINTV > 6
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
```


UNE (Provisioning)

Report Labels: PR-5-03-3112 POTS - Provisioning

Parity with VZ Retail

Guidelines: PR-5- Facility Missed Orders

% Orders Held for Facilities > 60 Days - Loop

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Orders Completed for product group.

Numerator:

Count of Orders where the completion date less due date is more than 60 days for Bell Atlantic Facility Reasons for product group

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &SOUNPSL&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,*),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Numerator

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &SOUNPSL&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND CISR_MAC = 'CF'
      AND (company_mac_days) > 60
      AND CMPINTV - APPINTV > 6
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,*),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RTPS&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,*),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Numerator

UNE (Provisioning)

Report Labels: PR-5-03-3140 POTS - Provisioning

Parity with VZ Retail

Guidelines: PR-5- Facility Missed Orders

% Orders Held for Facilities > 60 Days - Platform

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Orders Completed for product group.

Numerator:

Count of Orders where the completion date less due date is more than 60 days for Bell Atlantic Facility Reasons for product group

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &SOUNPSP&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND (
(ATC IN ('K','M','R','Y','W','X','C','S') AND ((TYPE IN ('N','T')) or
(TYPE in 'C' and (OUT_QTY=0 or INWARD_QTY>0 or
CHNG_QTY>0) and (OUTWARD_CKL=0 or INWARD_CKL>0 or
CHNG_CKL>0))))
or (type in ('R') and PON is not null ) )

```

Numerator

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &SOUNPSP&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND CISR_MAC = 'CF'
      AND (company_mac_days) > 60
      AND CMPINTV - APPINTV > 6
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
(
(TYPE IN ('N','T') or (TYPE =
AND (OUT_QTY=0 or INWARD_QTY>0
CHNG_QTY>0)
AND (OUTWARD_CKL =
OR INWARD_CKL > 0
OR CHNG_CKL > 0)))
AND ATC IN ('K','M','R','Y','W','X','C','S')
OR
(TYPE = 'R
AND PON IS NOT NULL)

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RTPS&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Numerator

UNE (Provisioning)

Report Labels: PR-5-03-3200 Special Services Provisioning Parity with VZ Retail

Guidelines: PR 5 - % Missed Appointment – Verizon – Facilities
% Orders Held for Facilities > 60 Days

Result: (Numerator / Denominator) * 100

Denominator: Count of Orders Completed for product group.	Numerator: Count of Orders where the completion date less due date is more than 60 days for Bell Atlantic Facility Reasons for product group
---	--

Filtered output file: ASR-UNE-SPECIAL
For the details on the above out put filtered file layout refer to File Appendix: 7 File Type: Excel

Denominator	Numerator
<div>SELECT COUNT(*) WHERE STATE = NJ AND ACTIVITY_DATE >= STARTDATE AND ACTIVITY_DATE <= ENDDATE AND ACT IN ('N', 'C') AND PRODUCT_TYPE IN ('DS1', 'DS3') AND ASR_STATUS = C</div>	<div>SELECT COUNT(*) WHERE STATE = NJ AND ACTIVITY_DATE >= STARTDATE AND ACTIVITY_DATE <= ENDDATE AND ACT IN ('N', 'C') AND PRODUCT_TYPE IN ('DS1', 'DS3') AND CD > DD + 60 AND NVL(SUBSTR(WFA_MFC,1,1),'X') IN ('G', 'H') AND ASR_STATUS = C</div>

UNE (Provisioning)

Report Labels: PR-5-03-3341

Complex Services - 2 Wire Digital

Parity with VZ Retail

Guidelines: PR-5 - Facility Missed Orders

% Orders Held for Facilities > 60 Days

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Orders Completed for product group.

Numerator:

Count of Orders where the completion date less due date is more than 60 days for Bell Atlantic Facility Reasons for product group

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &SOUNPI&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &SOUNPI&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND CISR_MAC = 'CF'
      AND (company_mac_days) > 60
      AND CMPINTV - APPINTV > 6
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RTPI&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPI&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND CISR_MAC = 'CF'
      AND (company_mac_days) > 60
      AND CMPINTV - APPINTV > 6
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

UNE (Provisioning)

Report Labels: PR-5-03-3342

Complex Services - 2 Wire xDSL

Parity with VZ Retail

Guidelines: PR-5 - Facility Missed Orders

% Orders Held for Facilities > 60 Days

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Orders Completed for product group.

Numerator:

Count of Orders where the completion date less due date is more than 60 days for Bell Atlantic Facility Reasons for product group

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```
SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &SOUNPD&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,*),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
```

Numerator

```
SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &SOUNPD&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND CISR_MAC = 'CF'
      AND (company_mac_days) > 60
      AND CMPINTV - APPINTV > 6
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,*),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator**

```
SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RTPD&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,*),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
```

Numerator

```
SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPD&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND CISR_MAC = 'CF'
      AND (company_mac_days) > 60
      AND CMPINTV - APPINTV > 6
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,*),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
```

TRUNKS (Aggregate)

Report Labels: PR-5-03-5000 PROVISIONING

Parity with IXC / FGD

Guidelines: PR-5 - Facility Missed Orders

% Orders Held for Facilities > 60 Days

Result: (Numerator / Denominator) * 100**Denominator:**

Count of Orders Completed for product group.

Numerator:

Count of Orders where the completion date less due date is more than 60 days for Bell Atlantic Facility Reasons for product group

Filtered output file: Trunking Filter Data

For the details on the above out put filtered file layout refer to File Appendix: 4 File Type: Excel

Formula For: CLEC**Denominator**

```
SELECT
SUM(NO_WFA_TRUNKS)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND SERVICE_TYPE = T
AND ORDER_STATUS = C
```

Numerator

```
SELECT
SUM(NO_WFA_TRUNKS)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND SERVICE_TYPE = T
AND ORDER_STATUS = C
AND NVL(SUBSTR(WFA_MFC,1,1),'X') = H
AND WFA_COMPLETED_INTERVAL >
WFA_OFFERED_INTERVAL + 60
```

Filtered output file: Trunking Filter Data

For the details on the above out put filtered file layout refer to File Appendix: 4 File Type: Excel

Formula For: VERIZON**Denominator**

```
SELECT
SUM(NO_WFA_TRUNKS)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND SERVICE_TYPE IN ('I', 'W')
AND ORDER_STATUS = C
```

Numerator

```
SELECT
SUM(NO_WFA_TRUNKS)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND SERVICE_TYPE IN ('I', 'W')
AND ORDER_STATUS = C
AND NVL(SUBSTR(WFA_MFC,1,1),'X') = H
AND WFA_COMPLETED_INTERVAL >
WFA_OFFERED_INTERVAL + 60
```

Guidelines For: PR-6 Installation Quality

C2C Guideline:	
Definition:	The percentage of lines/circuits/trunks installed where a trouble was reported and found in the BA network within 30 days (and within 7 days for POTS services) of order completion. Includes Drop Wire troubles (Disposition Code 3), Cable troubles (Disposition Code 4), and Central Office troubles (Disposition Code 5).
Performance Standard:	Metrics PR-6-01 and 02: Parity with BA Retail. Metric PR-6-03: No standard.
Exclusions:	Subsequent reports (additional customer calls while the trouble is pending). Troubles closed due to customer action. Troubles reported by Bell Atlantic employees in the course of performing preventative maintenance, where no customer has reported a trouble. Also excluded for Metrics PR-6-01 and 02: Customer Premises Equipment ("CPE") troubles. oubles reported but not found (Found OK/Test OK).
Report Dimensions:	BA Retail, CLEC Aggregate ,CLEC Specific, BA Affiliate Aggregate, BA Affiliate Specific
Geography:	POTS, 2 Wire Digital Services, and 2 Wire xDSL Services: Southern, Eastern Shore, Raritan, Suburban, Hudson-Bergen Specials: State Trunks: State

RESALE (PROVISIONING)

Report Labels: PR-6-01-2100

POTS - Provisioning - Total

Parity with VZ Retail

Guidelines: PR-6 - Installation Quality

% Installation Troubles reported within 30 Days

Result: (Numerator / Denominator) * 100**Denominator:**

Total Lines with installation activity within the reporting month.

Numerator:

Count of central office and outside plant loop (disposition code 03, 04 and 05) troubles with installation activity within 30 days of trouble report.

Filtered output file: FCC File Extract Def

For the details on the above out put filtered file layout refer to File Appendix: 23 File Type: Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
COUNT(*)
WHERE STATE = '&ST&'
      AND &RSPS&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE = 'R' and
RESELLER_ACT='I' ))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
COUNT(*)
WHERE FDIS >= 0300
AND FDIS <= 0599
AND ( AFLAG2 <> 'I', 'D'
OR CS <> 11
OR TN <> "IBZD" )
AND RESELL LIKE ("S*") AND TABLE VALIDATION
ALGORITHM
AND CDT >= STARTDATE
AND CDT <= ENDDATE
AND I30 = 'X'
AND R30 <> 'X'

```

Filtered output file: FCC File Extract Def

For the details on the above out put filtered file layout refer to File Appendix: 23 File Type: Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(*)
WHERE STATE = '&ST&'
      AND &RSPS&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE = 'R' and
RESELLER_ACT='I' ))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
COUNT(*)
WHERE FDIS >= 0300
AND FDIS <= 0599
AND ( AFLAG2 <> 'I', 'D'
OR CS <> 11
OR TN <> "IBZD" )
AND RESELL LIKE ("S*") AND TABLE VALIDATION
ALGORITHM
AND CDT >= STARTDATE
AND CDT <= ENDDATE
AND I30 = 'X'
AND R30 <> 'X'

```


RESALE (PROVISIONING)

Report Labels: PR-6-01-2200 Special Services - Provisioning

Parity with VZ Retail

Guidelines: PR-6- Installation Quality

% Installation Troubles reported within 30 Days

Result: (Numerator / Denominator) * 100**Denominator:**

Total Lines with installation activity within the reporting month.

Numerator:

Count of central office and outside plant loop (disposition code 03, 04 and 05) troubles with installation activity within 30 days of trouble report.

Filtered output file: FCC File Extract Def

For the details on the above out put filtered file layout refer to File Appendix: 23 File Type: Text

Formula For: CLEC**Denominator**

```
SELECT
SUM(decode((INWARD_QTY+
CHNG_QTY),0,(in_facil),(inward_qty+chng_qty)))
WHERE STATE = '&ST&'
AND &RSSS&
AND &Exclusions
AND STATUS in &STATUS&
AND (TYPE IN ('N','T','C')or (TYPE ='R' and
RESELLER_ACT='I' ))
AND ATC IN ('K','M','R','Y','W','X','C','S')
AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
```

Numerator

```
SELECT
SUM(decode((INWARD_QTY+
CHNG_QTY),0,(in_facil),(inward_qty+chng_qty)))
WHERE FDIS >= 0300
AND FDIS <= 0599
AND I30 = 'X'
AND R30 <> "X"
AND CDT >= STARTDATE
AND CDT <= ENDDATE
```

Filtered output file: MR Specials - Detail

For the details on the above out put filtered file layout refer to File Appendix: 25 File Type: Text

Formula For: CLEC**Denominator**

```
SELECT
SUM(decode((INWARD_QTY+
CHNG_QTY),0,(in_facil),(inward_qty+chng_qty)))
WHERE STATE = '&ST&'
AND &RSSS&
AND &Exclusions
AND STATUS in &STATUS&
AND (TYPE IN ('N','T','C')or (TYPE ='R' and
RESELLER_ACT='I' ))
AND ATC IN ('K','M','R','Y','W','X','C','S')
AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
```

Numerator

```
SELECT
SUM(decode((INWARD_QTY+
CHNG_QTY),0,(in_facil),(inward_qty+chng_qty)))
WHERE MCN 4 = 'RSID'
AND RPT_CAT = 'CR'
AND TRBL_CD IN ('FAC', 'CO', 'STN')
AND RPL_FLAG = 'Y'
```

Filtered output file: MR Specials - Detail

For the details on the above out put filtered file layout refer to File Appendix: 25 File Type: Text

Formula For: VERIZON**Denominator****Numerator**

```
SELECT
SUM(decode((INWARD_QTY+
CHNG_QTY),0,(in_facil),(inward_qty+chng_qty)))
WHERE STATE = '&ST&'
      AND &RTSS&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND TYPE IN ('N','T','C')
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
```

```
SELECT
SUM(decode((INWARD_QTY+
CHNG_QTY),0,(in_facil),(inward_qty+chng_qty)))
WHERE RPT_CAT = 'CR'
      AND TRBL_CD IN ('FAC', 'CO', 'STN')
      AND RPL_FLAG = 'Y'
      AND MCN 4 = 'NYNX'
```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON

Denominator

```
SELECT
SUM(decode((INWARD_QTY+
CHNG_QTY),0,(in_facil),(inward_qty+chng_qty)))
WHERE STATE = '&ST&'
      AND &RTSS&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND TYPE IN ('N','T','C')
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
```

Numerator

```
SELECT
SUM(decode((INWARD_QTY+
CHNG_QTY),0,(in_facil),(inward_qty+chng_qty)))
WHERE STATE = '&ST&'
      AND &RTSS&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND TYPE IN ('N','T','C')
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
```

RESALE (PROVISIONING)

Report Labels: PR-6-01-2341

Complex Services - 2 Wire Digital

Parity with VZ Retail

Guidelines: PR-6 - Installation Quality

% Installation Troubles reported within 30 Days

Result: (Numerator / Denominator) * 100**Denominator:**

Total Lines with installation activity within the reporting month.

Numerator:

Count of central office and outside plant loop (disposition code 03, 04 and 05) troubles with installation activity within 30 days of trouble report.

Filtered output file: FCC File Extract Def

For the details on the above out put filtered file layout refer to File Appendix: 23 File Type: Text

Formula For: CLEC**Denominator**

```
SELECT
COUNT(*)
WHERE STATE = '&ST&'
      AND &RSPI&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T','C') or (TYPE ='R' and
RESELLER_ACT='I' ))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
```

Numerator

```
SELECT
COUNT(*)
WHERE R30 <> X
      AND FDIS <= 0300
      AND ( FDIS >= 0599
      AND AFLAG2 = 'I'
      OR CS = 11
      OR TN LIKE "IBZD*" )
      AND CDT >= STARTDATE
      AND CDT <= ENDDATE
      AND I30 = X
      AND RESELL IS 'S' AND TABLE VALIDATION ALGORITHM
```

Filtered output file: FCC File Extract Def

For the details on the above out put filtered file layout refer to File Appendix: 23 File Type: Text

Formula For: VERIZON**Denominator**

```
SELECT
COUNT(*)
WHERE STATE = '&ST&'
      AND &RTPI&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND TYPE IN ('N','T','C')
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
```

Numerator

```
SELECT
COUNT(*)
WHERE R30 <> X
      AND FDIS >= 0300
      AND FDIS <= 0599
      AND ( AFLAG2 = 'I'
      OR CS = 11
      OR TN LIKE "IBZD*" )
      AND CDT >= STARTDATE
      AND CDT <= ENDDATE
      AND RESELL IS NULL AND TABLE VALIDATION ALGORITHM
      AND I30 = 'X'
```

RESALE (PROVISIONING)

Report Labels: PR-6-01-2342

Complex Services - 2 Wire xDSL

Parity with VZ Retail

Guidelines: PR-6 - Installation Quality

% Installation Troubles reported within 30 Days

Result: (Numerator / Denominator) * 100**Denominator:**

Total Lines with installation activity within the reporting month.

Numerator:

Count of central office and outside plant loop (disposition code 03, 04 and 05) troubles with installation activity within 30 days of trouble report.

Filtered output file: FCC File Extract Def

For the details on the above out put filtered file layout refer to File Appendix: 23 File Type: Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
COUNT(*)
WHERE STATE = '&ST&'
      AND &RSPD&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T','C') or (TYPE ='R' and
RESELLER_ACT='I' ))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
COUNT(*)
WHERE R30 <> X
      AND FDIS >= 0300
      AND FDIS <= 0599
      AND ( R30 = 'X'
      AND OR <> 'I' )
      AND AFLAG2 = 'D'
      AND CDT >= STARTDATE
      AND CDT <= ENDDATE
      AND RESELL IS 'S' AND TABLE VALIDATION ALGORITHM
      AND I30 = X

```

Filtered output file: FCC File Extract Def

For the details on the above out put filtered file layout refer to File Appendix: 23 File Type: Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
COUNT(*)
WHERE STATE = '&ST&'
      AND &RTPD&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND TYPE IN ('N','T','C')
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
COUNT(*)
WHERE R30 <> X
      AND FDIS >= 0300
      AND FDIS <= 0599
      AND ( R30 = 'X'
      AND OR <> 'I' )
      AND AFLAG2 = 'D'
      AND CDT >= STARTDATE
      AND CDT <= ENDDATE
      AND RESELL IS NULL AND TABLE VALIDATION ALGORITHM
      AND I30 = X

```

UNE (Provisioning)

Report Labels: PR-6-01-3112 POTS - Provisioning

Parity with VZ Retail

Guidelines: PR-6 - Installation Quality

% Installation Troubles reported within 30 Days - Loop

Result: (Numerator / Denominator) * 100**Denominator:**

Total Lines with installation activity within the reporting month.

Numerator:

Count of central office and outside plant loop (disposition code 03, 04 and 05) troubles with installation activity within 30 days of trouble report.

Filtered output file: FCC File Extract Def

For the details on the above out put filtered file layout refer to File Appendix: 23 File Type: Text

Formula For: CLEC**Denominator**

```
SELECT
SUM(INWARD_QTY+CHNG_QTY)
WHERE STATE = '&ST&'
      AND &SOUNPSL&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
```

Numerator

```
SELECT
SUM(INWARD_QTY+CHNG_QTY)
WHERE FDIS >= 0300
      AND FDIS <= 0499
      AND TN = "TXNU*"
      AND CDT >= STARTDATE
      AND CDT <= ENDDATE
      AND RESELL LIKE ("W*") AND TABLE VALIDATION
ALGORITHM
```

Filtered output file: FCC File Extract Def

For the details on the above out put filtered file layout refer to File Appendix: 23 File Type: Text

Formula For: VERIZON**Denominator****Numerator**

```
SELECT
SUM(INWARD_QTY+CHNG_QTY)
WHERE FDIS >= 0300
      AND FDIS <= 0499
      AND AFLAG2 NOT IN ('D', 'I')
      AND CS <> 11
      AND TN NOT LIKE "IBZD*"
      AND CDT >= STARTDATE
      AND CDT <= ENDDATE
      AND RESELL IS NULL AND TABLE VALIDATION ALGORITHM
```

UNE (Provisioning)

Report Labels: PR-6-01-3140 POTS - Provisioning

Parity with VZ Retail

Guidelines: PR-6 - Installation Quality

% Installation Troubles reported within 30 Days - Platform

Result: (Numerator / Denominator) * 100**Denominator:**

Total Lines with installation activity within the reporting month.

Numerator:

Count of central office and outside plant loop (disposition code 03, 04 and 05) troubles with installation activity within 30 days of trouble report.

Filtered output file: FCC File Extract Def

For the details on the above out put filtered file layout refer to File Appendix: 23 File Type: Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
SUM(INWARD_QTY+CHNG_QTY)
WHERE STATE = '&ST&'
      AND &SOUNPSP&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
      (
        (TYPE IN ('N','T','C')
          AND ATC IN ('K','M','R','Y','W','X','C','S'))
        OR
        (TYPE = 'R'
          AND PON IS NOT NULL)
      )

```

```

SELECT
SUM(INWARD_QTY+CHNG_QTY)
WHERE FDIS >= 0300
      AND FDIS <= 0599
      AND AFLAG2 NOT IN ('D', 'I')
      AND CS <> 11
      AND CDT >= STARTDATE
      AND TN NOT LIKE "IBZD*"
      AND CDT <= ENDDATE
      AND RESELL IS 'S' AND TABLE VALIDATION ALGORITHM
      AND R30 <> X
      AND I30 = X

```

Filtered output file: FCC File Extract Def

For the details on the above out put filtered file layout refer to File Appendix: 23 File Type: Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
SUM(INWARD_QTY+CHNG_QTY)
WHERE STATE = '&ST&'
      AND &RTPS&
      AND &RetailExclusions&
      AND TYPE IN ('N','T','C')
      AND STATUS in &STATUS&
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
SUM(INWARD_QTY+CHNG_QTY)
WHERE FDIS >= 0300
      AND FDIS <= 0599
      AND AFLAG2 NOT IN ('D', 'I')
      AND CS <> 11
      AND CDT >= STARTDATE
      AND TN NOT LIKE "IBZD*"
      AND CDT <= ENDDATE
      AND RESELL IS NULL AND TABLE VALIDATION ALGORITHM
      AND R30 <> X
      AND I30 = X

```

UNE (Provisioning)

Report Labels: PR-6-01-3200 Special Services Provisioning

Parity with VZ Retail

Guidelines: PR-6 - Installation Quality

% Installation Troubles reported within 30 Days

Result: (Numerator / Denominator) * 100**Denominator:**

Total Lines with installation activity within the reporting month.

Numerator:

Count of central office and outside plant loop (disposition code 03, 04 and 05) troubles with installation activity within 30 days of trouble report.

Filtered output file: ASR-UNE-SPECIAL

For the details on the above out put filtered file layout refer to File Appendix: 7 File Type: Excel

Denominator**Numerator****SELECT
COUNT(*)**

```
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND ACT IN ('N', 'C')
AND PRODUCT_TYPE IN ('DS1', 'DS3', 'IOF')
AND ASR_STATUS = C
```

Filtered output file: ASR-UNE-SPECIAL

For the details on the above out put filtered file layout refer to File Appendix: 7 File Type: Excel

Formula For: CLEC**Denominator****Numerator****SELECT
COUNT(*)**

```
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND ACT IN ('N', 'C')
AND PRODUCT_TYPE IN ('DS1', 'DS3', 'IOF')
AND ASR_STATUS = 'C'
```

Filtered output file: MR Specials - Detail

For the details on the above out put filtered file layout refer to File Appendix: 25 File Type: Text

Formula For: CLEC**Denominator****Numerator****SELECT
COUNT(*)**

```
WHERE MCN 4 = 'AECN'
AND RPT_CAT = 'CR'
AND TRBL_CD IN ('FAC', 'CO', 'STN')
AND RPL_FLAG = 'Y'
```

Filtered output file: ASR-UNE-SPECIAL

For the details on the above out put filtered file layout refer to File Appendix: 7 File Type: Excel

Formula For: VERIZON**Denominator****Numerator**

<div><div><div>SELECT COUNT(*) WHERE STATE = NJ AND ACTIVITY_DATE >= STARTDATE AND ACTIVITY_DATE <= ENDDATE AND ACT IN ('N', 'C') AND PRODUCT_TYPE IN ('DS1', 'DS3', 'IOF') AND ASR_STATUS = 'C'</div></div></div>	
<div><div><div><div>Filtered output file: MR Specials - Detail</div><div>For the details on the above out put filtered file layout refer to File Appendix: 25 File Type: Text</div></div><div>Formula For: VERIZON</div></div></div>	
Denominator	Numerator
	<div><div><div>SELECT COUNT(*) WHERE MCN 4 = 'NYNX' AND RPT_CAT = 'CR' AND TRBL_CD IN ('FAC', 'CO', 'STN') AND RPI_FLAG = 'Y'</div></div></div>

UNE (Provisioning)

Report Labels: PR-6-01-3341

Complex Services - 2 Wire Digital

Parity with VZ Retail

Guidelines: PR-6 - Installation Quality

% Installation Troubles reported within 30 Days

Result: (Numerator / Denominator) * 100**Denominator:**

Total Lines with installation activity within the reporting month.

Numerator:

Count of central office and outside plant loop (disposition code 03, 04 and 05) troubles with installation activity within 30 days of trouble report.

Filtered output file: FCC File Extract Def

For the details on the above out put filtered file layout refer to File Appendix: 23 File Type: Text

Formula For: CLEC**Denominator**

```
SELECT
COUNT(*)
WHERE STATE = '&ST&'
      AND &SOUNPI&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
```

Numerator

```
SELECT
COUNT(*)
WHERE FDIS >= 0300
      AND FDIS <= 0499
      AND CDT >= STARTDATE
      AND CDT <= ENDDATE
      AND RESELL LIKE ("W*") AND TABLE VALIDATION
ALGORITHM
      AND TN IN ('DY', 'TY', 'HMXU')
```

Filtered output file: FCC File Extract Def

For the details on the above out put filtered file layout refer to File Appendix: 23 File Type: Text

Formula For: VERIZON**Denominator****Numerator**

```
SELECT
COUNT(*)
WHERE FDIS >= 0300
      AND FDIS <= 0499
      AND CDT >= STARTDATE
      AND CDT <= ENDDATE
      AND RESELL IS NULL AND TABLE VALIDATION ALGORITHM
AND ( AFLAG2 = 'I'
      OR CS = 11
      OR TN LIKE 'IBZD*')
```

UNE (Provisioning)

Report Labels: PR-6-01-3342

Complex Services - 2 Wire xDSL

Parity with VZ Retail

Guidelines: PR-6 - Installation Quality

% Installation Troubles reported within 30 Days

Result: (Numerator / Denominator) * 100**Denominator:**

Total Lines with installation activity within the reporting month.

Numerator:

Count of central office and outside plant loop (disposition code 03, 04 and 05) troubles with installation activity within 30 days of trouble report.

Filtered output file: FCC File Extract Def

For the details on the above out put filtered file layout refer to File Appendix: 23 File Type: Text

Formula For: CLEC**Denominator**

```
SELECT
COUNT(*)
WHERE STATE = '&ST&'
      AND &SOUNPD&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
```

Numerator

```
SELECT
COUNT(*)
WHERE FDIS >= 0300
      AND FDIS <= 0499
      AND CDT >= STARTDATE
      AND CDT <= ENDDATE
      AND RESELL LIKE ("W*") AND TABLE VALIDATION
ALGORITHM
      AND TN IN ('DY','TY','HMXU')
```

Filtered output file: FCC File Extract Def

For the details on the above out put filtered file layout refer to File Appendix: 23 File Type: Text

Formula For: VERIZON**Denominator**

```
SELECT
COUNT(*)
WHERE STATE = '&ST&'
      AND &SOUNPD&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
```

Numerator

```
SELECT
COUNT(*)
WHERE FDIS >= 0300
      AND FDIS <= 0499
      AND CDT >= STARTDATE
      AND CDT <= ENDDATE
      AND RESELL IS NULL AND TABLE VALIDATION ALGORITHM
      AND ( AFLAG2 = 'L'
      OR TN IN ('ARDU','AQDU') )
```

TRUNKS (Aggregate)

Report Labels: PR-6-01-5000 PROVISIONING

Parity with IXC / FGD

Guidelines: PR-6 - Installation Quality

% Installation Troubles reported within 30 Days

Result: (Numerator / Denominator) * 100**Denominator:**

Total Lines with installation activity within the reporting month.

Numerator:

Count of central office and outside plant loop (disposition code 03, 04 and 05) troubles with installation activity within 30 days of trouble report.

Filtered output file: FCC File Extract Def

For the details on the above out put filtered file layout refer to File Appendix: 23 File Type: Text

Formula For: CLEC**Denominator****Numerator**

```
SELECT
SUM(ACTUAL_DUR)
WHERE FDIS >= 0300
AND FDIS <= 5999
AND CDT >= STARTDATE
AND CDT <= ENDDATE
AND I30 = 'X'
AND R30 = 'X'
```

Filtered output file: Trunking Filter Data

For the details on the above out put filtered file layout refer to File Appendix: 4 File Type: Excel

Formula For: CLEC**Denominator****Numerator**

```
SELECT
COUNT(*)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND SERVICE_TYPE IN ('T', 'R')
AND ORDER_STATUS = C
```

Filtered output file: Trunking Filter Data

For the details on the above out put filtered file layout refer to File Appendix: 4 File Type: Excel

Formula For: VERIZON**Denominator****Numerator**

```
SELECT
COUNT(*)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND SERVICE_TYPE IN ('I', 'W')
AND ORDER_STATUS = C
```

RESALE (PROVISIONING)

Report Labels: PR-6-02-2100 POTS - Provisioning - Total

Parity with VZ Retail

Guidelines: PR-6 - Installation Quality

% Installation Troubles reported within 7 Days

Result: (Numerator / Denominator) * 100**Denominator:**

Total Lines with installation activity within the reporting month.

Numerator:

Count of central office and outside plant loop (disposition code 03, 04 and 05) troubles with installation activity within 7 days of trouble report.

Filtered output file: FCC File Extract Def

For the details on the above out put filtered file layout refer to File Appendix: 23 File Type: Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
SUM(INWARD_QTY+CHNG_QTY)
WHERE STATE = '&ST&'
      AND &RSPS&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE = 'R' and
RESELLER_ACT='I' ))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
SUM(INWARD_QTY+CHNG_QTY)
WHERE FDIS >= 0300
AND FDIS <= 0499
AND ( AFLAG2 <> 'I', 'D'
OR CS <> 11
OR TN <> "IBZD" )
AND RESELL LIKE ("S*") AND TABLE VALIDATION
ALGORITHM
AND CDT >= STARTDATE
AND CDT <= ENDDATE

```

Filtered output file: FCC File Extract Def

For the details on the above out put filtered file layout refer to File Appendix: 23 File Type: Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
SUM(INWARD_QTY+CHNG_QTY)
WHERE STATE = '&ST&'
      AND &RSPS&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE = 'R' and
RESELLER_ACT='I' ))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
SUM(INWARD_QTY+CHNG_QTY)
WHERE FDIS >= 0300
AND FDIS <= 0499
AND ( AFLAG2 <> 'I', 'D'
OR CS <> 11
OR TN <> "IBZD" )
AND RESELL LIKE NULL AND TABLE VALIDATION
ALGORITHM
AND CDT >= STARTDATE
AND CDT <= ENDDATE

```

UNE (Provisioning)

Report Labels: PR-6-02-3112 POTS - Provisioning

Parity with VZ Retail

Guidelines: PR-6 - Installation Quality

% Installation Troubles reported within 7 Days - Loop

Result: (Numerator / Denominator) * 100**Denominator:**

Total Lines with installation activity within the reporting month.

Numerator:

Count of central office and outside plant loop (disposition code 03, 04 and 05) troubles with installation activity within 7 days of trouble report.

Filtered output file: FCC File Extract Def

For the details on the above out put filtered file layout refer to File Appendix: 23 File Type: Text

Formula For: CLEC**Denominator**

```
SELECT
SUM(INWARD_QTY+CHNG_QTY)
WHERE STATE = '&ST&'
      AND &SOUNPSP&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
```

Numerator

```
SELECT
SUM(INWARD_QTY+CHNG_QTY)
WHERE FDIS >= 0300
      AND FDIS <= 0499
      AND TN = "TXNU*"
      AND CDT >= STARTDATE
      AND CDT <= ENDDATE
      AND RESELL LIKE ("W*") AND TABLE VALIDATION
ALGORITHM
```

Filtered output file: FCC File Extract Def

For the details on the above out put filtered file layout refer to File Appendix: 23 File Type: Text

Formula For: VERIZON**Denominator****Numerator**

```
SELECT
SUM(INWARD_QTY+CHNG_QTY)
WHERE FDIS >= 0300
      AND FDIS <= 0499
      AND AFLAG2 NOT IN ('D', 'I')
      AND CS <> 11
      AND TN NOT LIKE "IBZD*"
      AND CDT >= STARTDATE
      AND CDT <= ENDDATE
      AND RESELL IS NULL AND TABLE VALIDATION ALGORITHM
```

UNE (Provisioning)

Report Labels: PR-6-02-3140 POTS - Provisioning

Parity with VZ Retail

Guidelines: PR-6 - Installation Quality

% Installation Troubles reported within 7 Days - Platform

Result: (Numerator / Denominator) * 100**Denominator:**

Total Lines with installation activity within the reporting month.

Numerator:

Count of central office and outside plant loop (disposition code 03, 04 and 05) troubles with installation activity within 7 days of trouble report.

Filtered output file: FCC File Extract Def

For the details on the above out put filtered file layout refer to File Appendix: 23 File Type: Text

Formula For: CLEC**Denominator**

```
SELECT
SUM(INWARD_QTY+CHNG_QTY)
WHERE STATE = '&ST&'
      AND &SOUNPSP&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND
      (
        (TYPE IN ('N','T','C')
          AND ATC IN ('K','M','R','Y','W','X','C','S'))
        OR
        (TYPE = 'R'
          AND PON IS NOT NULL)
```

Numerator

```
SELECT
SUM(INWARD_QTY+CHNG_QTY)
WHERE FDIS >= 0300
      AND FDIS <= 0499
      AND CDT >= STARTDATE
      AND CDT <= ENDDATE
      AND RESELL LIKE ("W*") AND TABLE VALIDATION
      ALGORITHM
      AND SC IN ('RBM','RUC','RRM','RDXJX','RDXUX','RBX')
```

Filtered output file: FCC File Extract Def

For the details on the above out put filtered file layout refer to File Appendix: 23 File Type: Text

Formula For: VERIZON**Denominator**

```
SELECT
SUM(INWARD_QTY+CHNG_QTY)
WHERE STATE = '&ST&'
      AND &RTPS&
      AND &RetailExclusions&
      AND TYPE IN ('N','T','C')
      AND STATUS in &STATUS&
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
```

Numerator

```
SELECT
SUM(INWARD_QTY+CHNG_QTY)
WHERE FDIS >= 0300
      AND FDIS <= 0499
      AND AFLAG2 NOT IN ('D','I')
      AND CS <> 11
      AND TN NOT LIKE "IBZD*"
      AND CDT >= STARTDATE
      AND CDT <= ENDDATE
      AND RESELL IS NULL AND TABLE VALIDATION ALGORITHM
```

RESALE (PROVISIONING)

Report Labels: PR-6-03-2100 POTS - Provisioning - Total

No Standard

Guidelines: PR-6 - Installation Quality

% Installation Troubles reported within 30 Days – FOK/TOK/CPE

Result: (Numerator / Denominator) * 100**Denominator:**

Total Lines with installation activity within the reporting month.

Numerator:

Count of Not Found, Test OK and CPE troubles with installation activity within 30 days of trouble report.

Filtered output file: FCC File Extract Def

For the details on the above out put filtered file layout refer to File Appendix: 23 File Type: Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
SUM(INWARD_QTY+CHNG_QTY)
WHERE STATE = '&ST&'
      AND &RSPS&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE = 'R' and
RESELLER_ACT='I' ))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
SUM(INWARD_QTY+CHNG_QTY)
WHERE AFLAG2 NOT IN ('D', 'I')
      AND CDT >= STARTDATE
      AND CDT <= ENDDATE
      AND CS <> 11
      AND TN NOT LIKE "IBZD*"
      AND RESELL LIKE ("S*") AND TABLE VALIDATION
      ALGORITHM
      AND FDIS >= 0700
      AND FDIS <= 0999
      OR FDIS >= 1200
      AND FDIS <= 1399

```

Filtered output file: FCC File Extract Def

For the details on the above out put filtered file layout refer to File Appendix: 23 File Type: Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
SUM(INWARD_QTY+CHNG_QTY)
WHERE STATE = '&ST&'
      AND &RSPS&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE = 'R' and
RESELLER_ACT='I' ))
      AND ATC in ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
SUM(INWARD_QTY+CHNG_QTY)
WHERE AFLAG2 NOT IN ('D', 'I')
      AND CDT >= STARTDATE
      AND CDT <= ENDDATE
      AND CS <> 11
      AND TN NOT LIKE "IBZD*"
      AND RESELL IS NULL AND TABLE VALIDATION ALGORITHM
      AND FDIS >= 0700
      AND FDIS <= 0999
      OR FDIS >= 1200
      AND FDIS <= 1399

```

RESALE (PROVISIONING)

Report Labels: PR-6-03-2200 Special Services - Provisioning

No Standard

Guidelines: PR-6- Installation Quality

% Installation Troubles reported within 30 Days – FOK/TOK/CPE

Result: (Numerator / Denominator) * 100**Denominator:**

Total Lines with installation activity within the reporting month.

Numerator:

Count of Not Found, Test OK and CPE troubles with installation activity within 30 days of trouble report.

Filtered output file: MR Specials - Detail

For the details on the above out put filtered file layout refer to File Appendix: 25 File Type: Text

Formula For: CLEC**Denominator**

```
SELECT
SUM(decode((INWARD_QTY+
CHNG_QTY),0,(in_facil),(inward_qty+chng_qty)))
WHERE STATE = '&ST&'
AND &RSSS&
AND &Exclusions
AND STATUS in &STATUS&
AND (TYPE IN ('N','T','C')or (TYPE ='R' and
RESELLER_ACT='I' ))
AND ATC IN ('K','M','R','Y','W','X','C','S')
AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
```

Numerator

```
SELECT
SUM(decode((INWARD_QTY+
CHNG_QTY),0,(in_facil),(inward_qty+chng_qty)))
WHERE MCN 4 = 'RSID'
AND RPT_CAT = 'CR'
AND TRBL_CD IN ('FOK', 'TOK', 'CPE', 'CC', NTF')
AND RPI_FLAG = 'Y'
```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```
SELECT
SUM(decode((INWARD_QTY+
CHNG_QTY),0,(in_facil),(inward_qty+chng_qty)))
WHERE STATE = '&ST&'
AND &RSSS&
AND &Exclusions
AND STATUS in &STATUS&
AND (TYPE IN ('N','T','C')or (TYPE ='R' and
RESELLER_ACT='I' ))
AND ATC IN ('K','M','R','Y','W','X','C','S')
AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
```

Numerator

```
SELECT
SUM(decode((INWARD_QTY+
CHNG_QTY),0,(in_facil),(inward_qty+chng_qty)))
WHERE STATE = '&ST&'
AND &RSSS&
AND &Exclusions
AND STATUS in &STATUS&
AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 o
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' ))
AND CISR_MAC = 'CF'
AND (company_mac_days) > 60
AND CMPINTV - APPINTV > 6
AND ATC IN ('K','M','R','Y','W','X','C','S')
AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
```

Filtered output file: MR Specials - Detail

For the details on the above out put filtered file layout refer to File Appendix: 25 File Type: Text

Formula For: VERIZON**Denominator****Numerator**

<pre>SELECT SUM(decode((INWARD_QTY+ CHNG_QTY),0,(in_facil),(inward_qty+chng_qty))) WHERE STATE = '&ST&' AND &RTSS& AND &RetailExclusions AND STATUS in &STATUS& AND TYPE IN ('N','T','C') AND ATC IN ('K','M','R','Y','W','X','C','S') AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&) AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O' AND NVL(CLS,0) NOT IN ('DB2','DB5','MMS','MUZ','SU2','ZZO')</pre>	<pre>SELECT SUM(decode((INWARD_QTY+ CHNG_QTY),0,(in_facil),(inward_qty+chng_qty))) WHERE MCN 4 = 'NYNX' AND RPT_CAT = 'CR' AND TRBL_CD IN ('FOK', 'TOK', 'CPE', 'CC', NTF') AND RPI_FLAG = 'Y'</pre>
<p>Filtered output file: Service Order Record Data Layout</p> <p>For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text</p> <p>Formula For: VERIZON</p>	
<p>Denominator</p> <pre>SELECT SUM(decode((INWARD_QTY+ CHNG_QTY),0,(in_facil),(inward_qty+chng_qty))) WHERE STATE = '&ST&' AND &RTSS& AND &RetailExclusions AND STATUS in &STATUS& AND TYPE IN ('N','T','C') AND ATC IN ('K','M','R','Y','W','X','C','S') AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&) AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O' AND NVL(CLS,0) NOT IN ('DB2','DB5','MMS','MUZ','SU2','ZZO')</pre>	<p>Numerator</p>

RESALE (PROVISIONING)

Report Labels: PR-6-03-2341

Complex Services - 2 Wire Digital

No Standard

Guidelines: PR-6 - Installation Quality

% Inst. Troubles reported w/ in 30 Days - FOK/TOK/CPE

Result: (Numerator / Denominator) * 100**Denominator:**

Total Lines with installation activity within the reporting month.

Numerator:

Count of Not Found, Test OK and CPE troubles with installation activity within 30 days of trouble report.

Filtered output file: FCC File Extract Def

For the details on the above out put filtered file layout refer to File Appendix: 23 File Type: Text

Formula For: CLEC**Denominator**

```

SELECT
SUM(IN_FACIL)
WHERE STATE = '&ST&'
      AND &RSPI&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T','C') or (TYPE ='R' and
RESELLER_ACT='I' ))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Numerator

```

SELECT
SUM(IN_FACIL)
WHERE AFLAG2 = 'I' (
OR CS = 11
OR TN LIKE "IBZD*" )
AND CDT >= STARTDATE
AND CDT <= ENDDATE
AND RESELL LIKE ("S*") AND TABLE VALIDATION
ALGORITHM
AND FDIS >= 0700
AND FDIS <= 0999
OR FDIS >= 1200
AND FDIS <= 1399

```

Filtered output file: FCC File Extract Def

For the details on the above out put filtered file layout refer to File Appendix: 23 File Type: Text

Formula For: VERIZON**Denominator**

```

SELECT
SUM(IN_FACIL)
WHERE STATE = '&ST&'
      AND &RTPI&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND TYPE IN ('N','T','C')
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Numerator

```

SELECT
SUM(IN_FACIL)
WHERE AFLAG2 = 'I' (
OR CS = 11
OR TN LIKE "IBZD*" )
AND CDT >= STARTDATE
AND CDT <= ENDDATE
AND RESELL IS NULL AND TABLE VALIDATION ALGORITHM
AND FDIS >= 0700
AND FDIS <= 0999
OR FDIS >= 1200
AND FDIS <= 1399

```

RESALE (PROVISIONING)

Report Labels: PR-6-03-2342

Complex Services - 2 Wire xDSL

No Standard

Guidelines: PR-6 - Installation Quality

% Inst. Troubles reported w/ in 30 Days - FOK/TOK/CPE

Result: (Numerator / Denominator) * 100**Denominator:**

Total Lines with installation activity within the reporting month.

Numerator:

Count of Not Found, Test OK and CPE troubles with installation activity within 30 days of trouble report.

Filtered output file: FCC File Extract Def

For the details on the above out put filtered file layout refer to File Appendix: 23 File Type: Text

Formula For: CLEC**Denominator**

```

SELECT
SUM(INWARD_QTY+CHNG_QTY)
WHERE STATE = '&ST&'
      AND &RSPD&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T','C') or (TYPE ='R' and
RESELLER_ACT='I' ))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Numerator

```

SELECT
SUM(INWARD_QTY+CHNG_QTY)
WHERE AFLAG2 = 'D'
      AND CDT >= STARTDATE
      AND CDT <= ENDDATE
      AND RESELL LIKE ("S*") AND TABLE VALIDATION
      ALGORITHM
      AND FDIS >= 0700
      AND FDIS <= 0999
      OR FDIS >= 1200
      AND FDIS <= 1399

```

Filtered output file: FCC File Extract Def

For the details on the above out put filtered file layout refer to File Appendix: 23 File Type: Text

Formula For: VERIZON**Denominator**

```

SELECT
SUM(INWARD_QTY+CHNG_QTY)
WHERE STATE = '&ST&'
      AND &RTPD&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND TYPE IN ('N','T','C')
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Numerator

```

SELECT
SUM(INWARD_QTY+CHNG_QTY)
WHERE AFLAG2 = 'D'
      AND CDT >= STARTDATE
      AND CDT <= ENDDATE
      AND RESELL LIKE (NULL) AND TABLE VALIDATION
      ALGORITHM
      AND FDIS >= 0700
      AND FDIS <= 0999
      OR FDIS >= 1200
      AND FDIS <= 1399

```

UNE (Provisioning)

Report Labels: PR-6-03-3112 POTS - Provisioning

No Standard

Guidelines: PR-6 - Installation Quality

% Installation Troubles reported within 30 Days – FOK/TOK/CPE - Loop

Result: (Numerator / Denominator) * 100**Denominator:**

Total Lines with installation activity within the reporting month.

Numerator:

Count of Not Found, Test OK and CPE troubles with installation activity within 30 days of trouble report.

Filtered output file: FCC File Extract Def

For the details on the above out put filtered file layout refer to File Appendix: 23 File Type: Text

Formula For: CLEC**Denominator**

```
SELECT
SUM(INWARD_QTY+CHNG_QTY)
WHERE STATE = '&ST&'
      AND &SOUNL&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND TYPE IN ('N','T','C')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
```

Numerator

```
SELECT
SUM(INWARD_QTY+CHNG_QTY)
WHERE TN = "TXNU*"
      AND CDT >= STARTDATE
      AND CDT <= ENDDATE
      AND RESELL LIKE ("W*") AND TABLE VALIDATION
      ALGORITHM
      AND FDIS >= 0700
      AND FDIS <= 0999
      OR FDIS >= 1200
      AND FDIS <= 1399
```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator**

```
SELECT
SUM(INWARD_QTY+CHNG_QTY)
WHERE STATE = '&ST&'
      AND &RTPS&
      AND &RetailExclusions&
      AND TYPE IN ('N','T','C')
      AND STATUS in &STATUS&
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
```

Numerator

UNE (Provisioning)

Report Labels: PR-6-03-3121 POTS - Provisioning

No Standard

Guidelines: PR-6 - Installation Quality

% Installation Troubles reported within 30 Days – FOK/TOK/CPE - Other

Result: (Numerator / Denominator) * 100**Denominator:**

Total Lines with installation activity within the reporting month.

Numerator:

Count of Not Found, Test OK and CPE troubles with installation activity within 30 days of trouble report.

Filtered output file: FCC File Extract Def

For the details on the above out put filtered file layout refer to File Appendix: 23 File Type: Text

Formula For: CLEC**Denominator****SELECT**

```

WHERE STATE = '&ST&'
      AND &SOUNPSO&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND TYPE IN ('N','T','C')
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Numerator**SELECT**

```

WHERE STATE = '&ST&'
      AND &SOUNPSO&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND TYPE IN ('N','T','C')
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Filtered output file: FCC File Extract Def

For the details on the above out put filtered file layout refer to File Appendix: 23 File Type: Text

Formula For: VERIZON**Denominator****SELECT**

```

WHERE STATE = '&ST&'
      AND &RTPS&
      AND &RetailExclusions&
      AND TYPE IN ('N','T','C')
      AND STATUS in &STATUS&
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Numerator**SELECT**

```

WHERE AFLAG2 NOT IN ('D', 'I')
AND CS <> 11
AND TN NOT LIKE "IBZD*"
AND CDT >= STARTDATE
AND CDT <= ENDDATE
AND RESELL IS NULL AND TABLE VALIDATION ALGORITHM
AND FDIS >= 0700
AND FDIS <= 0999
OR FDIS >= 1200
AND FDIS <= 1399

```

UNE (Provisioning)

Report Labels: PR-6-03-3200 Special Services Provisioning

No Standard

Guidelines: PR-6 - Installation Quality

% Installation Troubles reported within 30 Days – FOK/TOK/CPE

Result: (Numerator / Denominator) * 100**Denominator:**

Total Lines with installation activity within the reporting month.

Numerator:

Count of Not Found, Test OK and CPE troubles with installation activity within 30 days of trouble report.

Filtered output file: ASR-UNE-SPECIAL

For the details on the above out put filtered file layout refer to File Appendix: 7 File Type: Excel

Denominator**Numerator**

```
SELECT
SUM(ASR_QTY)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND ACT IN ('N', 'C')
AND PRODUCT_TYPE IN ('DS1', 'DS3', 'IOF')
AND ASR_STATUS = C
```

Filtered output file: ASR-UNE-SPECIAL

For the details on the above out put filtered file layout refer to File Appendix: 7 File Type: Excel

Formula For: CLEC**Denominator****Numerator**

```
SELECT
SUM(ASR_QTY)
WHERE STATE = 'NJ'
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND ACT IN ('N', 'C')
AND PRODUCT_TYPE IN ('DS1', 'DS3', 'IOF')
AND ASR_STATUS = 'C'
```

Filtered output file: MR Specials - Detail

For the details on the above out put filtered file layout refer to File Appendix: 25 File Type: Text

Formula For: CLEC**Denominator****Numerator**

```
SELECT
COUNT(*)
WHERE MCN 4 = 'AECN'
AND RPT_CAT = 'CR'
AND TRBL_CD IN ('FOK', 'TOK', 'CPE', 'CC', 'NTF')
AND RPL_FLAG = 'Y'
```

Filtered output file: ASR-UNE-SPECIAL

For the details on the above out put filtered file layout refer to File Appendix: 7 File Type: Excel

Formula For: VERIZON**Denominator****Numerator**

<div><div><div>SELECT SUM(ASR_QTY) WHERE STATE = 'NJ' AND ACTIVITY_DATE >= STARTDATE AND ACTIVITY_DATE <= ENDDATE AND ACT IN ('N', 'C') AND PRODUCT_TYPE IN ('DS1', 'DS3', 'IOF') AND ASR_STATUS = 'C'</div></div></div>	
<div><div><div><div>Filtered output file: MR Specials - Detail</div><div>For the details on the above out put filtered file layout refer to File Appendix: 25 File Type: Text</div></div><div>Formula For: VERIZON</div></div></div>	
Denominator	<div><div><div>SELECT COUNT(*) WHERE MCN 4 = 'NYNX' AND RPT_CAT = 'CR' AND TRBL_CD IN ('FOK', 'TOK', 'CPE', 'CC', 'NTF') AND RPI_FLAG = 'Y'</div></div></div>

UNE (Provisioning)

Report Labels: PR-6-03-3341

Complex Services - 2 Wire Digital

No Standard

Guidelines: PR-6 - Installation Quality

% Inst. Troubles reported w/ in 30 Days - FOK/TOK/CPE

Result: (Numerator / Denominator) * 100**Denominator:**

Total Lines with installation activity within the reporting month.

Numerator:

Count of Not Found, Test OK and CPE troubles with installation activity within 30 days of trouble report.

Filtered output file: FCC File Extract Def

For the details on the above out put filtered file layout refer to File Appendix: 23 File Type: Text

Formula For: CLEC**Denominator**

```
SELECT
SUM(decode((INWARD_QTY+
CHNG_QTY),0,(in_facil),(inward_qty+chng_qty)))
WHERE STATE = '&ST&'
AND &SOUNPI&
AND &Exclusions
AND STATUS in &STATUS&
AND (TYPE in ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
AND ATC in ('K','M','R','Y','W','X','C','S')
AND
decode(WFA_NUM_do,null,decode(ocb_coc,'O',1,'C',0,0),WFA_N
UM_DO)>0
AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
AND SUBSTR(NVL(SWO_CODE,*),1,1)<>'O'
AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
```

Numerator

```
SELECT
SUM(decode((INWARD_QTY+
CHNG_QTY),0,(in_facil),(inward_qty+chng_qty)))
WHERE CDT >= STARTDATE
AND CDT <= ENDDATE
AND RESELL LIKE ("W*") AND TABLE VALIDATION
ALGORITHM
AND ( AFLAG2 = 'L'
OR TN in ('ARDU', 'AQDU') )
AND FDIS >= 0700
AND FDIS <= 0999
OR FDIS >= 1200
AND FDIS <= 1399
```

Filtered output file: FCC File Extract Def

For the details on the above out put filtered file layout refer to File Appendix: 23 File Type: Text

Formula For: VERIZON**Denominator****Numerator**

```
SELECT
SUM(IN_FACIL)
WHERE CDT >= STARTDATE
AND CDT <= ENDDATE
AND ( AFLAG2 = 'I'
OR CS = 11
OR TN LIKE 'IBZD*' )
AND RESELL IS NULL AND TABLE VALLIDATION ALGORITHM
AND FDIS >= 0700
AND FDIS <= 0999
OR FDIS >= 1200
AND FDIS <= 1399
```


UNE (Provisioning)

Report Labels: PR-6-03-3342

Complex Services - 2 Wire xDSL

No Standard

Guidelines: PR-6 - Installation Quality

% Inst. Troubles reported w/ in 30 Days - FOK/TOK/CPE

Result: (Numerator / Denominator) * 100**Denominator:**

Total Lines with installation activity within the reporting month.

Numerator:

Count of Not Found, Test OK and CPE troubles with installation activity within 30 days of trouble report.

Filtered output file: FCC File Extract Def

For the details on the above out put filtered file layout refer to File Appendix: 23 File Type: Text

Formula For: CLEC**Denominator****Numerator**

```
SELECT
SUM(decode((INWARD_QTY+
CHNG_QTY),0,(in_facil),(inward_qty+chng_qty)))
WHERE CDT >= STARTDATE
AND RESELL LIKE "W*" AND TABLE VALIDATION ALGORITHM
AND CDT <= ENDDATE
AND AFLAG2 = 'L'
AND TN IN 'AQDU', 'ARDU' )
```

```
SELECT
SUM(decode((INWARD_QTY+
CHNG_QTY),0,(in_facil),(inward_qty+chng_qty)))
WHERE CDT >= STARTDATE
AND RESELL LIKE "W*" AND TABLE VALIDATION
ALGORITHM
AND CDT <= ENDDATE
AND FDIS >= 0700
AND FDIS <= 0999
OR FDIS >= 1200
AND FDIS <= 1399
AND ( AFLAG2 = 'L'
AND TN IN 'AQDU', 'ARDU' )
```

Filtered output file: FCC File Extract Def

For the details on the above out put filtered file layout refer to File Appendix: 23 File Type: Text

Formula For: VERIZON**Denominator****Numerator**

```
SELECT
SUM(INWARD_QTY+CHNG_QTY)
WHERE STATE = '&ST&'
AND &SOUNPD&
AND &Exclusions
AND STATUS in &STATUS&
AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
AND ATC IN ('K','M','R','Y','W','X','C','S')
AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
```

```
SELECT
SUM(INWARD_QTY+CHNG_QTY)
WHERE AFLAG2 = 'D'
AND CDT <= ENDDATE
AND CDT >= STARTDATE
AND RESELL IS NULL AND TABLE VALIDATION ALGORITHM
AND FDIS >= 0700
AND FDIS <= 0999
OR FDIS >= 1200
AND FDIS <= 1399
```

TRUNKS (Aggregate)

Report Labels: PR-6-03-5000 PROVISIONING

No Standard

Guidelines: PR-6 - Installation Quality

% Inst. Troubles reported within 30 Days - FOK/TOK/CPE

Result: (Numerator / Denominator) * 100**Denominator:**

Total Lines with installation activity within the reporting month.

Numerator:

Count of Not Found, Test OK and CPE troubles with installation activity within 30 days of trouble report.

Filtered output file: FCC File Extract Def

For the details on the above out put filtered file layout refer to File Appendix: 23 File Type: Text

Formula For: CLEC**Denominator****Numerator**

```
SELECT
SUM(ACTUAL_DUR)
WHERE CDT >= STARTDATE
AND CDT <= ENDDATE
AND (( FDIS >= 0700
AND FDIS <= 0999 )
OR ( FDIS >= 1200
AND FDIS <= 1399 ))
AND I30 = 'X'
AND R30 = 'X'
```

Filtered output file: Trunking Filter Data

For the details on the above out put filtered file layout refer to File Appendix: 4 File Type: Excel

Formula For: CLEC**Denominator****Numerator**

```
SELECT
SUM(NO_WFA_TRUNKS)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND SERVICE_TYPE IN ('T', 'R')
AND ORDER_STATUS = C
```

Filtered output file: Trunking Filter Data

For the details on the above out put filtered file layout refer to File Appendix: 4 File Type: Excel

Formula For: VERIZON**Denominator****Numerator**

```
SELECT
SUM(NO_WFA_TRUNKS)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND SERVICE_TYPE IN ('I', 'W')
AND ORDER_STATUS = C
```

Guidelines For: PR-7 Jeopardy Reports

C2C Guideline:	
Definition:	The percent of orders completed or canceled identified with a jeopardy condition. Jeopardy notices will be posted twice daily on the BA Web server for a CLEC to retrieve.
Performance Standard:	95% on time in accordance with the schedule below:(footnote 27) Jeopardy Status Notification: Timeliness of notice of jeopardy of service order request where miss is known in advance of due date (missed commitment with new date/time) Resale and UNE Where the jeopardy condition is due to a lack of BA facilities and the jeopardy condition is known to BA at least 48 hours before the due date, the jeopardy notice will be given at least 48 hours before the due date. Where the jeopardy condition is due to a BA condition other than a lack of facilities and the jeopardy condition is known to BA at least 24 hours before the due date, the jeopardy notice will be given at least 24 hours before the due date. Interconnection Trunks Where the jeopardy condition is known to BA at least two days before the due date, the jeopardy notice will be given at least two days before the due date.
Exclusions:	BA Test Orders, Disconnect Orders, Bell Atlantic Administrative orders, Additional Segments on orders (parts of a whole order are included in the whole), Orders that are not complete or canceled.
Report Dimensions:	CLEC Aggregate, CLEC Specific, BA Affiliate Aggregate, BA Affiliate Specific
Geography:	State
27 If BA adopts a practice of giving Jeopardy Notices to BA Retail customers who purchase retail services that are analogous to the services covered by this metric, the standard will be "Parity with BA Retail".	

UNE (Provisioning)

Report Labels: PR-7-01-3510 Special Services Provisioning See Guidelines

Guidelines: PR-7 - Jeopardy Reports

% Orders with Jeopardy Status - EEL

Result: (Numerator / Denominator) * 100	
Denominator:	Numerator:
Total EEL orders completed or canceled	Count of EEL orders with jeopardy status

Filtered output file: ASR-UNE-SPECIAL

For the details on the above out put filtered file layout refer to File Appendix: 7 File Type: Excel

Denominator	Numerator
<pre>SELECT COUNT(*) WHERE STATE = NJ AND ACTIVITY_DATE >= STARTDATE AND ACTIVITY_DATE <= ENDDATE AND ACT IN ('N', 'C') AND PRODUCT_TYPE IN ('EEL') AND ASR_STATUS = C</pre>	<pre>SELECT COUNT(*) WHERE STATE = NJ AND ACTIVITY_DATE >= STARTDATE AND ACTIVITY_DATE <= ENDDATE AND ACT IN ('N', 'C') AND PRODUCT_TYPE IN ('EEL') AND ASR_STATUS = C AND WFA_MFC <> NULL</pre>

Guidelines For: PR-8 Open Orders in a Hold Status

C2C Guideline:	
Definition:	This metric measures the number of open orders that at the close of the reporting period have been in a hold status for more than 30 or 90 calendar days, as a percentage of orders completed in the reporting period. An "open order" is a valid order that has not been completed or canceled. Open orders in a "hold status" include: (1) open orders that have passed the originally committed completion date due to BA reasons; and, (2) open orders that have not been assigned a completion date due to BA reasons. Measurement of the 30 and 90 day intervals for open orders that have passed the originally committed completion date due to BA reasons will commence with such passed originally committed completion date (passed originally committed completion date = Day 0). Measurement of the 30 and 90 day intervals for open orders that have not been assigned a completion date due to BA reasons will commence with the application date (application date = Day 0).
Performance Standard:	Parity with BA Retail.
Exclusions:	BA Test Orders, Disconnect Orders, Bell Atlantic Administrative orders, Additional Segments on orders (parts of a whole order are included in the whole). Orders that are complete or canceled. Suspend for non-payment and associated restore orders. Orders that have passed the committed completion date, or whose completion has been delayed, due to CLEC or end user delay. Orders that at the request of the CLEC or BA Retail customer have not been assigned a completion date.
Report Dimensions:	BA Retail, CLEC Aggregate, CLEC Specific, BA Affiliate Aggregate, BA Affiliate Specific
Geography:	POTS, 2 Wire Digital Services, and 2 Wire xDSL Services: Southern, Eastern Shore, Raritan, Suburban, Hudson-Bergen Specials, EEL and IOF: State Trunks: State

RESALE (PROVISIONING)

Report Labels: PR-8-01-2100 POTS - Provisioning - Total

Parity with VZ Retail

Guidelines: PR-8 - Open Orders in a Hold Status

% Open Orders in a Hold Status > 30 Days

Result: (Numerator / Denominator) * 100**Denominator:**

Total number of orders completed in the reporting period

Numerator:

Number of open orders that at the close of the reporting period have been in a hold status for more than 90 days

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RSPS&
      AND &Exclusions
      AND &STATUS8&
      AND COMPANY_MAC_DAYS > 3
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' ))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      and trunc(load_date) - due > 30
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND NVL(CISR_MAC,1) not in
('SA','SC','SE','SL','SO','SP','SR')

```

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RSPS&
      AND &Exclusions
      AND &STATUS8&
      AND COMPANY_MAC_DAYS > 3
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' ))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      and trunc(load_date) - due > 30
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND NVL(CISR_MAC,1) not in
('SA','SC','SE','SL','SO','SP','SR')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RTPS&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RTPS&
      AND &RetailExclusions
      AND &STATUS8&
      AND COMPANY_MAC_DAYS > 3
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      and trunc(load_date) - due > 30
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND NVL(CISR_MAC,1) not in
('SA','SC','SE','SL','SO','SP','SR')

```

RESALE (PROVISIONING)

Report Labels: PR-8-01-2200 Special Services - Provisioning

Parity with VZ Retail

Guidelines: PR-8 - Open Orders in a Hold Status

% Open Orders in a Hold Status > 30 Days

Result: (Numerator / Denominator) * 100**Denominator:**

Total number of orders completed in the reporting period

Numerator:

Number of open orders that at the close of the reporting period have been in a hold status for more than 90 days

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RSSS&
      AND &Exclusions
      AND &STATUS8&
      AND COMPANY_MAC_DAYS > 3
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' ))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      and trunc(load_date) - due > 30
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND NVL(CISR_MAC,1) not in
('SA','SC','SE','SL','SO','SP','SR')

```

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RSSS&
      AND &Exclusions&
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0
or INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0
or INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I'))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RSSS&
      AND &Exclusions
      AND &STATUS8&
      AND COMPANY_MAC_DAYS > 3
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' ))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      and trunc(load_date) - due > 30
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND NVL(CISR_MAC,1) not in
('SA','SC','SE','SL','SO','SP','SR')

```

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RSSS&
      AND &Exclusions&
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0
or INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0
or INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I'))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

RESALE (PROVISIONING)

Report Labels: PR-8-01-2341

Complex Services - 2 Wire Digital

Parity with VZ Retail

Guidelines: PR-8 - Open Orders in a Hold Status

% Open Orders in a Hold Status > 30 Days

Result: (Numerator / Denominator) * 100**Denominator:**

Total number of orders completed in the reporting period

Numerator:

Number of open orders that at the close of the reporting period have been in a hold status for more than 90 days

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RSPI&
      AND &Exclusions
      AND &STATUS8&
      AND COMPANY_MAC_DAYS > 3
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' ))
      AND ATC IN ('K','M','R','Y','W','X','C','S'
      and trunc(load_date) - due > 30
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND NVL(CISR_MAC,1) not in
('SA','SC','SE','SL','SO','SP','SR')

```

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RSPI&
      AND &Exclusions
      AND &STATUS8&
      AND COMPANY_MAC_DAYS > 3
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' ))
      AND ATC IN ('K','M','R','Y','W','X','C','S'
      and trunc(load_date) - due > 30
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND NVL(CISR_MAC,1) not in
('SA','SC','SE','SL','SO','SP','SR')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RTPI&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RTPI&
      AND &RetailExclusions
      AND &STATUS8&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND COMPANY_MAC_DAYS > 3
      AND ATC IN ('K','M','R','Y','W','X','C','S'
      and trunc(load_date) - due > 30
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND NVL(CISR_MAC,1) not in
('SA','SC','SE','SL','SO','SP','SR')

```


RESALE (PROVISIONING)

Report Labels: PR-8-01-2342

Complex Services - 2 Wire xDSL

Parity with VZ Retail

Guidelines: PR-8 - Open Orders in a Hold Status

% Open Orders in a Hold Status > 30 Days

Result: (Numerator / Denominator) * 100**Denominator:**

Total number of orders completed in the reporting period

Numerator:

Number of open orders that at the close of the reporting period have been in a hold status for more than 90 days

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RSPD&
      AND &Exclusions
      AND &STATUS8&
      AND COMPANY_MAC_DAYS > 3
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' ))
      AND ATC IN ('K','M','R','Y','W','X','C','S'
      and trunc(load_date) - due > 30
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND NVL(CISR_MAC,1) not in
('SA','SC','SE','SL','SO','SP','SR')

```

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RSPD&
      AND &Exclusions
      AND &STATUS8&
      AND COMPANY_MAC_DAYS > 3
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' ))
      AND ATC IN ('K','M','R','Y','W','X','C','S'
      and trunc(load_date) - due > 30
      AND NVL(SELLER_NAME,0) NOT IN
(&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND NVL(CISR_MAC,1) not in
('SA','SC','SE','SL','SO','SP','SR')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RTPD&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RTPD&
      AND &RetailExclusions
      AND &STATUS8&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND COMPANY_MAC_DAYS > 3
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      and trunc(load_date) - due > 30
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND NVL(CISR_MAC,1) not in
('SA','SC','SE','SL','SO','SP','SR')

```

UNE (Provisioning)

Report Labels: PR-8-01-3100 POTS - Provisioning

Parity with VZ Retail

Guidelines: PR-8 - Open Orders in a Hold Status

% Open Orders in a Hold Status > 30 Days

Result: (Numerator / Denominator) * 100**Denominator:**

Total number of orders completed in the reporting period

Numerator:

Number of open orders that at the close of the reporting period have been in a hold status for more than 90 days

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &SOUNPS&
      AND &Exclusions
      AND &STATUS&
      AND COMPANY_MAC_DAYS > 3
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND nvl(ATC,0) IN ('K','M','R','Y','W','X','C','S')
      and trunc(load_date) - due > 30
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND NVL(CISR_MAC,1) not in
('SA','SC','SE','SL','SO','SP','SR')

```

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &SOUNPS&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (
(ATC IN ('K','M','R','Y','W','X','C','S') AND ((TYPE IN ('N','T')) or
(TYPE in 'C' and (OUT_QTY=0 or INWARD_QTY>0 or
CHNG_QTY>0) and (OUTWARD_CKL=0 or INWARD_CKL>0 or
CHNG_CKL>0))))
or (type in ('R') and PON is not null and cls in ('RRM','RBM')) )
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &SOUNPS&
      AND &Exclusions
      AND &STATUS&
      AND COMPANY_MAC_DAYS > 3
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND nvl(ATC,0) IN ('K','M','R','Y','W','X','C','S')
      and trunc(load_date) - due > 30
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND NVL(CISR_MAC,1) not in
('SA','SC','SE','SL','SO','SP','SR')

```

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &SOUNPS&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (
(ATC IN ('K','M','R','Y','W','X','C','S') AND ((TYPE IN ('N','T')) or
(TYPE in 'C' and (OUT_QTY=0 or INWARD_QTY>0 or
CHNG_QTY>0) and (OUTWARD_CKL=0 or INWARD_CKL>0 or
CHNG_CKL>0))))
or (type in ('R') and PON is not null and cls in ('RRM','RBM')) )
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

UNE (Provisioning)

Report Labels: PR-8-01-3200 Special Services Provisioning Parity with VZ Retail

Guidelines: PR-8 - Open Orders in a Hold Status

% Open Orders in a Hold Status > 30 Days

Result: (Numerator / Denominator) * 100

Denominator:	Numerator:
Total number of orders completed in the reporting period	Number of open orders that at the close of the reporting period have been in a hold status for more than 90 days

Filtered output file: ASR-UNE-SPECIAL

For the details on the above out put filtered file layout refer to File Appendix: 7 File Type: Excel

Denominator	Numerator
<div>SELECT COUNT(*) WHERE STATE = NJ AND ACTIVITY_DATE >= STARTDATE AND ACTIVITY_DATE <= ENDDATE AND ASR_STATUS = C AND PRODUCT_TYPE IN ('DS1', 'DS3') AND ACT IN ('N', 'C')</div>	<div>SELECT COUNT(*) WHERE STATE = NJ AND ACTIVITY_DATE >= STARTDATE AND ACTIVITY_DATE <= ENDDATE AND ACTIVITY_DT > DD + 30 AND NVL(SUBSTR(WFA_MFC,1,1),'X') NOT IN ('C', 'D') AND ASR_STATUS = P AND PRODUCT_TYPE IN ('DS1', 'DS3') AND ACT IN ('N', 'C')</div>

UNE (Provisioning)

Report Labels: PR-8-01-3341

Complex Services - 2 Wire Digital

Parity with VZ Retail

Guidelines: PR-8 - Open Orders in a Hold Status

% Open Orders in a Hold Status > 30 Days

Result: (Numerator / Denominator) * 100**Denominator:**

Total number of orders completed in the reporting period

Numerator:

Number of open orders that at the close of the reporting period have been in a hold status for more than 90 days

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &SOUNPI&
      AND &Exclusions
      AND &STATUS8&
      AND COMPANY_MAC_DAYS > 3
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      and trunc(load_date) - due > 30
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND NVL(CISR_MAC,1) not in
('SA','SC','SE','SL','SO','SP','SR')

```

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &SOUNPI&
      AND &Exclusions
      AND &STATUS8&
      AND COMPANY_MAC_DAYS > 3
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      and trunc(load_date) - due > 30
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND NVL(CISR_MAC,1) not in
('SA','SC','SE','SL','SO','SP','SR')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RTPI&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RTPI&
      AND &RetailExclusions
      AND &STATUS8&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND COMPANY_MAC_DAYS > 3
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      and trunc(load_date) - due > 30
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND NVL(CISR_MAC,1) not in
('SA','SC','SE','SL','SO','SP','SR')

```

UNE (Provisioning)

Report Labels: PR-8-01-3342

Complex Services - 2 Wire xDSL

Parity with VZ Retail

Guidelines: PR-8 - Open Orders in a Hold Status

% Open Orders in a Hold Status > 30 Days

Result: (Numerator / Denominator) * 100**Denominator:**

Total number of orders completed in the reporting period

Numerator:

Number of open orders that at the close of the reporting period have been in a hold status for more than 90 days

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &SOUNPD&
      AND &Exclusions
      AND &STATUS8&
      AND COMPANY_MAC_DAYS > 3
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      and trunc(load_date) - due > 30
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND NVL(CISR_MAC,1) not in
('SA','SC','SE','SL','SO','SP','SR')

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &SOUNPD&
      AND &Exclusions
      AND &STATUS8&
      AND COMPANY_MAC_DAYS > 3
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      and trunc(load_date) - due > 30
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND NVL(CISR_MAC,1) not in
('SA','SC','SE','SL','SO','SP','SR')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RTPD&
      AND &RetailExclusions
      AND STATUS in &STATUS8&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPD&
      AND &RetailExclusions
      AND &STATUS8&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND COMPANY_MAC_DAYS > 3
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      and trunc(load_date) - due > 30
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND NVL(CISR_MAC,1) not in
('SA','SC','SE','SL','SO','SP','SR')

```

UNE (Provisioning)

Report Labels: PR-8-01-3510 Special Services Provisioning Parity with VZ Retail

Guidelines: PR-8 - Open Orders in a Hold Status

% Open Orders in a Hold Status > 30 Days - EEL

Result: (Numerator / Denominator) * 100

Denominator:	Numerator:
Total number of orders completed in the reporting period	Number of open orders that at the close of the reporting period have been in a hold status for more than 90 days

Filtered output file: ASR-UNE-SPECIAL

For the details on the above out put filtered file layout refer to File Appendix: 7 File Type: Excel

Denominator	Numerator
<div>SELECT COUNT(*) WHERE STATE = NJ AND ACTIVITY_DATE >= STARTDATE AND ACTIVITY_DATE <= ENDDATE AND PRODUCT_TYPE = EEL AND ASR_STATUS = C AND ACT IN ('N', 'C')</div>	<div>SELECT COUNT(*) WHERE STATE = NJ AND ACTIVITY_DATE >= STARTDATE AND ACTIVITY_DATE <= ENDDATE AND PRODUCT_TYPE = EEL AND ACTIVITY_DT > DD + 30 AND NVL(SUBSTR(WFA_MFC,1,1),'X') NOT IN ('C', 'D') AND ASR_STATUS = P AND ACT IN ('N', 'C')</div>

UNE (Provisioning)

Report Labels: PR-8-01-3530 Special Services Provisioning Parity with VZ Retail

Guidelines: PR-8 - Open Orders in a Hold Status

% Open Orders in a Hold Status > 30 Days - IOF

Result: (Numerator / Denominator) * 100

Denominator:	Numerator:
Total number of orders completed in the reporting period	Number of open orders that at the close of the reporting period have been in a hold status for more than 90 days

Filtered output file: ASR-UNE-SPECIAL

For the details on the above out put filtered file layout refer to File Appendix: 7 File Type: Excel

Denominator	Numerator
<div>SELECT COUNT(*) WHERE STATE = NJ AND ACTIVITY_DATE >= STARTDATE AND ACTIVITY_DATE <= ENDDATE AND ASR_STATUS = C AND PRODUCT_TYPE = IOF AND ACT IN ('N', 'C')</div>	<div>SELECT COUNT(*) WHERE STATE = NJ AND ACTIVITY_DATE >= STARTDATE AND ACTIVITY_DATE <= ENDDATE AND ACTIVITY_DT > DD + 30 AND NVL(SUBSTR(WFA_MFC,1,1),'X') NOT IN ('C', 'D') AND ASR_STATUS = P AND PRODUCT_TYPE = IOF AND ACT IN ('N', 'C')</div>

TRUNKS (Aggregate)

Report Labels: PR-8-01-5000

PROVISIONING

Parity with IXC / FGD

Guidelines: PR-8 - Average Days Held on Pending Orders

% Open Orders in a Hold Status > 30 Days

Result: (Numerator / Denominator) * 100**Denominator:**

Total number of orders completed in the reporting period

Numerator:

Number of open orders that at the close of the reporting period have been in a hold status for more than 90 days

Filtered output file: Trunking Filter Data

For the details on the above out put filtered file layout refer to File Appendix: 4 File Type: Excel

Formula For: CLEC**Denominator**

```
SELECT
SUM(NO_WFA_TRUNKS)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND SERVICE_TYPE IN ('T', 'R')
AND ORDER_STATUS = C
```

Numerator

```
SELECT
SUM(NO_WFA_TRUNKS)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND SERVICE_TYPE IN ('T', 'R')
AND ORDER_STATUS = P
AND WFA_DDOBJ <
TO_DATE(ACTIVITY_DATE,'YYYYMMDD') - 30
AND CNR_YN = N
```

Filtered output file: Trunking Filter Data

For the details on the above out put filtered file layout refer to File Appendix: 4 File Type: Excel

Formula For: VERIZON**Denominator**

```
SELECT
SUM(NO_WFA_TRUNKS)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND SERVICE_TYPE IN ('I', 'W')
AND ORDER_STATUS = C
```

Numerator

```
SELECT
SUM(NO_WFA_TRUNKS)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND SERVICE_TYPE IN ('I', 'W')
AND ORDER_STATUS = P
AND WFA_DDOBJ <
TO_DATE(ACTIVITY_DATE,'YYYYMMDD') - 30
AND CNR_YN = N
```


RESALE (PROVISIONING)

Report Labels: PR-8-02-2100 POTS - Provisioning - Total

Parity with VZ Retail

Guidelines: PR-8 - Open Orders in a Hold Status

% Open Orders in a Hold Status > 90 Days

Result: (Numerator / Denominator) * 100**Denominator:**

Total number of orders completed in the reporting period

Numerator:

Number of open orders that at the close of the reporting period have been in a hold status for more than 90 days

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RSPS&
      AND &Exclusions
      AND &STATUS8&
      AND COMPANY_MAC_DAYS > 9
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' ))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      and trunc(load_date) - due > 90
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND NVL(CISR_MAC,1) not in
('SA','SC','SE','SL','SO','SP','SR')

```

Numerator

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RSPS&
      AND &Exclusions
      AND &STATUS8&
      AND COMPANY_MAC_DAYS > 9
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' ))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      and trunc(load_date) - due > 90
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND NVL(CISR_MAC,1) not in
('SA','SC','SE','SL','SO','SP','SR')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RTPS&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Numerator

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RTPS&
      AND &RetailExclusions
      AND STATUS8&
      AND COMPANY_MAC_DAYS > 9
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      and trunc(load_date) - due > 90
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND NVL(CISR_MAC,1) not in
('SA','SC','SE','SL','SO','SP','SR')

```

RESALE (PROVISIONING)

Report Labels: PR-8-02-2200 Special Services - Provisioning Parity with VZ Retail

Guidelines: PR-8 - Open Orders in a Hold Status

% Open Orders in a Hold Status > 90 Days

Result: (Numerator / Denominator) * 100	
Denominator:	Numerator:
Total number of orders completed in the reporting period	Number of open orders that at the close of the reporting period have been in a hold status for more than 90 days

Filtered output file: Service Order Record Data Layout
For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON

Denominator Numerator

RESALE (PROVISIONING)

Report Labels: PR-8-02-2341

Complex Services - 2 Wire Digital

Parity with VZ Retail

Guidelines: PR-8 - Open Orders in a Hold Status

% Open Orders in a Hold Status > 90 Days

Result: (Numerator / Denominator) * 100**Denominator:**

Total number of orders completed in the reporting period

Numerator:

Number of open orders that at the close of the reporting period have been in a hold status for more than 90 days

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RSPI&
      AND &Exclusions
      AND &STATUS8&
      AND COMPANY_MAC_DAYS > 9
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' ))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      and trunc(load_date) - due > 90
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND NVL(CISR_MAC,1) not in
('SA','SC','SE','SL','SO','SP','SR')

```

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RSPI&
      AND &Exclusions
      AND &STATUS8&
      AND COMPANY_MAC_DAYS > 9
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' ))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      and trunc(load_date) - due > 90
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND NVL(CISR_MAC,1) not in
('SA','SC','SE','SL','SO','SP','SR')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RTPI&
      AND &RetailExclusions
      AND STATUS in &STATUS&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RTPI&
      AND &RetailExclusions
      AND &STATUS8&
      AND COMPANY_MAC_DAYS > 9
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      and trunc(load_date) - due > 90
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND NVL(CISR_MAC,1) not in
('SA','SC','SE','SL','SO','SP','SR')

```

RESALE (PROVISIONING)

Report Labels: PR-8-02-2342 Complex Services - 2 Wire xDSL

Parity with VZ Retail

Guidelines: PR-8 - Open Orders in a Hold Status

% Open Orders in a Hold Status > 90 Days

Result: (Numerator / Denominator) * 100**Denominator:**

Total number of orders completed in the reporting period

Numerator:

Number of open orders that at the close of the reporting period have been in a hold status for more than 90 days

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RSPD&
      AND &Exclusions
      AND &STATUS8&
      AND COMPANY_MAC_DAYS > 9
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' ))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      and trunc(load_date) - due > 90
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND NVL(CISR_MAC,1) not in
('SA','SC','SE','SL','SO','SP','SR')

```

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RSPD&
      AND &Exclusions
      AND &STATUS8&
      AND COMPANY_MAC_DAYS > 9
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)) or (TYPE ='R' and
RESELLER_ACT='I' ))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      and trunc(load_date) - due > 90
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND NVL(CISR_MAC,1) not in
('SA','SC','SE','SL','SO','SP','SR')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RTPD&
      AND &RetailExclusions
      AND &STATUS8&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RTPD&
      AND &RetailExclusions
      AND &STATUS8&
      AND COMPANY_MAC_DAYS > 9
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      and trunc(load_date) - due > 90
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND NVL(CISR_MAC,1) not in
('SA','SC','SE','SL','SO','SP','SR')

```

UNE (Provisioning)

Report Labels: PR-8-02-3100 POTS - Provisioning

Parity with VZ Retail

Guidelines: PR-8 - Open Orders in a Hold Status

% Open Orders in a Hold Status > 90 Days

Result: (Numerator / Denominator) * 100**Denominator:**

Total number of orders completed in the reporting period

Numerator:

Number of open orders that at the close of the reporting period have been in a hold status for more than 90 days

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &SOUNPS&
      AND &Exclusions
      AND &STATUS&
      AND COMPANY_MAC_DAYS > 9
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND nvl(ATC,0) IN ('K','M','R','Y','W','X','C','S')
      and trunc(load_date) - due > 90
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND NVL(CISR_MAC,1) not in
('SA','SC','SE','SL','SO','SP','SR')

```

Numerator

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &SOUNPS&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (
(ATC IN ('K','M','R','Y','W','X','C','S') AND ((TYPE IN ('N','T')) or
(TYPE in 'C' and (OUT_QTY=0 or INWARD_QTY>0 or
CHNG_QTY>0) and (OUTWARD_CKL=0 or INWARD_CKL>0 or
CHNG_CKL>0))))
or (type in ('R') and PON is not null and cls in ('RRM','RBM')) )
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &SOUNPS&
      AND &Exclusions
      AND &STATUS&
      AND COMPANY_MAC_DAYS > 9
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND nvl(ATC,0) IN ('K','M','R','Y','W','X','C','S')
      and trunc(load_date) - due > 90
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND NVL(CISR_MAC,1) not in
('SA','SC','SE','SL','SO','SP','SR')

```

Numerator

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &SOUNPS&
      AND &Exclusions
      AND STATUS in &STATUS&
      AND (
(ATC IN ('K','M','R','Y','W','X','C','S') AND ((TYPE IN ('N','T')) or
(TYPE in 'C' and (OUT_QTY=0 or INWARD_QTY>0 or
CHNG_QTY>0) and (OUTWARD_CKL=0 or INWARD_CKL>0 or
CHNG_CKL>0))))
or (type in ('R') and PON is not null and cls in ('RRM','RBM')) )
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,''),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

UNE (Provisioning)

Report Labels: PR-8-02-3200 Special Services Provisioning Parity with VZ Retail

Guidelines: PR-8 - Open Orders in a Hold Status

% Open Orders in a Hold Status > 90 Days

Result: (Numerator / Denominator) * 100	
Denominator:	Numerator:
Total number of orders completed in the reporting period	Number of open orders that at the close of the reporting period have been in a hold status for more than 90 days

Filtered output file: ASR-UNE-SPECIAL
For the details on the above out put filtered file layout refer to File Appendix: 7 File Type: Excel

Denominator	Numerator
<pre>SELECT COUNT(*) WHERE STATE = NJ AND ACTIVITY_DATE >= STARTDATE AND PRODUCT_TYPE IN ('DS1', 'DS3') AND ACTIVITY_DATE <= ENDDATE AND ASR_STATUS = C</pre>	<pre>SELECT COUNT(*) WHERE STATE = NJ AND ACTIVITY_DATE >= STARTDATE AND PRODUCT_TYPE IN ('DS1', 'DS3') AND ACTIVITY_DATE <= ENDDATE AND ACTIVITY_DT > DD + 90 AND NVL(SUBSTR(WFA_MFC,1,1),'X') NOT IN ('C', 'D') AND ASR_STATUS = P</pre>

UNE (Provisioning)

Report Labels: PR-8-02-3341

Complex Services - 2 Wire Digital

Parity with VZ Retail

Guidelines: PR-8 - Open Orders in a Hold Status

% Open Orders in a Hold Status > 90 Days

Result: (Numerator / Denominator) * 100**Denominator:**

Total number of orders completed in the reporting period

Numerator:

Number of open orders that at the close of the reporting period have been in a hold status for more than 90 days

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator**

```
SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &SOUNPI&
      AND &Exclusions
      AND &STATUS8&
      AND COMPANY_MAC_DAYS > 9
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      and trunc(load_date) - due > 90
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND NVL(CISR_MAC,1) not in
('SA','SC','SE','SL','SO','SP','SR')
```

Numerator

```
SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &SOUNPI&
      AND &Exclusions
      AND &STATUS8&
      AND COMPANY_MAC_DAYS > 9
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      and trunc(load_date) - due > 90
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND NVL(CISR_MAC,1) not in
('SA','SC','SE','SL','SO','SP','SR')
```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator**

```
SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RTPI&
      AND &RetailExclusions
      AND STATUS in &STATUS8&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
```

Numerator

```
SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RTPI&
      AND &RetailExclusions
      AND &STATUS8&
      AND COMPANY_MAC_DAYS > 9
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      and trunc(load_date) - due > 90
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND NVL(CISR_MAC,1) not in
('SA','SC','SE','SL','SO','SP','SR')
```

UNE (Provisioning)

Report Labels: PR-8-02-3342

Complex Services - 2 Wire xDSL

Parity with VZ Retail

Guidelines: PR-8 - Open Orders in a Hold Status

% Open Orders in a Hold Status > 90 Days

Result: (Numerator / Denominator) * 100**Denominator:**

Total number of orders completed in the reporting period

Numerator:

Number of open orders that at the close of the reporting period have been in a hold status for more than 90 days

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: CLEC**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &SOUNPD&
      AND &Exclusions
      AND &STATUS8&
      AND COMPANY_MAC_DAYS > 9
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      and trunc(load_date) - due > 90
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND NVL(CISR_MAC,1) not in
('SA','SC','SE','SL','SO','SP','SR')

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &SOUNPD&
      AND &Exclusions
      AND &STATUS8&
      AND COMPANY_MAC_DAYS > 9
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      and trunc(load_date) - due > 90
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND NVL(CISR_MAC,1) not in
('SA','SC','SE','SL','SO','SP','SR')

```

Filtered output file: Service Order Record Data Layout

For the details on the above out put filtered file layout refer to File Appendix: 22 File Type: Fixed Text

Formula For: VERIZON**Denominator****Numerator**

```

SELECT
count(order_num)
WHERE STATE = '&ST&'
      AND &RTPD&
      AND &RetailExclusions
      AND STATUS in &STATUS8&
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')

```

```

SELECT
COUNT(ORDER_NUM)
WHERE STATE = '&ST&'
      AND &RTPD&
      AND &RetailExclusions
      AND &STATUS8&
      AND COMPANY_MAC_DAYS > 9
      AND (TYPE IN ('N','T') or (TYPE in 'C' and (OUT_QTY=0 or
INWARD_QTY>0 or CHNG_QTY>0) and (OUTWARD_CKL=0 or
INWARD_CKL>0 or CHNG_CKL>0)))
      AND ATC IN ('K','M','R','Y','W','X','C','S')
      and trunc(load_date) - due > 90
      AND NVL(SELLER_NAME,0) NOT IN (&TEST_SELLERS&)
      AND SUBSTR(NVL(SWO_CODE,**),1,1)<>'O'
      AND NVL(CLS,0) NOT IN
('DB2','DB5','MMS','MUZ','SU2','ZZO')
      AND NVL(CISR_MAC,1) not in
('SA','SC','SE','SL','SO','SP','SR')

```


UNE (Provisioning)

Report Labels: PR-8-02-3510 Special Services Provisioning Parity with VZ Retail

Guidelines: PR-8 - Open Orders in a Hold Status

% Open Orders in a Hold Status > 90 Days - EEL

Result: (Numerator / Denominator) * 100	
Denominator:	Numerator:
Total number of orders completed in the reporting period	Number of open orders that at the close of the reporting period have been in a hold status for more than 90 days

Filtered output file: ASR-UNE-SPECIAL

For the details on the above out put filtered file layout refer to File Appendix: 7 File Type: Excel

Denominator	Numerator
<pre>SELECT COUNT(*) WHERE STATE = NJ AND ACTIVITY_DATE >= STARTDATE AND ACTIVITY_DATE <= ENDDATE AND ASR_STATUS = C AND PRODUCT_TYPE IN EEL AND ACT IN ('N', 'C')</pre>	<pre>SELECT COUNT(*) WHERE STATE = NJ AND ACTIVITY_DATE >= STARTDATE AND ACTIVITY_DATE <= ENDDATE AND ACTIVITY_DT > DD + 90 AND NVL(SUBSTR(WFA_MFC,1,1),'X') NOT IN ('C', 'D') AND ASR_STATUS = P AND PRODUCT_TYPE IN EEL AND ACT IN ('N', 'C')</pre>

UNE (Provisioning)

Report Labels: PR-8-02-3530 Special Services Provisioning Parity with VZ Retail

Guidelines: PR-8 - Open Orders in a Hold Status

% Open Orders in a Hold Status > 90 Days - IOF

Result: (Numerator / Denominator) * 100	
Denominator:	Numerator:
Total number of orders completed in the reporting period	Number of open orders that at the close of the reporting period have been in a hold status for more than 90 days

Filtered output file: ASR-UNE-SPECIAL
For the details on the above out put filtered file layout refer to File Appendix: 7 File Type: Excel

Denominator	Numerator
<pre>SELECT COUNT(*) WHERE STATE = NJ AND ACTIVITY_DATE >= STARTDATE AND ACTIVITY_DATE <= ENDDATE AND ASR_STATUS = C AND PRODUCT_TYPE IN IOF AND ACT IN ('N', 'C')</pre>	<pre>SELECT COUNT(*) WHERE STATE = NJ AND ACTIVITY_DATE >= STARTDATE AND ACTIVITY_DATE <= ENDDATE AND ACTIVITY_DT > DD + 90 AND NVL(SUBSTR(WFA_MFC,1,1),'X') NOT IN ('C', 'D') AND ASR_STATUS = P AND PRODUCT_TYPE IN IOF AND ACT IN ('N', 'C')</pre>

TRUNKS (Aggregate)

Report Labels: PR-8-02-5000

PROVISIONING

Parity with IXC / FGD

Guidelines: PR-8 - Average Days Held on Pending Orders

% Open Orders in a Hold Status > 90 Days

Result: (Numerator / Denominator) * 100**Denominator:**

Total number of orders completed in the reporting period

Numerator:

Number of open orders that at the close of the reporting period have been in a hold status for more than 90 days

Filtered output file: Trunking Filter Data

For the details on the above out put filtered file layout refer to File Appendix: 4 File Type: Excel

Formula For: CLEC**Denominator**

```
SELECT
SUM(NO_WFA_TRUNKS)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND SERVICE_TYPE IN ('T' 'R')
AND ORDER_STATUS = C
```

Numerator

```
SELECT
SUM(NO_WFA_TRUNKS)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND SERVICE_TYPE IN ('T' 'R')
AND ORDER_STATUS = P
AND WFA_DDOBJ <
TO_DATE(ACTIVITY_DATE,'YYYYMMDD') - 90
AND CNR_YN = N
```

Filtered output file: Trunking Filter Data

For the details on the above out put filtered file layout refer to File Appendix: 4 File Type: Excel

Formula For: VERIZON**Denominator**

```
SELECT
SUM(NO_WFA_TRUNKS)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND SERVICE_TYPE IN ('I' 'W')
AND ORDER_STATUS = C
```

Numerator

```
SELECT
SUM(NO_WFA_TRUNKS)
WHERE STATE = NJ
AND ACTIVITY_DATE >= STARTDATE
AND ACTIVITY_DATE <= ENDDATE
AND SERVICE_TYPE IN ('I' 'W')
AND ORDER_STATUS = P
AND WFA_DDOBJ <
TO_DATE(ACTIVITY_DATE,'YYYYMMDD') - 90
AND CNR_YN = N
```

Guidelines For: PR-9 Hot Cut Loops

C2C Guideline:

Definition:

BA calculates On Time Performance for LNP and Hot Cuts using WFA. Time stamps for framework start and stop times and translation start and stop times will be used to ensure work is completed according to prescribed requirements. Two work types are used in WFA-DI NDSUB - for pre-wire and testing CLEC dial-tone on DD-2 NDSCT - for performing "hot cut" on DD Note: Separate work requests will be created for RCMAC. The work requests include combined order number, lead CKID, number of ckts/segments, NPA-NXX, commitment date & time. A Hot Cut is considered complete when one of the following occurs: 1. BA performs the hot cut, notifies the CLEC by telephone, and the CLEC accepts the hot cut and issues a serial number (or index number); or 2. BA performs the hot-cut, notifies the CLEC by telephone, but the CLEC does not accept the hot cut, or report a trouble, within one hour of notification and has not specifically requested, within the hour, more time to test; or 3. BA performs the hot cut, attempts to notify the CLEC by telephone but receives no answer and leaves a phone message, and the CLEC does not respond within one hour of the message.(footnote 28) For Metrics PR-9-02, 03, 06 and 07, orders are measured for the month in which they are completed. For Metrics PR-9-01, 04, 05, 08 and 09, orders are measured for the month in which they are (a) completed, or (b) cancelled by the CLEC.

Performance Standard: Metric PR-9-01: 95% completed within Cut-Over Window. Cut-Over Window: Amount of time from start to completion of physical cut-over of lines: 1 to 9 lines: 1 Hour 10 to 49 lines: 2 Hours 50 to 99 lines: 3 Hours 100 to 199 lines: 4 Hours 200 or more lines: 8 Hours If IDLC is involved - 4 Hour Window (8AM to 12 Noon or 1PM to 5PM) applies to start time.(footnote 29) Metrics PR-9-02 through PR-9-09: No Standard.

Exclusions: BA Test Orders., Bell Atlantic Administrative orders, Additional Segments on orders (parts of a whole order are included in the whole). If a CLEC cancels an order before the start of a hot cut window and BA performs the hot cut, this BA error will result in a retail trouble report and need not be reflected elsewhere. Metric PR-9-09: Hot Cuts where no dial tone was found on the DD-2 test and the CLEC was notified of the problem. Hot Cuts where dial tone was found on the DD-2 test and was not present on the due date.

Report Dimensions: CLEC Aggregate, CLEC Specific, BA Affiliate Aggregate, BA Affiliate Specific

Geography: POTS: Southern, Eastern Shore, Raritan, Suburban, Hudson-Bergen

28 If BA adopts a practice of giving Jeopardy Notices to BA Retail customers who purchase retail services that are analogous to the services covered by this metric, the standard will be "Parity with BA Retail".

29 Only applicable if BA notified CLEC by 2:30 PM Eastern Time on DD-2 that the service was on IDLC.

UNE (Provisioning)

Report Labels:

PR-9-01-3114

POTS - Provisioning

95% w/in cut over window

Guidelines:

PR-9 - Hot Cuts

% On Time Performance - Hot Cuts

Result: (Numerator / Denominator) * 100

Denominator: Count of hot cut (coordinated loop) orders completed.	Numerator: Count of Hot Cut (coordinated loop) orders (with or without number portability) completed within commitment window (as scheduled on order) on due date.
--	--

Filtered output file: Order Detail

For the details on the above out put filtered file layout refer to File Appendix: 41 File Type: Excel

Formula For: VERIZON

Denominator	Numerator
<div>SELECT COUNT(#ORDS) WHERE STATE = NJ</div>	<div>SELECT COUNT(#ORDS) WHERE STATE = NJ AND MET = "Y"</div>

UNE (Provisioning)

Report Labels:

PR-9-02-3520

POTS - Provisioning

No Standard

Guidelines:

PR-9 - Hot Cuts

% Early Cuts - Lines

Result: (Numerator / Denominator) * 100

Denominator:	Numerator:
Count of Hot Cut lines completed	Count of Hot Cut (coordinated loop) lines (with or without number portability) cut before frame due time.

Filtered output file: Order Detail

For the details on the above out put filtered file layout refer to File Appendix: 41 File Type: Excel

Formula For: CLEC

Denominator	Numerator
<div>SELECT COUNT(# OF LPS) WHERE STATE = NJ AND UT TICKET COMP DATE,UT TICKET COMP TIME < FDT</div>	<div>SELECT COUNT(*) WHERE STATE = NJ AND UT TICKET COMP DATE,UT TICKET COMP TIME < FDT</div>

UNE (Provisioning)

Report Labels:

PR-9-03-3520

POTS - Provisioning

No Standard

Guidelines:

PR-9 - Hot Cuts

% Early Cuts - Orders

Result: (Numerator / Denominator) * 100

Denominator:	Numerator:
Count of Hot Cut orders completed	Count of Hot Cut (coordinated loop) orders with lines (with or without number portability) cut before frame due time.

Filtered output file: Order Detail

For the details on the above out put filtered file layout refer to File Appendix: 41 File Type: Excel

Formula For: VERIZON

Denominator	Numerator
<div>SELECT COUNT(#ORDS) WHERE STATE = NJ AND UT TICKET COMP DATE,UT TICKET COMP TIME < FDT</div>	<div>SELECT COUNT(*) WHERE STATE = NJ AND UT TICKET COMP DATE,UT TICKET COMP TIME < FDT</div>

UNE (Provisioning)

Report Labels: PR-9-04-3520 POTS - Provisioning No Standard

Guidelines: PR-9 - Hot Cuts

% Defective Cuts - Lines

Result: (Numerator / Denominator) * 100

Denominator:	Numerator:
Count of Hot Cut lines completed	Count of Hot Cut (coordinated loop) lines with troubles reported by CLEC following notification of completion but before acceptance.

Filtered output file: Order Detail

For the details on the above out put filtered file layout refer to File Appendix: 41 File Type: Excel

Formula For: VERIZON

Denominator	Numerator
SELECT COUNT(# OF LPS) WHERE STATE = NJ	SELECT COUNT(# OF LPS) WHERE STATE = NJ

UNE (Provisioning)

Report Labels:

PR-9-05-3520

POTS - Provisioning

No Standard

Guidelines:

PR-9 - Hot Cuts

% Defective Cuts - Orders

Result: (Numerator / Denominator) * 100

Denominator: Count of Hot Cut (coordinated loop) orders with lines with troubles reported by CLEC following notification of completion but before acceptance.	Numerator: Count of Hot Cut (coordinated loop) orders with lines with troubles reported by CLEC following notification of completion but before acceptance.
---	---

Filtered output file: Order Detail

For the details on the above out put filtered file layout refer to File Appendix: 41 File Type: Excel

Formula For: VERIZON

Denominator	Numerator
<div>SELECT COUNT#ORDS) WHERE STATE = NJ</div>	<div>SELECT COUNT(#ORDS) WHERE STATE = NJ</div>

UNE (Provisioning)

Report Labels: PR-9-06-3520 POTS - Provisioning No Standard

Guidelines: PR-9 - Hot Cuts

% Late Cuts - Lines

Result: (Numerator / Denominator) * 100

Denominator:	Numerator:
Count of Hot Cut lines completed	Count of Hot Cut (coordinated loop) lines cut more than 30 minutes after the cut-over window (includes time for notification to CLEC)

Filtered output file: Order Detail

For the details on the above out put filtered file layout refer to File Appendix: 41 File Type: Excel

Formula For: VERIZON

Denominator	Numerator
SELECT COUNT(# OF LPS) WHERE STATE = NJ	SELECT COUNT(# OF LPS) WHERE STATE = NJ AND MET = N

UNE (Provisioning)

Report Labels:

PR-9-07-3520

POTS - Provisioning

No Standard

Guidelines:

PR-9 - Hot Cuts

% Late Cuts - Orders

Result: (Numerator / Denominator) * 100

Denominator:	Numerator:
Count of Hot Cut orders completed	Count of Hot Cut (coordinated loop) orders with lines cut more than 30 minutes after the cut-over window (includes time for notification to CLEC)

Filtered output file: Order Detail

For the details on the above out put filtered file layout refer to File Appendix: 41 File Type: Excel

Formula For: VERIZON

Denominator	Numerator
<div>SELECT COUNT#ORDS) WHERE STATE = NJ</div>	<div>SELECT COUNT#ORDS) WHERE STATE = NJ AND MET = "N"</div>

UNE (Provisioning)

Report Labels: PR-9-08-3520 POTS - Provisioning No Standard

Guidelines: PR-9 - Hot Cuts

Average Duration of Service Interruption

Result: (Numerator / Denominator)	
Denominator:	Numerator:
Count of early cuts plus defective cuts plus cuts with service interruption reported within 7 days of cut.	Duration time from identification of Early cut Defective cut Report of installation trouble for service interruption reported within 7 days of cut To Closure of trouble reported in each case.

Filtered output file: FCC File Extract Def

For the details on the above out put filtered file layout refer to File Appendix: 23 File Type: Text

Formula For: CLEC

Denominator	Numerator
<div>SELECT COUNT(*) WHERE AFLAG3 = H AND CAT = 1 AND FDIS >= 0300 AND FDIS <= 0599 AND I7 = X AND R30 <> X</div>	<div>SELECT SUM(CLDT, CLEAR) - SUM(RDT, RECT) WHERE AFLAG3 = H AND CAT = 1 AND FDIS >= 0300 AND FDIS <= 0599 AND I7 = X AND R30 <> X</div>

UNE (Provisioning)

Report Labels:

PR-9-09-3520

POTS - Provisioning

No Standard

Guidelines:

PR-9 - Hot Cuts

% Supplemented or Cancelled Orders

Result: (Numerator / Denominator) * 100

Denominator:	Numerator:
Count of Hot Cut orders completed plus cancelled orders	Count of Hot Cut orders cancelled or supplemented at BA Request

Filtered output file: Order Detail

For the details on the above out put filtered file layout refer to File Appendix: 41 File Type: Excel

Formula For: CLEC

Denominator	Numerator
<div>SELECT COUNT(#ORDS) WHERE STATE = NJ</div>	<div>SELECT COUNT(#ORDS) WHERE STATE = NJ AND CNR CODE IN (7, 5)</div>